FED. SUP CLASS
6640

REVIEW ACTIVITY: DM, GL, 82

USER ACTIVITY: DP, ME, NM



PART NUMBER	STANDARD TAPER SIZE	DIMENSIONAL DATA mm		
		*BOTTOM DIAMETER	GROUND LENGTH	GAGE POINT DIAMETER
MS36366-3	9	8.00	14.0 ± 1.0	9.40
MS36366-4	13	12.00	14.0 ± 1.0	13.40
MS36366-5	16	15.00	15.0 ± 1.0	16.50
MS36366-6	19	18.00	17.0 ± 1.0	19.70
MS36366-7	22	20.00	20.5 ± 1.5	22.05
MS36366-1	27	25.00	21.5 ± 1.5	27.15
MS36366-2	32	30.00	21.5 ± 1.5	32.15
MS36366-8	38	35.00	30.0 ± 2.0	38.00

*Nominal dimension

MATERIAL: Borosilicate glass in accordance with Federal Specification DD-G-541, Type I, Grade A or B.

DESIGN: Stoppers shall be of the solid pennyhead type and in accordance with the Standard Taper specifications of the U. S. Department of Commerce Standard CS21.

NOTES:

1. Stoppers of this type are generally used in flasks and separatory funnels.
2. For design feature purposes, this standard takes precedence over procurement documents referenced herein.
3. Referenced documents shall be of the issue in effect on date of invitations for bid.

☆ U. S. GOVERNMENT PRINTING OFFICE: 1970-433-691/1838

APPROVED 18 JUN 1965 REVISED (A) 17 AUG 1970

(A) ENTIRE STANDARD REVISED

P A.	MU	TITLE	MILITARY STANDARD
Other Cust	MS 82	STOPPERS, BOTTLE glass, pennyhead, std taper	MS 36366
Procurement Specification DD-S-750		SUPERSEDES	SHEET 1 OF 1

This military standard is approved by the Department of Defense and is mandatory on all activities. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

DD FORM 672 (Coordinated)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:39Z
Check the source to verify that this is the current version before use.