MIL-B-8242C
1 February 1979
SUPERSEDING
MIL-B-8242B
1 July 1970

MILITARY SPECIFICATION

BELT, SAFETY, LAP, TROOP, TYPE C-3A

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers a detachable aircraft lap safety belt designated Type C-3A.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

DDD-L-20	Label; For Clothing, Equipage, And Tentage, (General Use)
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-636	Boxes, Shipping, Fiberboard
PPP-B-676	Boxes, Setup

Military

MIL-P-116	Preservation-Packaging, Methods Of

Beneficial comments (recommendations, additions, deletions) and any pertient data which may be of use in improving this document should be addressed to: HQ AFLC CASO/LODS, Federal Center, Battle Creek MI 49016 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1680

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

STANDARDS

Military

MIL-STD-105	Sampling Procedures And Tables for Inspection By Attributes
MIL-STD-129	Marking For Shipment And Storage
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking, And Waterproofing: With Appropriate Test Methods

DRAWING

US Air Force

56F589	Belt - Safety, Lap,Troop, Type C-3A, Assembly Of

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for approval shall apply.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 General requirements. The requirements specified on Drawing 56F589 shall form a part of this specification. When the drawing requirements conflict with this specification, the requirements of this specification shall govern.

3.2 Strength. The belt shall be capable of withstanding a proof load of 1,000 pounds and a static load of 2,500 pounds without weakening of the webbing or stitching, slippage of the webbing through the adjusting hardware, or deformation of the metal fittings.

3.3 Marking. Each half of the belt shall be marked by means of a label sewn on the belt in the location shown on Drawing 56F589. These labels shall be in accordance with DDD-L-20, type II, class 11, except that the lettering shall consist of white letters on a black background. The lettering shall read in the direction of the warp of the label. The following information shall be included on the label:

Belt, Safety, Lap, Troop

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

Type C-3A
Specification MIL-B-8242C
Stock No.
Contract or Order No.
Date of Manufacture
Manufacturer's Name or Trademark

3.4 Workmanship. The belt, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Quality conformance inspection. The quality conformance inspection shall consist of:

a. Individual inspection

b. Sampling inspection

4.2.1 Individual inspection. Each belt produced shall be subjected to the following examination and test:

a. Examination of product (see 4.3.1)

b. Proof load (see 4.3.2)

4.2.2 Sampling inspection. Two belts shall be selected at random from each lot of 200 belts, or fraction thereof, on the order and subjected to the maximum load test as described in 4.3.3.

4.2.2.1 Lot. A lot shall consist of belts manufactured under essentially the same conditions and submitted for inspection at substantially the same time.

4.3 Inspection methods.

4.3.1 Examination of product. The belt shall be examined to determine conformance to this specification in accordance with Tables I, II, and III. A selected defect found in a sample shall cause rejection of the lot regardless of lot size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

4.3.2 Dimensional examination. Any measurement deviating from normal dimension and tolerance in this drawing shall be scored as measurement defect.

TABLE I. Classification of defects for visual examination.

Defects	Major	Minor
Any hole, scissor or knife cut, tear, patch or mend	X	
Any weakening material defect	X	
Any needle chew	X	
Any component not as specified (type, size, color, etc.)	X	
Incorrect assembling or improper positioning of components	X	
Any components omitted, missing, malformed, fractured or otherwise damaged	X	
Sharp edge or burr on any component	X	
Incorrect or incomplete marking		X
Any functioning part that works with difficulty	X	
Missing stitches, patterns not as specified	X	
Gauge of stitching not within range specified		X
Backstitching missing, continuous skipped stitches	X	
Number stitches per inch exceeding minimum or maximum specified		X
Not type stitch or thread size specified	X	
Loose tension resulting in loosely exposed loops of lower or top thread (score only when condition exists on more than 1/2 the length of seam		X
Loose tension resulting in a loose seam		
a. Less than 3/4 inch		X
b. 3/4 inch or more	X	
Tight tension (stitches break when normal strain is applied in the direction of the seam or stitching)	X	

* Lightly frayed area and separation of the webbing yarn caused by the stitching pattern covering areas of different thickness shall not be scored as a defect.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

TABLE II. Selected Defects

Any belt in the sample which shows evidence of weakening of the webbing or stitching, slippage of the webbing through the metal adjusters, or deformation of any metal fittings in the belt assembly due to the proof load test. Any belt in the sample that show evidence of the above, shall be tested in accordance with para. 4.3.3.

TABLE III. Sample Size and Acceptance Criteria.

Inspection	Method	Inspection Level	Acceptable Quality Level AQL
Visual Exam	Tbl. I, II & Para. 4.3.1, MIL-B-8242	Inspection Level II MIL-STD-105	Majors - 1.0DHU Totals (Major plus Minor) AQL 4.0DHU Selected Accept on 0, reject lot on 1.
Dimensional	Para. 4.3.2	S-3	AQL 10.0 (1 Class)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

4.3.3 Proof load. The belt shall be assembled in a testing machine by attaching the end snap metal fittings to one movable and one stationary head, with the quick-release latch assembly closed. A proof load of 1,000 pounds shall be applied. There shall be no evidence of weakening of the webbing or stitching, slipping of the webbing through the metal adjusters, or deformation of any metal fittings in the belt assembly.

* 4.3.4 Maximum load. The belt shall be assembled in the testing machine (as described in 4.3.3) and subjected to a static load of 2,500 pounds. Any evidence of weakening of the webbing or stitching, slippage of webbing through the adjusting hardware, or deformation of the metal fittings shall be cause for rejection of the lot. Belts and components thereof which have been subjected to the maximum load test shall be considered unfit for further use.

* 4.4 Examination of preparation for delivery requirements. An examination shall be made to determine whether the packaging, packing and marking comply with the Section 5 requirements. Defects shall be scored in accordance with table IV. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be sealed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

* TABLE IV. Classification of preparation for delivery defects

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing. Any component damaged, affecting serviceability.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling or bulging or distortion of containers.
Content	Number of units in interior container is more or less than required. Number of interior containers per shipping container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Unless otherwise specified in the contract or order, each belt shall be preserved and packaged in accordance with MIL-P-116, method III, one each in a unit container conforming to PPP-B-676.

5.1.2 Level C. Unless otherwise specified in the contract or order, belts shall be preserved and packaged in a manner to provide adequate protection against deterioration or damage during shipment from the supply source to the first receiving activity.

5.2 Packing. Packing shall be level A, B or C, as specified (see 6.2).

5.2.1 Level A. Unless otherwise specified in the contract or order, belts preserved and packaged as specified in 5.1.1 shall be packed in exterior shipping containers shall be of uniform shape and size and shall contain identical quantities. Gross weight of each container shall not exceed 200 pounds.

5.2.2 Level B. Belts preserved and packaged as specified in 5.1.1 shall be packed in exterior shipping containers conforming to PPP-B-636, class weather-resistant. Exterior shipping containers shall be of minimum cube and tare consistent with the protection required. Insofar as practicable, exterior shipping containers shall be of uniform shape and size and shall contain identical quantities. The gross weight of each shipping container shall not exceed the weight limitation of the specification. Containers shall be closed and strapped in accordance with the specification and appendix thereto. Shipping containers shall meet the special requirements table of PPP-B-636, as applicable.

5.2.3 Level C. Packages that require overpacking for acceptance by the carrier shall be placed in exterior-type shipping containers in a manner that will insure safe transportation at the lowest rate to the point of delivery. Containers shall comply with Uniform Freight Classification Rules or regulations of other common carriers as applicable to the mode of transportation.

5.3 Physical protection. Cushioning, blocking, and bracing, shall be in accordance with MIL-STD-1186, except that for domestic shipments, waterproofing requirements for cushioning materials and containers shall be waived. Drop tests of MIL-STD-1186 shall be waived when the item is preserved, packaged, and packed for immediate use or when the drop tests of MIL-P-116 are applicable.

5.4 Marking. Interior and exterior containers shall be marked in accordance with MIL-STD-129. The nomenclature shall be as follows: Belt, Safety, Lap, Troop, Type C-3A, Specification MIL-B-8242D. Part No. 56F589.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The type C-3A safety belt covered by this specification is intended for use to secure troop personnel in their aircraft seats and is easily and quickly detachable if cargo only is to be carried in the aircraft.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.

b. Levels of preservation, packaging, and packing (see 5.1 and 5.2).

* 6.3 Reclaimed materiels. The use of reclaimed materiels shall be encouraged to the maximum extent possible.

6.4 Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Air Force - 99
Army - AV
Navy - AS

Preparing Activity:
Air Force - 99

Project No. 1680-0442

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER (Number) AND TITLE
MIL-B-8242C 1 FEB 1979

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1 ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY (Printed or typed name and address — Optional)

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 Replaces edition of 1 Jan 72 which may be used. S/N 0102-LF-001-4260

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DoD-316

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

HQ AFLC
CASO/LODS
Federal Center
Battle Creek, MI 49016

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:18Z
Check the source to verify that this is the current version before use.