MILITARY SPECIFICATION

COMPASS, MAGNETIC, SLAVED GYRO, TYPE J-4

This amendment forms a part of MIL-C-8412B(USAF), dated 18 August 1969, and is approved for use within the Department of the Air Force and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Delete "2.1" and add:
"2.1 Government documents."

* Add:
"2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issued of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation.

Under SPECIFICATIONS, Federal: Delete: "L-P-378", "QQ-P-416", "PPP-C-843", and
* "PPP-F-320", Add: PPP-B-601 Boxes, Wood, Cleated Plywood".

* Under SPECIFICATIONS, Military: Change: "MIL-E-1E" to "MIL-E-1", and delete: "MIL-I-5126" and "MIL-E-5272", add: "MIL-I-6424 Indicator, Induction Compass, Type V-8", "MIL-B-26503 Dector, Magnetic Azimuth, And Compensator, Detector, Magnetic Azimuth" and "MIL-C-83488 Coating, Aluminum, ION Vapor Deposited".

Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

Under SPECIFICATIONS, Military: Delete: "MIL-D-1000" and "MIL-C-7769".

Under STANDARDS, Military: Add:
"MIL-STD-100 Engineering Drawing Practices
* MIL-STD-129 Marking For Shipment And Storage
* MIL-STD-810 Enviromental Test Methods and Engineering Guidelines."

AMSC N/A FSC 6605

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:24Z
Check the source to verify that this is the current version before use.

* Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

ASTM D3951 Packaging, Commercial

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103).

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services)."

3.1 Change "Preproduction" to "First Article".

PAGE 3

3.2.1 Under "DESCRIPTION" and "SPECIFICATION" delete "Gyroscope, Rate CN-436/AJN-3 MIL-C-25773". Delete "Indicator, Directional Gyro, Magnetic Compass, Type V-7A MIL-I-5126" and substitute "Indicator, Induction Compass, Type V-8 MIL-I-6424". Delete "Detector, Magnetic Azimuth DT-309/AJN MIL-D-25531" and substitute "Detector, Magnetic Azimuth, And Compensator, Detector, Magnetic Azimuth MIL-D-26503".

3.4.1 Lines 5 and 6: Delete "cadmium plating" and substitute "protection".

PAGE 4

* Add:
"3.4.5 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item."

PAGE 5

3.5.2.1 Delete and substitute the following:
"3.5.2.1 Maximum requirements. The compass shall operate on 115V, 3-phase, 400 Hz and 27.5V DC and the power demand shall not exceed 100 volt-amperes AC and 28 watts DC."

PAGE 6

3.5.5 Line 3: Delete "excepted" and substitute "expected".

PAGE 11

3.7.2.3.1 Line 3: Delete "MIL-E-1E" and substitute "MIL-E-1".

PAGE 12

3.7.2.7 Line 5: Delete "GD" and substitute "DG".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:24Z
Check the source to verify that this is the current version before use.

PAGE 15

* 3.7.3.4 Line 7: delete "Type V-7A indicator" and add: "Type V-8 indicator".

PAGE 16

3.8 Line 3: Delete "MIL-D-1000" and substitute "MIL-STD-100".

PAGE 17

* 3.9.7.2 Delete and add:
"3.9.7.2 Steel parts. Steel parts shall be coated with ion vapor deposited aluminum, where practicable, in accordancce with MIL-C-83488, type I or II as applicable and of a class that is adequate to achieve the degree of protection required. Other protective coating, in lieu of MIL-C-83488, may be used if demonstrated to be satisfactory and approved by the preparing activity. Cadmium plating must be avoided when satisfactory alternative processes can be used."

PAGE 20

* 4.5.4 Line 2 delete: "MIL-E-5272" and add: "MIL-STD-810".

* 4.5.7 Line 1 and 5 delete: "Type V-7A indicator" and add: "Type V-8 indicator".

PAGE 27

* 4.6.22.1 Line 2 delete: "Type V-7A indicator" and add: "Type V-8 indicator".

PAGE 30

4.6.27a Delete "80 Volt-ampreres and 15 watts" and substitute "135 volt-amperes and 30 watts".

4.6.27b Delete "75 volt-amperes and 15 watts" and substitute "100 volt-amperes and 28 watts".

PAGE 32

* 4.6.31.3 Line 2 delete: "MIL-E-5272" and add "MIL-STD-810".

* 4.6.31.4 Line 2 delete: "MIL-E-5272" and add "MIL-STD-810".

PAGE 33

* 4.6.33.1 Line 3 delete: "MIL-E-5272" and add "MIL-STD-810".

* 4.6.33.1a Line 4 delete "Type V-7A indicator and add: "Type V-8 indicator".

PAGE 34

Delete Sectin 5 in its entirety and add:

"5 PACKAGING

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:24Z
Check the source to verify that this is the current version before use.

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Compass shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Compass shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each compass shall be in quantity unit packs of one each in accordance with Method ICI of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G's established for the compass when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Compass shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The industrial preservation of compass shall be in accordance with ASTM D3951.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Compass packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistant with the protection required.

5.2.2 Level B. Compass packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

5.2.3 Level C. Packing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged compass shall be packed in accordance with ASTM D3951.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:24Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
AIR FORCE - 99

Preparing Activity:
AIR FORCE - 71

Project Number:
6605 - F352

☆U.S. GOVERNMENT PRINTING OFFICE: 1986—605-036/44756

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:24Z
Check the source to verify that this is the current version before use.