MIL-G-8266C(USAF)
AMENDMENT 2

13 July 1959

Superseding
AMENDMENT 1
23 September 1958

MILITARY SPECIFICATION

GAGE, LIQUID OXYGEN CONTENT, DIAL INDICATING,
5-LITER 70-PSI CONVERTER

This amendment forms a part of Military Specification MIL-G-8266C(USAF) dated 29 July 1957.

Pages 1 and 2, section 2: Delete entirely and substitute:

"2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification:

SPECIFICATIONS

Federal

BB-O-925	Oxygen, 99.5 Percent, Gas and Liquid
PPP-B-585	Boxes, Wood, Wirebound
PPP-B-591	Boxes, Fiberboard, Wood-Cleated
PPP-B-601	Boxes, Wood, Cleated-Plywood
PPP-B-621	Boxes, Wood, Nailed and Lock-Corner
PPP-B-636	Boxes, Fiber
PPP-T-60	Tape; Pressure Sensitive Adhesive, Waterproof--For Packaging and Sealing

Military

MIL-P-116	Preservation, Methods of
MIL-B-138	Boxes, Wood, Fiberboard-Lined For Overseas Shipment (For Weight Contents Not Exceeding 500 Pounds)
MIL-D-5028	Drawings and Data Lists; Preparation Of Manufacturers' (For Production Aeronautical and Associated Equipment)
MIL-N-6011	Nitrogen; Liquid And Gas
MIL-P-7105	Pipe Threads, Taper, Aeronautical National Form, Symbol ANPT
MIL-T-9107	Test Reports, Preparation Of

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:19Z
Check the source to verify that this is the current version before use.

MIL-B-10377	Box, Wood, Cleated, Veneer, Paper Overlaid
MIL-L-10547	Liners, Case, Waterproof
MIL-L-25142	Luminescent Material, Fluorescent
MIL-L-25567	Leak Test Compound, Oxygen Systems

STANDARDS

Military

MIL-STD-129	Marking For Shipment and Storage
MIL-STD-130	Identification Marking of U. S. Military Property
MS33548	Case, Instrument, 1-7/8 Dial, Standard Dimensions For
MS33586	Metals, Definition of Dissimilar

Air Force-Navy Aeronautical

AND10053	Bosses; Pipe-Thread, Internal - Standard Dimensions For

PUBLICATION

Air Force-Navy Aeronautical Bulletin

No. 143	Specifications and Standards; Use of

(Copies of documents required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Page 3, paragraph 3.3.1: Delete the first sentance and substitute: "Metals shall be of the corrosion-resistant type or suitably treated to resist corrosion due to fuels, salt spray, or atmospheric conditions likely to be met in storage or normal service."

Page 3: Add the following:
"3.3.1.1 Dissimilar Metals.- Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MS33586."

Page 5, figure 1: Delete "BOSSES IN ACCORDANCE WITH DRAWING AND10053" and substitute "BOSSES IN ACCORDANCE WITH ANA STANDARD 10053".

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:19Z
Check the source to verify that this is the current version before use.

Page 7, paragraph 3.6: Delete and substitute:
"3.6 Interchangeability.- All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The drawing number requirements of MIL-D-5028 shall govern changes in the manufacturer's part numbers."

Page 7, paragraph 3.9.3: Delete and substitute:
"3.9.3 Cover Glass.- The cover glass shall withstand a pressure of 600 pounds per square inch applied to the inside of the cover glass when tested as specified in 4.5.4.

Page 8, paragraph 3.9.4: Add the following sentence:
"This damping shall be accomplished by means of suitable filters in both the gas and the liquid ports of the gage."

Page 8, paragraph 3.9.5: In line 4, delete "350 and 15" and substitute "150 and 45".

Page 8, paragraph 3.9.8: Add to the last line "for not less then 3 hours".

Page 10, paragraph 4.3.2, line 4: Delete "Government activity specified in 6.3" and substitute "procuring activity".

Page 10, paragraph 4.3.3: Delete and substitute:
"4.3.3 Preproduction Test Sample for the Procuring Activity.- Along with the preproduction test report, the contractor shall submit one sample to the procuring activity."

Page 11, paragraph 4.5.1, lines 1 and 2: Delete "Unless otherwise specified by the procuring activity".

Page 11, paragraph 4.5.5: In line 3, delete "requiring" and substitute "required". Delete sentence 4 entirely. In the last line, delete "addition of".

Page 12, paragraph 4.5.7: In line 6, delete "350" and substitute "150". In line 12, delete "15" and substitute "45".

Page 12, paragraph 4.5.8, line 6: Delete "15" and substitute "45".

Page 13, paragraph 4.5.10, line 4: Delete "at least 3 hours" and substitute "not less than 3 hours".

Pages 13 and 14, section 5: Delete and substitute:
"5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging

5.1.1 Level A.- Gages shall be preserved in accordance with MIL-P-116, method IA, without the use of a contact preservative.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:19Z
Check the source to verify that this is the current version before use.

5.1.2 Level C.- Gages shall be preserved and packaged to provide adequate protection against corrosion and physical damage during shipment from supply source to the first receiving activity for immediate use. Contact preservatives shall not be used.

5.2 Packing

5.2.1 Level A.- Gages, preserved and packaged as specified in 5.1.1, shall be packed in overseas type shipping containers conforming to the requirements of PPP-B-585, PPP-B-591, PPP-B-601, PPP-B-636, MIL-B-138, or MIL-B-10377. As far as practical, containers shall be of uniform shape and size, be of minimum cube and tare consistent with the protection required, and contain identical quantities. The gross weight of the container shall be limited to approximately 200 pounds. Containers shall be provided with a case liner conforming to MIL-L-10547, and sealed in accordance with the appendix thereto. Containers shall be closed and strapped in accordance with the applicable container specification and appendix thereto. Case liners will not be required when the interior or exterior containers conform to PPP-B-636, class 2 or 3, and are sealed at all joints and seams including the manufacturer's joints with tape conforming to PPP-T-60.

5.2.2 Level B.- Gages, preserved and packaged as specified in 5.1.1, shall be packed in domestic type shipping containers conforming to PPP-B-585, PPP-B-601, PPP-B-621, PPP-B-636, or MIL-B-10377. As far as practical, containers shall be of uniform shape and size and contain identical quantities. Containers shall be of minimum cube and tare consistent with the protection required. The gross weight of each container shall be limited to approximately 500 pounds. Containers shall be closed and strapped in accordance with the applicable container specification or appendix thereto.

5.2.3 Level C.- Gages, preserved and packaged as specified in 5.1.2, shall be packed to afford adequate protection against damage during direct shipment, from supply source to the first receiving activity for immediate use. Containers shall comply with Consolidated Freight Classification rules or other common carrier regulations applicable to the mode of transportation.

5.3 Marking

5.3.1 Normal Markings.- The interior packages and the exterior shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:19Z
Check the source to verify that this is the current version before use.

5.3.2 Precautionary Marking.- "Do not allow oil of any kind to be used on or about oxygen gage."

Page 15, paragraph 6.2: Under "a" and "b", delete entirely and substitute:

"a. Title, number, and date of this specification
b. Preproduction requirements
c. Levels of preparation for delivery required."

Page 15, paragraphs 6.3, 6.3.1, 6.3.2, 6.3.3, 6.3.4, and 6.3.5: Delete entirely.

WCLDAS
JMA/jma

GPO 823969

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:19Z
Check the source to verify that this is the current version before use.