MILITARY SPECIFICATION

Vacuum Pump, Rotary, Power Driven

This amendment forms a part of Military Specification MIL-V-8419A (USAF) dated 24 February 1964.

PAGE 1

2.1 Military Specification: Delete the following:

| | |
|---|---|
| "MIL-P-7105 | Pipe threads, Aeronautical |
| MIL-S-7742 | Screw threads, Aeronautical |
| MIL-T-9107 | Test Reports, Preparation of |
| MIL-E-7729 | Protective Coatings" |

2.1 Specifications, Standards: Add following,

| | |
|---|---|
| "FED-STD-595 | Colors |
| MIL-STD-831 | Test Reports, Preparation of |
| MIL-STD-882 | Systems Safety Program for Systems and Associated Subsystems and Equipment; Requirements for" |

PAGE 2

Add paragraph 2.2, Other publications,

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or the request for proposal shall apply.

American Society of Mechanical Engineers, Unfired Pressure Vessel Code

American Society Of Mechanical Engineers Power Test Code
19.5.4 Supplement on Instruments and Apparatus - Part 5, Chapter 4. Flow measurement by means of standardization nozzles and orifice plates.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York 17, NY)

National Bureau of Standards

Handbook H-28 Screw Thread Standards of Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)"

"Department of Labor, Occupational Safety and Health Administration

Occupational Safety and Health Act (OSHA) Standards with Supplemental Revisions

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)"

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:24Z
Check the source to verify that this is the current version before use.

PAGE 2

Add new paragraph:

"3.3.2 Reclaimed Materials. Recycled and recovered raw materials shall be used to the maximum extent possible in lieu of virgin raw materials as long as these materials do not jeopardize the intended use and fully comply with all contract requirements. Materials used shall be free from defects which would adversely affect the performance or maintainability of individual components or the overall assembly. Materials not specified herein shall be of the same quality used for the intended purpose in commercial practice. None of the above shall be interpreted to mean that the use of used or rebuilt products will be allowed."

PAGE 3

3.4.3: Delete and substitute the following,

"3.4.3 Safety.

Add new paragraph:

3.4.3.1 Occupational Safety and Health Act (OSHA). The vacuum pump shall be consistent with applicable "OSHA" Standards.

Add new paragraph:

3.4.3.2 Category I and II hazards. All equipment furnished under this specification shall be analyzed for Category I and Category II hazards as defined in MIL-STD-882. Any hazard so identified shall be brought to the attention of the procuring agency with recommended action for satisfying safety requirements. Action order of precedence shall be as specified in MIL-STD-882, para 5.4.2."

PAGE 5

3.15.1: Delete "MIL-P-7105" and substitute "Handbook H-28."

3.16: Delete "MIL-S-7742 and substitute "Handbook H-28."

4.4.1: Delete "MIL-T-9107" and substitute "MIL-STD-831."

3.19: Delete and substitute the following:

"3.19 Protective Coatings. The portions of the pump normally painted shall be cleaned, treated, and painted in accordance with the manufacturer's standard practice and the finish shall be gray, Color No. 16473, according to FED-STD-595."

Custodian:
Air Force - 99

Preparing Activity:
Air Force - 99

Project Number:
4310-F084



Source: https://assist.dla.mil -- Downloaded: 202610-17T10:24Z
Check the source to verify that this is the current version before use.