INCH-POUND
MIL-PRF-15160/64E
17 August 2006
SUPERSEDING
MIL-PRF-15160/64D
13 February 1998

PERFORMANCE SPECIFICATION SHEET

FUSES, INSTRUMENT, POWER, AND TELEPHONE (NONINDICATING), STYLE F64

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-15160.





ALTERNATE CONSTRUCTION WITH TERMINALS ATTACHED INTERNAL TO THE TUBE

Inches	mm
.003	0.08
.035	0.89
.062	1.57
.188	4.78
.125	28.58
1.188	30.20
1.375	34.93
1.688	42.88
1.875	47.63
4.12	104.6
7.125	180.98

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. The length of the cylindrical body may be less than the indicated value if other acceptable interference means (pins through blades, collars, and so forth) are provided to prevent mounting the fuse in a fuseholder that will accommodate a fuse rated in the next lower bracket of current ratings.

FIGURE 1. Style F64, characteristic C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Interface and physical dimensions: See figure 1.

Case: Glass melamine.

Knifeblade: Brass, copper, bronze, or copper alloy.

Finish: Nickel or bright alloy plate, silver plated when specified.

Terminal strength: Method 211 of MIL-STD-202, test condition E, 5 pound-inch torque.

Electrical:

Current rating: See table I.

Current carrying capacity: 110 percent of rated current.

Voltage rating: See table I.

Characteristic: Characteristic C only.

Overload interrupt: Within 2 hour at 135 percent of rated current; and within 8 minutes at 200 percent.

Short circuit interrupt: 200,000 A at 500 V ac (symmetrical), 150,000 A at 500 V dc.

Shock: Method 207 of MIL-STD-202, HI shock.

Vibration: Method 204 of MIL-STD-202, test condition A (except 5g, 500 Hz).

Type designation: Type designation shall be as specified in table I.

TABLE I. Type designation. 1/

Style	Characteristic	Voltage	Current
F64	C	500V	110A
F64	C	500V	125A
F64	C	500V	150A
F64	C	500V	175A
F64	C	500V	200A

1/ For silver plated terminals, the designator "S" is added after the current rating.

Temperature rise: Temperature rise shall be not greater than the values shown in table II.

TABLE II. Allowable temperature rise.

Casing or body		Terminal	
Thermometer	Thermocouple	Thermometer	Thermocouple
50°C	90°C	60°C	90°C

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:49Z
Check the source to verify that this is the current version before use.

VERIFICATION:

Qualification inspections: The number of qualification samples required shall be:

a. 24 samples maximum current rating of each voltage and design.

b. 24 samples minimum current rating of each voltage and design.

NOTE: If labels are used, five additional samples of any rating are required.

Sample size: The number of group III samples shall be twelve samples each of the maximum and minimum current ratings. The samples shall be divided as shown in table III.

TABLE III. Short circuit test.

Number of samples	Short circuit current	Test voltage
3	5,000 A	500 V ac 1/
3	200,000 A	500 V ac 1/
3	5,000 A	500 V dc
3	150,000 A	500 V dc

1/ A 600 volt ac test voltage may be used.

Group C inspection: Group C inspection shall be performed on short circuit current ratings of 5,000 A at 500 V ac; 200,000 A at 500 V ac; and 5,000 A at 500 V dc. The 150,000 A at 500V dc short circuit current test is not required to be performed for group C testing.

INSPECTION ROUTINE:

AC short circuit test: AC short circuit tests shall be performed at the currents shown in table II at not less than 500 volts, single phase, and not greater than 20 percent power factor, lagging. The current shall be applied within plus or minus 10 degrees of the zero point of the voltage wave.

DC short circuit test: DC short circuit tests shall be performed at the currents shown in table II at not less than 500 volts. The rate of rise shall be between 25,000,000 and 30,000,000 amperes per second.

Cross-reference: For applicable cross-reference see table IV. The existing stocks of superseded items may be used. When exhausted, the superseding parts shall be used.

TABLE IV. Cross-reference.

Superseding number	Superseded numbers for CAGE	
	81349	96906
F64C500V110A	F64H110R0C	MS15253-1
F64C500V125A	F64H125R0C	MS15253-2
F64C500V150A	F64H150R0C	MS15253-3
F64C500V175A	F64H175R0C	MS15253-4
F64C500V200A	F64H200R0C	MS15253-5

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:49Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-15160, this document references the following:

MIL-STD-202

The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - CR
Navy - SH
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5920-2005-023)

Review activities:
Army - AR, AT, CR4, MI
Navy - AS, CG, MC, OS, YD
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:49Z
Check the source to verify that this is the current version before use.