The documentation and process conversion measures necessary to comply with this document shall be completed by 24 June 2023.

INCH-POUND
MIL-PRF-19500/578R
w/AMENDMENT 2
24 March 2023
SUPERSEDING
MIL-PRF-19500/578R
w/AMENDMENT 1
16June 2020

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, SWITCHING, TYPES 1N6638, 1N6642, 1N6643, QUALITY LEVELS JAN, JANTX, JANTXV, JANS, JANHC, AND JANKC

This specification is approved for use by all Departments and Agencies of the Department of Defnse.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for switching diodes. Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

* 1.2 Package outlines and die topography. The device packages for the encapsulated device types are as follows: DO-35 in accordance with figure 1, U and US in accordance with figure 2, UB in accordance with figure 3, UB2 in accordance with figure 4, and surface mount versions UMC in accordance with figure 5. The dimensions and topography for JANHC and JANKC unencapsulated die are as follows: A version die in accordance with figure 6, B in accordance with figure 7, C in accordance with figure 8, D in accordance with figure 9, E in accordance with figure 10, and F in accordance with figure 11.

1.3 Maximum ratings. Unless otherwise specified T_A = +25°C.

Types	V_{BR}	V_{RWM}	$I_{O(PCB)}$ T_A=75° (1) (2)	I_{FSM} t_p = 1/120 s	$R_{\theta JL}$ L = .375 inch (9.53 mm) (1)	$R_{\theta JEC}$ L = 0 (1) (2)	$R_{\theta JA(PCB)}$ (2) (3) (5)	$R_{\theta JSP}$ (1) (2) (4) (5)	T_{STG} and T_J
	V (pk)	V (pk)	mA	A (pk)	°C/W	°C/W	°C/W	°C/W	°C
1N6638	150	125	300	2.5	150		250		-65 to +175
1N6638U, 1N6638US	150	125	300	2.5		40	250		-65 to +175
1N6638UB, UBCC, UBCA, UBD	150	125	300	2.5		40	325	100	-65 to +200
1N6642	100	75	300	2.5	150		250		-65 to +175
1N6642U, 1N6642US	100	75	300	2.5		40	250		-65 to +175
1N6642UB, UB2, UB2R, UBCA, UBD, and UBCC	100	75	300	2.5			325	100	-65 to +200
1N6643	75	50	300	2.5	150		250		-65 to +175
1N6643U, 1N6643US	75	50	300	2.5		40	250		-65 to +175
1N6643UB, UBCC, UBCA, UBD	75	50	300	2.5		40	325	100	-65 to +200
1N6638UMC	150	125	300	2.5			82	67	-65 to +200
1N6642UMC	100	75	300	2.5			82	67	-65 to +200
1N6643UMC	75	50	300	2.5			82	67	-65 to +200

Comments, suggestions, or questions on this document should be addressed to DLA Land and Maritime, ATTN: VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to Semiconductor@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A
FSC 5961

* DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

* 1.3 Maximum ratings - Continued.

* (1) For temperature-current derating curves, see figure 12 and figure 13.
* (2) See- figure 14, figure 15, figure 16, figure 17, figure 18, figure 19, and figure 20 for thermal impedance curves.
(3) T_A = +75°C for both axial and Metal Electrode Leadless Face diodes (MELF) (U, US) on printed circuit board (PCB), PCB = FR4 - .0625 inch (1.59 mm) 1-layer 1-Oz Cu, horizontal, in still air; pads for U, US = .061 inch (1.55 mm) x .105 inch (2.67 mm); pads for axial = .092 inch (2.34 mm) diameter, strip = .030 inch (0.76 mm) x 1 inch (25.4 mm) long, lead length L ≤ .187 inch (≤ 4.75 mm); $R_{\theta JA}$ with a defined PCB thermal resistance condition included, is measured at I_O = 300 mA dc.
(4) $R_{\theta JSP}$ refers to thermal resistance from junction to the solder pads of the UB and UMC package.
(5) $R_{\theta JA}$ and $R_{\theta JSP}$ for the UMC package were measured with 1.5” x 1.5” PCB, FR4, 1.0 oz copper.

1.4 Primary electrical characteristics. Unless otherwise specified, primary electrical characteristics at T_A = +25°C.

Types (1)	V_{F1} I_F = 10 mA	V_{F2}	I_{R1} V_R = 20 V	I_{R2} V_R = V_{RWM}	I_{R3} V_R = 20 V T_A = +150°C	I_{R4} V_R = V_{RWM} T_A = +150°C	t_{fr} I_F = 200mA	t_{rr} I_{RM} = I_F = 10 mA	C_{T1} V_R = 0
	V dc	V dc	nA dc	nA dc	µA dc	µA dc	ns	ns	pF
1N6638, 1N6638U, 1N6638US, 1N6638UMC	0.8	1.1 (2)	35	500	50	100	20	4.5	2.5
1N6642, 1N6642U, 1N6642US, 1N6642UB, 1N6642UB2, 1N6642UBCA, 1N6642UB2R, 1N6642UBD, 1N6642UBCC 1N6642UBE, 1N6642UMC	0.8	1.2 (3)	25	500	50	100	20	5.0	5.0
1N6643, 1N6643U, 1N6643US, 1N6643UMC	0.8	1.2 (3)	50	500	75	100	20	6.0	5.0

(1) Suffix "U" devices are structurally identical to the suffix "US" devices.
(2) I_F = 200 mA.
(3) I_F = 100 mA.

1.5 Part or Identifying Number (PIN). The PIN is in accordance with MIL-PRF-19500, and as specified herein. See 6.4 for supersession information, 6.5 for the suppliers of die, 6.6 for PIN construction example, and 6.7 for a list of available PINs.

1.5.1 JAN certification mark and quality level.

1.5.1.1 Quality level designators for encapsulated devices. The quality level designators for encapsulated devices that are applicable for this specification sheet from the lowest to the highest level are as follows: The base quality level "JAN", "JANTX", "JANTXV", and "JANS".

1.5.1.2 Quality level designators for unencapsulated devices (die). The quality level designators for unencapsulated devices (die) that are applicable for this specification sheet from the lowest to the highest level are as follows: "JANHC" and "JANKC".

1.5.2 Device type. The designation system for the device types of diodes covered by this specification sheet are as follows.

1.5.2.1 First number and first letter symbols. The diodes of this specification sheet use the first number and letter symbols "1N".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

1.5.2.2 Second number symbols. The second number symbols for the diodes covered by this specification sheet are as follows: "6638", "6642", and "6643".

1.5.3 Suffix symbols. The following suffix letters are incorporated in the PIN in the order listed in the table as applicable:

	A blank first suffix symbol indicates an axial through-hole mount package (see figure 1).
US (1)	Indicates a surface mount, square endcap, package (see figure 2).
UB	Indicates a surface mount UB package (see figure 3).
UB2	Indicates a surface mount UB2 package (see figure 4).
UMC	Indicates a surface mount package (see figure 5).

(1) For this specification sheet, the suffix symbols "US" have superseded suffix symbol "U" to designate square endcap surface mount packages.

1.5.4 Lead finish. The lead finishes applicable to this specification sheet are listed on QPDSIS-19500.

* 1.5.5 Die identifiers for unencapsulated devices (manufacturers and critical interface identifiers). The manufacturer die identifiers that are applicable for this specification sheet are "A", “B”, "C", “D”, “E” and "F".

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.


DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Notes
	in	in	mm	mm	
	Min	Max	Min	Max	
BD	.056	.080	1.42	2.03	2
BL	.130	.180	3.30	4.57	
LD	.018	.022	0.46	0.56	3
LL	1.00	1.50	25.40	38.10	

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Dimension BD shall be measured at the largest diameter.
3. The specified lead diameter applies in the zone between .050 inch (1.27 mm) from the diode body to the end of the lead. Outside of this zone lead shall not exceed BD.

TYPES 1N6638, 1N6642, AND 1N6643.

* FIGURE 1. Physical dimensions (DO-35).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
BD	.070	.085	1.78	2.16
BL	.165	.195	4.19	4.95
ECT	.019	.028	0.48	0.71
S	.003		0.08	


NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Dimensions are pre-solder dip.
3. U-suffix parts are structurally identical to the US-suffix parts.

TYPES 1N6638U, 1N6642U, AND 1N6643U, 1N6638US, 1N6642US, AND 1N6643US

* FIGURE 2. Physical dimensions of surface mount family.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.






Symbol	Dimensions				Symbol	Dimensions			
	in	in	mm	mm		in	in	mm	mm
	Min	Max	Min	Max		Min	Max	Min	Max
BH	.046	.056	1.17	1.42	LS1	.035	.039	0.89	0.99
BL	.115	.128	2.92	3.25	LS2	.071	.079	1.80	2.01
BW	.085	.108	2.16	2.74	LW	.016	.024	0.41	0.61
CL		.128		3.25	r		.008		0.20
CW		.108		2.74	r1		.012		0.31
LL1	.022	.038	0.56	0.97	r2		.022		0.56
LL2	.017	.035	0.43	0.89					

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
* 2. Hatched areas on package denote metallized areas. Pad 4 = shielding, connected to the lid.
* 3. Dimensions are pre-solder dip.

* FIGURE 3. Physical dimensions, surface mount (UB version).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




Symbol	Dimensions				Symbol	Dimensions			
	in	in	mm	mm		in	in	mm	mm
	Min	Max	Min	Max		Min	Max	Min	Max
BH	.046	.056	1.17	1.42	LS	.071	.079	1.80	2.01
BL	.115	.128	2.92	3.25	LW	.016	.024	0.41	0.61
BW	.085	.108	2.16	2.74	r	.008 TYP		0.20 TYP	
CL		.128		3.25	r1	.012 TYP		0.30 TYP	
CW		.108		2.74	r2	.022 TYP		0.56 TYP	
LL1	.022	.038	0.56	0.96	r3	.008 TYP		0.20 TYP	
LL2	.017	.035	0.43	0.89	r4	.012 TYP		0.30 TYP	

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Ceramic package only.
3. Hatched areas on package denote metallized areas. Pad 4 = shielding, connected to the lid.
4. Dimensions are pre-solder dip.

* FIGURE 4. Physical dimensions, surface mount (2 pin UB2 version).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




NOTES:
1. Dimensions are in inches.
2. Millimeters are given for general information only.
3. Hatched areas denote metallized areas.
4. For design reference only.

Ltr.	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
CL	.200	.210	5.080	5.334
CW	.110	.120	2.794	3.048
BL	.243	.253	6.172	6.426
BW	.152	.162	3.861	4.115
R1	.020	.030	0.508	0.762
BCH	.064	.074	1.626	1.880
CH	.042	.052	1.067	1.321
BH	.015	.025	0.381	0.635
BLM	.099	.109	2.515	2.769
LMW	.057	.067	1.448	1.702
PH	.001	.003	0.025	0.076

* FIGURE 5. Physical dimensions of UMC surface mount.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.



BACKSIDE IS CATHODE




Ltr	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
A	.014	.018	0.360	0.460
B	.005	.007	0.120	0.180
C	.008	.012	0.20	0.30

NOTES:

1. Dimensions are in inches. Millimeters are given for general information only.
* 2. The physical characteristics of the die are:
   Metallization:
      Top (anode): Al
      Back (cathode): Au
      Al thickness: 25,000 Å minimum.
      Gold thickness: 4,000 Å minimum.
   Chip thickness: .010 inches (0.25 mm) ±.002 inches (0.05 mm).

FIGURE 6. Physical dimensions JANHCA and JANKCA die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
A	.0130	.0170	0.330	0.432
B	.0059	.0061	0.150	0.155
C	.008	.012	0.20	0.30

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Element evaluation accomplished utilizing TO-5 package.
3. The physical characteristics of the die are:

Metallization:
Top (anode): Al
Back (cathode): Au
Al thickness: 25,000 Å minimum.
Gold thickness: 4,000 Å minimum.
Chip thickness: .010 inches (0.25 mm) ±.002 inches (0.05 mm).

FIGURE 7. Physical dimensions, JANHCB and JANKCB die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.



BACKSIDE IS CATHODE




Ltr	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
A	.016	.020	0.406	0.508
B	.006	.007	0.152	0.178
C	.006	.010	0.152	0.254

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Element evaluation accomplished utilizing UB package.
3. The physical characteristics of the die are:

Metallization:
Top (anode): Al
Back (cathode): Au
* Al thickness: 25,000 Å minimum.
* Gold thickness: 4,000 Å minimum.

FIGURE 8. Physical dimensions, JANHCC and JANKCC die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




Ltr	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
A	.013	.017	0.330	0.432
B	.007	.009	0.178	0.229
C	.008	.012	0.20	0.30

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Element evaluation accomplished utilizing TO-39 package.
3. The physical characteristics of the die are:

Metallization:
Top (anode): Al
Back (cathode): Au
Al thickness: 34,000 Å minimum.
Gold thickness: Ti/Ni/Au (1,200 Å / 1,800 Å / 4,000 Å) nominal.
Chip thickness: .010 inches (0.25 mm) ±.002 inches (0.05 mm).

FIGURE 9. Physical dimensions, JANHCD and JANKCD die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.



BACKSIDE IS CATHODE




Ltr	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
A	.013	.017	0.330	0.432
B	.007	.009	0.178	0.229
C	.008	.012	0.20	0.30

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Element evaluation accomplished utilizing TO-39 package.
3. The physical characteristics of the die are:
   Metallization:
   Top (anode): Al
   Back (cathode): Au
   Al thickness: 34,000Å minimum.
   Gold thickness: Ti/Au (200Å/4,350Å) nominal.
   Chip thickness: .010 (0.25 mm) ±.002 inches (±0.05 mm).

* FIGURE 10. Physical dimensions, JANHCE and JANKCE die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.



BACKSIDE IS CATHODE



Ltr	Dimensions			
	in	in	mm	mm
	Min	Max	Min	Max
A	.016	.020	0.406	0.508
B	.005	.007	0.127	0.178
C	.006	.010	0.152	0.254

NOTES

1. Die Size: .017 x .017 Inch [± .002 Inch] (.432 mm x .432 mm [± .0508mm])
2. Die Thickness: .008 Inch [± .002 Inch] (.203 mm [± .0508mm])
3. Top Metal: Al-Si, 14,400 Å Minimum
4. Back Metal: Au, 5,800 Å Minimum
5. Backside: Cathode
6. Bonding pad: .006 x .006 Inch (.152 mm x .152 mm)

* FIGURE 11. Physical dimensions JANHCF and JANKCF die.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. Abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

* 3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 (DO-35), figure 2 (U and US), figure 3 (UB), figure 4 (UB2), figure 5 (UMC), figure 6 (A version die), figure 7 (B version die), and figure 8 (C version die), figure 9 (D version die) figure 10 (E version die), and figure 11 (F version die).

3.4.1 Lead finish. Lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the acquisition document (see 6.2).

3.4.2 Diode construction. These devices shall be constructed in a manner and using materials which enable the diodes to meet the applicable requirements of MIL-PRF-19500 and this document.

a. All devices except ‘UB’, ‘UB2’, and ‘UMC’ versions shall be of metallurgically bonded, thermally matched, non-cavity, double-plug construction in accordance with the requirements of category I (see MIL-PRF-19500).

b. The ‘UB’ devices shall be eutectically mounted and wire bonded in a ceramic package.

c. The ‘U’ and 'US' version shall be structurally identical to the axial leaded versions except for end-cap lead attachment.

3.5 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in 1.3, 1.4, and table I.

3.6 Electrical test requirements. The electrical test requirements shall be as specified in table I herein.

3.7 Marking. Marking shall be in accordance with MIL-PRF-19500. Manufacturer’s identification and date code shall be marked on the devices. Initial container package marking shall be in accordance with MIL-PRF-19500. The polarity shall be indicated with a contrasting color band to denote the cathode end. The prefixes JAN, JANTX, JANTXV, and JANS can be abbreviated as J, JX, JV, and JS respectively. The part number may be reduced to J6638, JX6638, JV6638, or JS6638. No color coding shall be permitted for part numbering.

3.7.1 Marking of U and US versions. ‘U’ and ‘US’ devices shall be marked with a cathode band as a minimum, or a minimum of three evenly spaced contrasting color dots around the periphery of the cathode end may be used. For ‘U’ and ‘US’ versions only, all marking may be omitted from the device except for the cathode marking. At the option of the manufacturer, ‘U’ and ‘US’ devices may include laser marking on an end-cap, to include part number and lot date code for all levels. JANS devices which are laser marked shall also include serialization. The prefixes JAN, JANTX, JANTXV, or JANS may be abbreviated as J, JX, JV, or JS, respectively. (For example: The part number may be reduced to JS6642). All marking which is omitted from the body of the device, except for polarity and serial numbers, shall appear on the initial container.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

3.7.2 UB devices. ‘UB’ and ‘UB2’ packages do not require polarity marking.

3.7.3 UMC devices. UMC devices shall mark the cathode with a minimum of 4 contrasting dots on the lid.

3.8 Workmanship. Devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500 and as specified herein.

4.2.1 JANHC and JANKC qualification. JANHC and JANKC qualification inspection shall be in accordance with MIL-PRF-19500.

4.2.2 Group E qualification. Group E inspection shall be performed for qualification or re-qualification only. In case qualification was awarded to a prior revision of the specification sheet that did not require the performance of table II tests, the tests specified in table II herein that were not performed in the prior revision shall be performed on the first inspection lot of this revision to maintain qualification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

4.3 Screening.

4.3.1 Screening of encapsulated devices (quality levels JANS, JANTXV, and JANTX only). Screening of packaged devices shall be in accordance with table E-IV of MIL-PRF-19500 and as specified herein. Specified electrical measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screen	JANS level	JANTXV and JANTX level
2	Not required	Not required
3b (1) 3c	Not applicable Thermal impedance (see 4.3.1.2)	Not applicable Thermal impedance (see 4.3.1.2)
4	Not applicable	Not applicable
5	Not applicable for axial leaded parts	Not applicable
6	Not applicable	Not applicable
9	I_{R1}	Not applicable
10	Method 1038 of MIL-STD-750, condition A	Method 1038 of MIL-STD-750, condition A
11	V_{F2}, I_{R1}, and V_{BR}; ΔI_{R1} ±15 nA dc or 100 percent of initial value whichever is greater.	V_{F2} and I_{R1}
12	Required, see 4.3.1.1	Required, see 4.3.1.1
13	Subgroups 2 and 3 of table I herein; $\Delta I_{R1} \leq$ 100 percent of initial reading or 15 nA dc, whichever is greater. $\Delta V_{F2} \leq \pm 0.030$ V dc (scope display, see 4.5.3).	Subgroup 2 of table I herein; $\Delta I_{R1} \leq$ 100 percent of initial reading or 15 nA dc, whichever is greater. $\Delta V_{F2} \leq \pm 0.030$ V dc (scope display, see 4.5.3).

(1) Shall be performed anytime after temperature cycling, screen 3a; JANTX and JANTXV levels do not need to be repeated in screening requirements.

4.3.1.1 Power burn-in conditions. Power burn-in conditions are as follows (see 4.5.1): Method 1038 of MIL-STD-750, condition B. V_R = rated V_{RWM}; f = 50 - 60 Hz; I_O(min) or $I_{F(min)}$ = $I_{O(PCB)}$. T_A = 75°C maximum. The maximum current density of small die shall be submitted to the qualifying activity for approval. With approval of the qualifying activity and preparing activity, alternate burn-in criteria (hours, bias conditions, and mounting conditions) may be used for JANTX and JANTXV quality levels. A justification demonstrating equivalence is required. In addition, the manufacturing site's burn-in data and performance history will be essential criteria for burn-in modification approval.

* 4.3.1.2 Thermal impedance measurements. The thermal impedance measurements shall be performed in accordance with method 3101 or 4081 of MIL-STD-750, as applicable, using the guidelines in that method for determining I_H I_M, and t_{MD}. t_H shall be 10 ms maximum. The thermal impedance limit shall comply with the thermal impedance graphs in figure 14, figure 15, figure 16, figure 17, figure 18, figure 19, and figure 20 (less than or equal to the curve value at the same t_H time) and shall be less than the process determined statistical maximum limit as outlined in method 3101 or 4081 of MIL-STD-750, as applicable. See group E, subgroup 4 of table II herein.

4.3.2 Screening (JANHC and JANKC). Screening of JANHC and JANKC die shall be in accordance with appendix G of MIL-PRF-19500. Burn-in duration for the JANKC level follows JANS requirements; the JANHC follows JANTX requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-V of MIL-PRF-19500, table I herein, and as specified herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in tables E-VIA (JANS) and E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500 and 4.4.2.1 and 4.4.2.2 herein. Read and record the change in thermal impedance. The accept criteria is a maximum change of 10 percent for group B, subgroups 3 and 4 for JANS, or group B, subgroup 2 for JANTX or JANTXV.

4.4.2.1 Group B inspection, table E-VIA (JANS) of MIL-PRF-19500.

Subgroup	Method	Conditions
B3	1056	0°C to +100°C, 25 cycles. (Not applicable for UB and UMC suffix parts.)
B3	1051	-55°C to +175°C, 100 cycles.
B4	1037	$t_{on} = t_{off}$ = 1 minute minimum; 2,000 cycles; I_O = 300 mA, pulsed; in lieu of ac conditions, a dc condition of I_F = 300 mA may be used.
B5	1027	I_O = 300 mA minimum, V_R = rated V_{RWM}, f = 50 - 60 Hz (see 4.5.1).
		Option 1: Adjust I_O or T_A to obtain a minimum T_J of +225°C, t = 216 hours, n = 45, c = 0.
		Option 2: Adjust I_O or T_A to obtain a minimum T_J of +175°C, t = 1,000 hours, n = 45, c = 0.

4.4.2.2 Group B inspection, table E-VIB (JAN, JANTX, and JANTXV) of MIL-PRF-19500. Leaded samples from the same lot may be used in lieu of U and US suffix sample for life test.

Subgroup	Method	Conditions
B2	1056	0°C to + 100°C, 10 cycles. (Not applicable for UB and UMC suffix parts.)
B2	1051	-55°C to +175°C, 45 cycles including screening.
B3	1027	$V_{(pk)}$ = rated V_{RWM}; f = 50 - 60 Hz; I_O = 300 mA dc minimum; adjust T_A or I_O to obtain a minimum T_J of +150°C. (See 4.5.1.)
B6	1032	T_A = +175°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500, and as follows. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

	Subgroup	Method	Conditions
	C2	1056	0°C to + 100°C, 10 cycles. (Not applicable for UB and UMC suffix parts.)
	C2	1051	-55°C to + 175°C, 45 cycles including screening.
*	C2	2036	Axial devices - Tension: Condition A, 6 pounds (2.72 Kilograms), t = 15 s. Fatigue: Condition E for all types. (Does not apply to UB, UB2, and UMC)
	C2	2038	US devices - Tension: Condition B, 6 pounds, t = 15 s. (Does not apply to UB, UB2, and UMC)
	C5	4081	L = .375 inch (9.53 mm); $R_{\theta JL}$ = 150°C/W maximum; $R_{\theta JEC}$ = 40°C/W maximum (see 4.3.1.2).
	C6	1026	1,000 hours minimum, $V_{(pk)}$ = rated V_{RWM}; f = 50 - 60 Hz; I_O = 300 mA dc minimum; adjust T_A or I_O to obtain a minimum T_J of +150°C. (See 4.5.1.)

4.4.4 Group E inspection. Group E inspection shall be conducted in accordance with the tests and conditions specified for subgroup testing in table E-IX of MIL-PRF-19500, and table II herein. Electrical measurements (end-points) shall be in accordance with table I, subgroup 2 herein.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows.

4.5.1 Free air power burn-in and life tests. The use of a current limiting or ballast resistor is permitted provided that each device under test still sees the full P_t (minimum) and that the minimum applied voltage, where applicable, is maintained through-out the burn-in period. Method 3100 of MIL-STD-750 shall be used to measure T_J.

4.5.2 Forward-recovery voltage and time. Forward recovery time shall be measured as the time interval between zero time and the point where the V_F pulse has decreased to 110 percent of the steady-state value of V_F when I_F = 200 mA dc. The maximum rise time of the response detector shall be 1 ns. The maximum forward recovery voltage (V_{fr}) during the forward recovery interval shall also be measured.

4.5.3 Scope display evaluation. Scope display evaluation shall be stable in accordance with method 4023 of MIL-STD-750. Scope display may be performed on automatic test equipment for screening only with the approval of the qualifying activity. Scope display in table I herein shall be performed on an oscilloscope. Reverse current (I_{BR}) over the knee shall be 100 μA peak.

4.5.4 Pulse measurements. Conditions for pulse measurements shall be as specified in section 4 of MIL-STD-750.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/ 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Thermal impedance	3101	See 4.3.1.2	$Z_{\theta JX}$			°C/W
Forward voltage	4011	I_F = 10 mA dc pulsed (see 4.5.4) (Condition B)	V_{F1}			
1N6638					.8	V dc
1N6642					.8	V dc
1N6643					.8	V dc
Forward voltage	4011	(Condition B)	V_{F2}			
1N6638		I_F = 200 mA pulsed (see 4.5.4)			1.1	V dc
1N6642		I_F = 100 mA pulsed (see 4.5.4)			1.2	V dc
1N6643		I_F = 100 mA pulsed (see 4.5.4)			1.2	V dc
Breakdown voltage	4021	I_R = 100 μA dc				
1N6638			V_{BR}	150		V dc
1N6642				100		V dc
1N6643				75		V dc
Reverse current	4016	Condition A or B, V_R = 20 V dc	I_{R1}			
1N6638					35	nA dc
1N6642					25	nA dc
1N6643					50	nA dc
Reverse current	4016	Condition A or B,	I_{R2}			
1N6638		V_R = 125 V dc			500	nA dc
1N6642		V_R = 75 V dc			500	nA dc
1N6643		V_R = 50 V dc			500	nA dc
Subgroup 3						
High temperature operation		T_A = +150°C				
Reverse current	4016	Condition A or B, V_R = 20 V dc	I_{R3}			
1N6638					50	μA dc
1N6642					50	μA dc
1N6643					75	μA dc

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/ 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 3 - continued						
Reverse current	4016	Condition A or B,	I_{R4}			
1N6638		V_R = 125 V dc			100	µA dc
1N6642		V_R = 75 V dc			100	µA dc
1N6643		V_R = 50 V dc			100	µA dc
Forward voltage	4011	I_F = 10 mA dc pulsed (see 4.5.4) (Condition B)	V_{F3}			
1N6638					.65	V dc
1N6642, 1N6643					.80	V dc
Low temperature operation		T_A = -55°C				
Forward voltage	4011	Pulsed (Condition B)	V_{F4}			
1N6638		I_F = 200 mA pulsed (see 4.5.4)			1.2	V dc
1N6642		I_F = 100 mA pulsed (see 4.5.4)			1.2	V dc
1N6643		I_F = 100 mA pulsed (see 4.5.4)			1.4	V dc
Subgroup 4						
Capacitance	4001	V_R = 0 V dc; V_{sig} = 50 mV(p-p) f = 1 MHz	C_{T1}			
1N6638					2.5	pF
1N6642					5.0	pF
1N6643					5.0	pF
Capacitance	4001	V_R = 1.5 V dc; V_{sig} = 50 mV(p-p) f = 1 MHz	C_{T2}			
1N6638					2.0	pF
1N6642					2.8	pF
1N6643					2.8	pF

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/ 2/	MIL-STD-750		Symbol	Limits	Limits	Unit
	Method	Conditions		Min	Max	
Subgroup 4 - continued						
Reverse recovery time	4031	Condition A, $I_F = I_R = 10$ mA dc	t_{rr}			
1N6638					4.5	ns
1N6642					5.0	ns
1N6643					6.0	ns
Scope display	4023	See method 4023 of MIL-STD-750, figures 4023-3, -7, -9, -10 only				
Subgroup 5						
Not applicable						
Subgroup 6	4066					
Surge current		Test Condition A, $I_{FSM} = 2.5$ A(pk) ten surges at one per minute (max), surge duration of 1/120 seconds				
Electrical measurements		See table I, subgroup 2				
Subgroup 7						
Forward recovery voltage and time	4026	$I_F = 200$ mA dc (see 4.5.2)	V_{fr} t_{fr}		5.0 20.0	V(pk) ns

1/ For sampling plan, see MIL-PRF-19500.
2/ Electrical characteristics for surface mount versions are identical to the corresponding axial leaded versions unless otherwise specified.


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

TABLE II. Group E inspection (all quality levels) for qualification and requalification only.

Inspection 1/	MIL-STD-750		Sample plan
	Method	Conditions	
Subgroup 1			n = 45, c = 0
Thermal shock (glass strain) 1/	1056	20 cycles, condition D except low temperature shall be achieved using liquid nitrogen (-195°C). A visual inspection for cracked glass shall be performed. (Not applicable for UB and UMC suffix parts.)	
Temperature cycling 1/	1051	-65°C to +175°C.	
Hermetic seal	1071	Gross leak only. Fine and gross for UB and UMC devices.	
Electrical tests		See table I, subgroup 2.	
Subgroup 2			n = 45, c = 0
Intermittent operation life	1037	10,000 cycles; $I_F = I_O$ = 300 mA dc, $t_{on} = t_{off}$ = 1 minute.	
Electrical end-points		See table I, subgroup 2.	
Subgroup 4			
Thermal resistance	4081	$R_{\theta JSP}$ can be calculated but shall be measured once in the same package with a similar die size to confirm calculations (may apply to multiple specification sheets).	n = 15, c = 0
Thermal impedance curves		See MIL-PRF-19500, table E-IX, group E, subgroup 4.	Sample size N/A
Subgroup 5			
Not applicable			
Subgroup 6			
ESD	1020		n = 11
Subgroup 8			
Resistance to glass cracking	1057	Test condition B. Test until failure occurs or to a maximum of 25 cycles, whichever comes first. Not required for UB and UMC devices.	n = 45
Subgroup 10			
Potted environment test	1054	Not required for UB and UMC packages	n = 22, c = 0

1/ Separate samples may be used for each test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.




NOTES:
1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperatures and current rating specified. (See 1.3.)
3. Derate design curve chosen at T_J ≤ 150°C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125°C, and 110°C to show current rating where most users want to limit T_J in their application.

* FIGURE 12. Temperature current derating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

TEMPERATURE – CURRENT DERATING CURVE
1N6642UB, UB2



Sinewave Operation 50% Duty Cycle
$R_{\theta JA(PCB)}$ = 325°C/W


Note: Max Finish-Alloy Temp = 175°C

NOTES:
1. All devices are capable of operating at ≤ T_J specified on this curve. Any parallel line to this curve will intersect the appropriate current for the desired maximum T_J allowed.
2. Derate design curve constrained by the maximum junction temperatures and current rating specified. (See 1.3.)
3. Derate design curve chosen at T_J ≤ 150°C, where the maximum temperature of electrical test is performed.
4. Derate design curves chosen at T_J ≤ 125°C, and 110°C to show current rating where most users want to limit T_J in their application.

* FIGURE 13. Temperature current derating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance Plots
Axial, 'U', 'US' parts, T_A = 55°C




$R_{\theta JA(PCB)}$ = 250°C/W

NOTE: $Z_{\theta JX}$ = 25°C/W maximum at t_H = 10ms.

* FIGURE 14. Thermal impedance - all glass devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance Plots
'U', 'US' parts, T_{EC} = 25°C




$R_{\theta JEC}$ = 40°C/W

NOTE: $Z_{\theta JX}$ = 25°C/W maximum at t_H = 10ms.

* FIGURE 15. Thermal impedance - all U and US devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance Plots
Axial parts, T_L = 25°C, at L = 0.375 inch




$R_{\theta JL}$ = 150°C/W

NOTE: $Z_{\theta JX}$ = 25°C/W maximum at t_H = 10ms.

* FIGURE 16. Thermal impedance (axial leads).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance Plots
UB Package on FR-4 PCB, T_A = 25°C




$R_{\theta JA(PCB)}$ = 325°C/W

NOTE: $Z_{\theta JX}$ = 65°C/W maximum at t_H = 10ms.

* FIGURE 17. Thermal impedance (UB versions).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

Maximum Thermal Impedance Plots
UB Package on FR-4 PCB, T_{SP} = 25°C




$R_{\theta JSP}$ = 100°C/W

NOTE: $Z_{\theta JX}$ = 65°C/W maximum at t_H = 10ms.

* FIGURE 18. Thermal impedance (UB versions).


Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.



NOTE: $Z_{\theta JX}$ = 34.76°C/W maximum at t_H = 10ms.
PCB Size: 1.5" x 1.5"
Type: FR4
Copper size: 1.0 oz

* FIGURE 19. Thermal impedance (UMC versions).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.



NOTE: $Z_{\theta JX}$ = 34.76°C/W maximum at t_H = 10ms.
PCB Size: 1.5" x 1.5"
Type: FR4
Copper size: 1.0 oz

* FIGURE 20. Thermal impedance (UMC versions).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Packaging requirements (see 5.1).

c. Lead finish (see 3.4.1).

d. The complete PIN, see 1.5 and 6.6.

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from DLA Land and Maritime, ATTN: VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://qpldocs.dla.mil.

6.4 Supersession information and cross-reference data.

6.4.1 Superseded PINs. The PIN JANS1N4148-1 from MIL-PRF-19500/116 has been superseded by PIN JANS1N6642 of this specification sheet. Subsequently, PIN JANS1N4148UR-1 has been superseded by PIN JANS1N6642US. The design of types JANS1N4148-1 and JANS1N4148UR-1 have been classified unsuitable for space flight applications. See MIL-PRF-19500/116 for additional information regarding these superseded PINs.

6.4.2 Cross-reference of PINs with superseded suffix symbol. The PINs 1N6638US, 1N6642US, and 1N6643US are structurally identical and are a direct substitute for PINs 1N6638U, 1N6642U, and 1N6643U. PINs 1N6638U, 1N6642U, and 1N6643U are not to be used for new design. A PIN for PIN cross-reference chart is as follows:

Superseded PIN	Superseding PIN
JANS1N6638U	JANS1N6638US
JANS1N6642U	JANS1N6642US
JANS1N6643U	JANS1N6643US

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.


* 6.5 Suppliers of die. The qualified die suppliers with the applicable letter version (e.g., JANHCB1N6638) will be identified on the QML.

JANHC and JANKC ordering information			
PIN	Manufacturer	Manufacturer	Manufacturer
	43611	13409	13409
1N6638	JANHCB1N6638 JANKCB1N6638	JANHCD1N6638 JANKCD1N6638	JANHCE1N6638 JANKCE1N6638
1N6642	JANHCB1N6642 JANKCB1N6642	JANHCD1N6642 JANKCD1N6642	JANHCE1N6642 JANKCE1N6642
1N6643	JANHCB1N6643 JANKCB1N6643	JANHCD1N6643 JANKCD1N6643	JANHCE1N6643 JANKCE1N6643


JANHC and JANKC ordering information			
PIN	Manufacturer	Manufacturer	Manufacturer
	34156	52GC4	52GC4
1N6638	JANHCC1N6638 JANKCC1N6638	JANHCA1N6638 JANKCA1N6638	JANHCF1N6638 JANKCF1N6638
1N6642	JANHCC1N6642 JANKCC1N6642	JANHCA1N6642 JANKCA1N6642	JANHCF1N6642 JANKCF1N6642
1N6643	JANHCC1N6643 JANKCC1N6643	JANHCA1N6643 JANKCA1N6643	JANHCF1N6643 JANKCF1N6643

6.6 PIN construction example.

6.6.1 Encapsulated devices The PINs for encapsulated devices are constructed using the following form.



6.6.2 Un-encapsulated devices. The PINs for un-encapsulated devices are constructed using the following form.



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

6.7 List of PINs.

6.7.1 PINs for encapsulated devices. The following is a list of possible PINs for encapsulated devices available on this specification sheet.

PINs for types1N6638, 1N6642, and 1N6643				
JAN1N6638	JAN1N6638U	JAN1N6638US	JAN1N6638UB	JAN1N6642UB2
JAN1N6642	JAN1N6642U	JAN1N6642US	JAN1N6642UB	JAN1N6642UB2R
JAN1N6643	JAN1N6643U	JAN1N6643US	JAN1N6643UB	JANTX1N6642UB2
JANTX1N6638	JANTX1N6638U	JANTX1N6638US	JANTX1N6638UB	JANTX1N6642UB2R
JANTX1N6642	JANTX1N6642U	JANTX1N6642US	JANTX1N6642UB	JANTXV1N6642UB2
JANTX1N6643	JANTX1N6643U	JANTX1N6643US	JANTX1N6643UB	JANTXV1N6642UB2R
JANTXV1N6638	JANTXV1N6638U	JANTXV1N6638US	JANTXV1N6638UB	JANS1N6642UB2
JANTXV1N6642	JANTXV1N6642U	JANTXV1N6642US	JANTXV1N6642UB	JANS1N6642UB2R
JANTXV1N6643	JANTXV1N6643U	JANTXV1N6643US	JANTXV1N6643UB	
JANS1N6638	JANS1N6638 U	JANS1N6638US	JANS1N6638UB	
JANS1N6642	JANS1N6642U	JANS1N6642US	JANS1N6642UB	
JANS1N6643	JANS1N6643U	JANS1N6643US	JANS1N6643UB	
JAN1N6638UMC	JANTX1N6638UMC	JANTXV1N6638UMC	JANS1N6638UMC	
JAN1N6642UMC	JANTX1N6642UMC	JANTXV1N6642UMC	JANS1N6642UMC	
JAN1N6643UMC	JANTX1N6643UMC	JANTXV1N6643UMC	JANS1N6643UMC	

(1) UB represents the four different configurations of "UB", "UBCC", "UBCA", and "UBD" for the 1N6638, 1N6642, and 1N6643 devices.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

* 6.7.2 PINs for unencapsulated devices (die). The following is a list of possible PINs for unencapsulated devices available on this specification sheet.

Quality level HC	Quality level HC w/ RHA	Quality level KC	Quality level KC w/ RHA
JANHCA1N6638	JANHCA1N6638	JANKCA1N6638	JANKCA1N6638
JANHCA1N6642	JANHCA1N6642	JANKCA1N6642	JANKCA1N6642
JANHCA1N6643	JANHCA1N6643	JANKCA1N6643	JANKCA1N6643
JANHCB1N6638	JANHCB1N6638	JANKCB1N6638	JANKCB1N6638
JANHCB1N6642	JANHCB1N6642	JANKCB1N6642	JANKCB1N6642
JANHCB1N6643	JANHCB1N6643	JANKCB1N6643	JANKCB1N6643
JANHCC1N6638	JANHCC1N6638	JANKCC1N6638	JANKCC1N6638
JANHCC1N6642	JANHCC1N6642	JANKCC1N6642	JANKCC1N6642
JANHCC1N6643	JANHCC1N6643	JANKCC1N6643	JANKCC1N6643
JANHCD1N6638	JANHCD1N6638	JANKCD1N6638	JANKCD1N6638
JANHCD1N6642	JANHCD1N6642	JANKCD1N6642	JANKCD1N6642
JANHCD1N6643	JANHCD1N6643	JANKCD1N6643	JANKCD1N6643
JANHCE1N6638	JANHCE1N6638	JANKCE1N6638	JANKCE1N6638
JANHCE1N6642	JANHCE1N6642	JANKCE1N6642	JANKCE1N6642
JANHCE1N6643	JANHCE1N6643	JANKCE1N6643	JANKCE1N6643
JANHCF1N6638	JANHCF1N6638	JANKCF1N6638	JANKCF1N6638
JANHCF1N6642	JANHCF1N6642	JANKCF1N6642	JANKCF1N6642
JANHCF1N6643	JANHCF1N6643	JANKCF1N6643	JANKCF1N6643

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.

6.8 Amendment notations. The margins of this specification are marked with asterisks to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Custodians:
Army - CR
* Navy - SH
Air Force - 85
NASA - NA
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, MC
Air Force - 19, 71

Preparing activity:
DLA - CC

(Project 5961-2023-036)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T03:35Z
Check the source to verify that this is the current version before use.