SS-C-621b
INT. AMENDMENT-1 (GSA-FSS)
July 15, 1968

INTERIM AMENDMENT
TO
FEDERAL SPECIFICATION

CONCRETE MASONRY UNITS, HOLLOW
(AND SOLID, PREFACED AND UNGLAZED)

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20405, based upon currently available information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized Federal agencies to use this interim amendment as a valid exception to Federal specification SS-C-621b, dated January 19, 1968.

PAGE 3

Paragraph 3.2.1, line 3. After "with" insert "a ceramic material,"

Paragraph 3.2.3.2, line 2. Delete "1/8" and substitute "1/16".

PAGE 4

Paragraph 3.2.4.8, line 2. Insert a period after "4.4.2.8.1." Delete "and 4.4.2.8.2" and substitute "Spotting media shall be completely removed when tested in accordance with 4.4.2.8.2."

PAGE 5

Paragraph 4.4.2.2, line 2. Change "uncovered" to "covered". Last Line. Delete in its entirely and substitute "Wipe tincture of iodine test area clean with alcohol. Wipe other test area clean with a clean cloth."

Paragraph 4.4.2.7, line 2. Add "Use test panels of not less than 3-inches wide by 6-inches long. Test panels need not be conditioned."

PAGE 6

Paragraph 4.4.2.8.1, line 4. After "specimen" insert "for 80 cycles".

Paragraph 4.4.2.8.2. Delete the last two lines and substitute "Clean the stained areas as specified in 4.4.2.8.1 except as follows: Use paint thinner conforming to TT-T-295 to clean spotting medium (b); clean spotting medium (a) for 10-cycles; clean spotting medium (b) for 150-cycles; clean spotting media (c) and (d) for 60-cycles."

FSC 5620

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:13Z
Check the source to verify that this is the current version before use.