AMENDMENT
TO
INTERIM FEDERAL SPECIFICATION

CLEANER, VACUUM, ELECTRIC
(INSTITUTIONAL/HOSPITAL)

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification W-C-001749 dated May 15, 1973.

PAGE 1

1.1 Scope. Delete last sentence and replace with "These cleaners are designed to operate either on 120 VAC, 60 Hertz, single phase, or 220 VAC, 50 Hertz power (see 6.2)."

PAGE 2

3.1 Materials. Delete in its entirety and substitute the following:

3.1 General requirements.

3.1.1 Preproduction sample. Unless otherwise specified, before production commences, a preproduction sample shall be made available to the government for inspection, testing, and determination as to compliance with all requirements of this specification. Acceptance of preproduction samples does not relieve the contractor of the responsibility to comply with all requirements of this specification.

3.1.2 Materials. The materials employed in fabrication of these cleaners shall be sound, adequate for the intended purpose and appropriately finished. All materials shall be free from defects which may affect the serviceability or the appearance of the vacuum cleaners.

PAGE 3

3.5.2 Add to last sentence after - orifice, "when operating at 120 volts."

PAGE 4

3.5.5 line 1: Add between the words operations and shall "at 120 volts."

3.6.3 Add after last sentence: "the tank shall hold the minimum liquid capacity for the size specified before the shutoff mechanism (see 3.3.2) is fully activated."

3.7 Mobility. Add between the second and third sentences the following: "Wheels/casters shall be no less than 3/4 inches wide by 4 inches diameter."

PAGE 5

3.8.2 Tool construction. Delete the first sentence and substitute the following: The tools and their assembly hardware shall be fabricated from synthetics, ferrous or non-ferrous metals. Add the following sentence: Tools and assembly hardware fabricated from ferrous metal shall be plated or finished to resist corrosion and prevent marking.

3.8.3 Hose construction. Delete the first sentence and substitute the following: The hose shall be of the polymer and filament jacket type with steel wire reinforcing helix.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

PAGE 5 (con)

3.9 line 3: After where necessary add "and outline the steps required to convert the cleaner to wet operation and back to dry."

3.10 line 3: After durability, delete or, and after serviceability add "and appearance."

4.2.2 Delete End Item Inspection, and add "Visual and Dimensional Examination." Examination of the end item shall be in accordance with the classification of defects set forth in table I. The lot sizes shall be expressed in units of vacuum cleaners for the purpose of determining the sample size in accordance with MIL-STD-105. The sample unit for this examination shall be one completely fabricated vacuum cleaner of each size offered for delivery at one time. The sample shall be visually examined for general defects identified in table I. The inspection level shall be level II of MIL-STD-105, using an Acceptable Quality Level (AQL) of 4.0 defects per 100 units.

4.2.2.1 Visual examination. Delete in its entirety.

PAGE 6

Add to Table I. Classification of defects

Examine	Defect	Major	Minor
Dimensions	Cord less than 35 feet long	X	
	Hose less than 10 feet long	X	
	Hose less than 1-1/2" I.D.	X	
	Attachment dimensions less than specified.		X

4.2.2.2 Delete entire paragraph.

4.3.1 Delete in its entirety and substitute the following:

4.3.1 General. Preproduction samples shall be tested for all requirements of paragraphs 4.3.2, 4.3.3, and 4.3.4. Subsequent manufacturing lots shall be tested to paragraph 4.3.4, performance test. Sampling for lot tests shall be at inspection level S-4 with an acceptable quality level (AQL) of 4.0 defects per 100 units.

PAGE 7

4.3.2.4 Add new sentence at the end of the paragraph "When released, the cleaner shall return to its upright position without tipping over."

4.3.2.5 First line change: "200 pounds" to "150 pounds".

4.3.2.5 line 5: After the word resulting, add the word "hose".

4.3.2.6 Delete first sentence and add new sentence "The engaged wand, hose and tools shall withstand a pull of 25 pounds for 2 minutes at each connecting joint without separation."

Add to last sentence "before and after testing".

PAGE 8

4.3.3 line 4: Insert between points and shall "except sealed bearings."

4.3.3.2 First sentence, second line: Delete the word detach and add "Attached with the intake end extending a minimum of 2 feet beyond the screen."

Second sentence: Delete the word suitable and replace with the word "vertical."

4.3.3.3 add to the end of the last sentence "at 120 volts."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

4.3.3.5 Change paragraph 4.3.3.5 to "4.3.4" add to last sentence after 3.5.2. "when operated at 120 volts."

6.2 Add (g) Voltage, as required (see 1.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.