W-C-001750 (GSA-FSS)
May 11, 1973
INTERIM REVISION OF
Fed. Spec. W-C-421f (In Part)
July 25, 1963

INTERIM FEDERAL SPECIFICATION

CLEANER, VACUUM, ELECTRIC

(COMMERCIAL/INDUSTRIAL)

This Interim Federal Specification was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. The cleaners covered by this specification are all vertical tank models for commercial and industrial use. The type I cleaners are for dry pickup only. The type II cleaners are for wet or dry pickup. The type III cleaners are designated explosion proof for use in UL defined class 1, group D and class II, group G atmospheres and are capable of wet or dry pickup. These cleaners are designed to operate on a 120 VAC, 60 Herts, single phase power source.

1.1.1 Federal specification coverage. Federal specifications do not include all varieties of the commodity as indicated by the title of the specification, or which are commercially available, but are intended to cover only those generally used by the Federal Government.

1.2 Classification.

1.2.1 Types, classes, styles, and sizes. The vacuum cleaners in accordance with this specification shall be of the following types, classes, styles, and sizes. For purposes of this specification, 231 cubic inches shall equate to one gallon. All capacities shown are minimum recoverable capacities.

Type I - Dry pickup only.
  Class A - Enclosed filter.
    Size 1 - 5 gallon.
    Size 2 - 10 gallon.
  Class B - Exposed filter.
    Size 1 - 5 gallon.
    Size 2 - 10 gallon.

Type II - Wet pickup.
    Size 1 - 5 gallon.
    Size 2 - 10 gallon.
    Size 3 - 30 gallon.

Type III - Explosion proof.
    Size 1 - 5 gallon.
    Size 2 - 10 gallon.
    Size 3 - 30 gallon.

FSC 7910

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issues in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

Federal Specifications:

QQ-S-781 - Strapping, Steel, Flat and Seals.
PPP-B-585 - Boxes, Wood, Wirebound.
PPP-B-591 - Boxes, Shipping, Fiberboard, Wood-Cleated.
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.
PPP-C-650 - Crates, Wood, Open and Covered.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:

MIL-C-104 - Crate, Wood, Lumber and Plywood Sheathed, Nailed and Bolted.
MIL-P-116 - Preservation, Methods Of.
MIL-L-10547 - Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.
MIL-E-16298 - Electric Machines Having Rotating Parts and Associated Repair Parts, Packaging Of.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issues in effect on date of invitation for bids or request for proposal shall apply.

Floor and Vacuum Machinery Manufacturers Association (FVMMA), Inc., Standard:

Industry Standard No. 1 - Method of Rating Commercial and Industrial Type Vacuum Cleaners (Portable and Mobile) Suction Only.

(Application for copies should be addressed to the Floor and Vacuum Machinery Manufacturers Association, Inc., 1803 South Busse Road, Mt. Prospect, IL 60056.)

Underwriters' Laboratories (UL), Inc., Standards:

UL Publication - Hazardous Location Equipment List.
UL 62 - Flexible Cord and Fixture Wire.
UL 674 A - Motors and Generators, Electric, for Use in Hazardous Locations, Class II, Groups F and G.
UL 674 B - Motors and Generators, Electric, for Use in Hazardous Locations, Class I, Groups C and D.
UL 698 - Industrial Control Equipment for Use in Hazardous Locations.
UL 894 - Switches, Snap, for Use in Hazardous Locations.
UL 1017 - Vacuum Cleaning Machines and Blower Cleaners.

(Application for copies should be addressed to the Underwriters' Laboratories, Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11749; 207 East Ohio Street, Chicago, IL 60611; or 1655 Scott Boulevard, Santa Clara, CA 95050.)

National Electrical Code.

National Fire Protection Association (NFPA) Standard:

No. 77 - Static Electricity.

(Application for copies should be addressed to the National Fire Protection Association, 60 Batterymarch Street, Boston, MA 02110.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 Material. The materials used shall be suitable for the purpose intended and shall be free from defects affecting the appearance or which may affect serviceability of the cleaners.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

3.2 Fire and casualty hazards.

3.2.1 Each bidder shall submit to the contracting agency proof that the cleaners he proposes to supply under this specification conform to the requirements of UL 1017. The listing may be accepted as evidence that the cleaners conform to this requirement.

3.2.2 In lieu of the listing, the bidder may submit proof, satisfactory to the contracting agency, that the cleaners conform to the applicable requirements of the published UL standards including methods of testing and test results.

3.2.3 Compliance with UL requirements regarding fire and casualty hazards does not absolve the contractor from complete compliance with the requirements of this specification in order to secure the acceptance of his cleaners. In event of difference between any of the requirements of this specification and those of UL, the requirements of this specification shall govern.

3.3 General. Each vacuum cleaner shall be complete, fully lubricated, ready to operate (minor assembly is permitted), simple in construction, reliable in operation, and constructed so as to be readily disassembled for inspection, adjustment, cleaning, or replacement. Each part of the vacuum cleaner shall be interchangeable with the similar part of any vacuum cleaner of the same model and size made by the same manufacturer. Motor bearings shall be sealed or shielded and shall not require periodic lubrication. Lubrication points shall be shielded from dirt entry and shall be adequately sealed to prevent leakage of the lubricant.

3.3.1 Identification marking. Each vacuum cleaner shall be legibly and indelibly marked with the manufacturer's designation for model number or part number and his name or trademark of such known character that the manufacturer may be readily determined. Nameplates on the cleaners shall be in accordance with UL requirements.

3.3.2 Surface finish. All exterior or interior surfaces readily visible or apt to be contacted by the machine operator shall be free from defects which may affect appearance, serviceability, or which may contribute to operator injury. All interior surfaces shall be suitably finished, coated or plated to prevent dirt adherence, erosion, or corrosion. Air passages and surfaces impinged upon by the airflow shall be free from pits, flashings, sharp radii, etc., which may cause dirt buildup or turbulent airflow. Finishes, coatings, or platings shall be in accordance with the best commercial practices.

3.3.3 Vacuum system. Motors employed in these cleaners shall be rated for continuous duty. Continuous duty is defined as constant operation for an 8 hour work day. The motor and vacuum producer shall be of rugged construction; shall operate at minimum RPM necessary to develop the required performance; shall be vibration isolated and shall not resonate or cause resonance in the cleaner.

3.3.3.1 Vacuum producer. The vacuum producer shall be balanced for minimum vibration. The water lift requirements shall be as specified for each type of cleaner.

3.3.4 Filtration system. The filter system in the cleaner shall be either the enclosed type or the exposed bag type when used for dry pickup. Unless bypass motors are employed, a secondary filter for motor inlet air shall be provided. The filter assemblies may be replaced (or removed) by the wet pickup automatic shut off assembly.

3.3.5 Switches or controls. The switch shall be a reliable, adequately insulated, quick make and break type. The switch or control shall be UL listed and rated no less than the rated current on the motor nameplate. The switch or control shall be prominently and conveniently located.

3.3.6 Power cord. The power cord assemblies shall conform to the requirements of UL. Type I and type II cleaners shall be furnished with 25 feet minimum, 3-conductor cords. Type III cleaners shall be furnished with 50 feet of 3-conductor cord conforming to UL 62 and wired in accordance with the National Electrical Code except the cord set shall not have a connector plug. The connector plug must be in accordance with and installed in accordance with local codes and insurance requirements. An acceptable strain relief shall be provided at the cord's point of entry into the machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

3.3.7 Cord storage. Each cleaner shall provide some means for coiling, wrapping, or otherwise storing the power cord when the cleaner is not in use.

3.3.8 Tanks. The tanks shall be of stainless steel when specified (see 6.2). Tanks, other than stainless, shall be suitably finished or plated to resist corrosion. Tanks of non-metal construction may be employed if service life and durability can be demonstrated to be equal to the metal tank. If weldments are used in tank construction, electrode or filler rod material shall approximate the base metal composition. Platings, coatings, or finishes used for corrosion protection shall resist the corrosive effects of normal cleaning solutions at 180° F. All type II and III cleaner tanks of 10 gallons and larger capacity shall have drain valves. The tanks of the type II and III shall also provide for foam suppression or allow for expansion.

3.3.9 Wet pickup. When employed for liquid recovery, the filter assembly may be removed or replaced by an automatic shutoff assembly. This assembly shall interrupt the air intake or power to the cleaner when a predetermined level is reached.

3.3.10 Mobility. Each cleaner shall be equipped with wheels and/or casters. The wheels or casters may be affixed to the tank or chassis of the cleaner or a dolly shall be provided. The wheels or casters shall run on bearings. The chassis or the motor assembly shall have a handle or adequate hand holds to facilitate cleaner movement.

3.3.11 Stability. When the vacuum cleaner, with all parts in operating position, is placed in any position on a plane inclined at 10° to the horizontal, each of the supports of the vacuum cleaner shall remain in contact with the plane surface when the tank is empty.

3.3.12 Tools and attachments. The tools and attachments for all cleaners shall be fabricated from non-ferrous alloy or suitable synthetic. The tools shall be suitably plated or finished to resist corrosion or prevent marking. Bristles, squeegee strips, etc., used in the tools shall be replaceable. The hose shall be of non-marking rubber or durable synthetic. The hose bore shall be of rubber or durable synthetic impervious to common solvents and detergents. Swivel couplings shall be provided on at least one end of the hose assembly. All components shall positively lock to the wand or the hose assembly. The tools shall conform to the following requirements:

Attachment	Length (min.)	Slot	
		Length (min.)	Area (min.)
	Inches	Inches	Sq. In.
Hose assembly 1-1/2 inches inside diameter	120	—	—
Bare floor tool	14	13	6-1/2
Carpet tool	11	10	3
Squeegee tool	14	13	6-1/2
Radiator and crevice tool	9	—	—
Floor wand 1-1/2 inches outside diameter	48	—	—

Hoses and couplings shall be subjected to the tests specified in 4.2.2.2.4 and 4.2.2.2.5.

3.3.13 Noise. The maximum noise generated by these cleaners when in operation shall be 90 dbA for class B cleaners and 85 dbA for all others. Measurements shall be taken with the test setup and procedure of 4.2.2.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

3.4 Type I cleaners. The type I cleaner shall be used for dry pickup only. All general requirements of 3.3 apply. Specific requirements are detailed herein.

3.4.1 Performance. The vacuum cleaners shall be tested in accordance with 4.2.2.3.3. The test setup and procedure of FVMMA Industry Standard No. 1 shall be employed. When tested, the class A cleaners shall develop 40 inches water lift through a 3/4 inch orifice and 6 inches water lift through a 1-1/2 inch orifice. Class B cleaners shall develop 45 inches water lift through a 3/4 inch orifice and 8 inches water lift through a 1-1/2 inch orifice.

3.4.2 Tools and attachments. Unless otherwise specified (see 6.2), the type I cleaners shall be provided with a 10 foot minimum 1-1/2 inches inside diameter hose assembly, a wand assembly, a carpet tool, a bare floor tool, and a crevice tool.

3.5 Type II cleaners. The type II cleaners shall be used for wet or dry pickup. All general requirements of 3.3 apply. Specific requirements are detailed herein.

3.5.1 Performance. The vacuum cleaners shall be tested in accordance with 4.2.2.3.3. The test setup and procedures of FVMMA Industry Standard No. 1 shall be employed. When tested, the type II cleaners shall be capable of developing a minimum of 40 inches water lift through a 3/4 inch orifice and 8 inches water lift through a 1-1/2 inch orifice.

3.5.2 Tools and attachments. Unless otherwise specified (see 6.2), the type II cleaners shall be furnished with the tools and attachments specified for the type I cleaners and shall, in addition, be furnished with a squeegee tool and any attachment or accessory required to convert the cleaner from wet to dry pickup.

3.6 Type III cleaners. The type III cleaners are to be used for wet or dry pickup in class 1, group D or class II, group G atmospheres as defined by the UL in the Hazardous Location Equipment List. All general requirements of 3.3 apply. Specific requirements are detailed herein.

3.6.1 Motor. The motors used shall be UL approved for use in hazardous locations and shall conform to UL 674 A and UL 674 B.

3.6.2 Performance. The vacuum cleaner shall meet the requirements of 3.5.1, except shall develop 35 inches water lift through a 3/4 inch orifice and 10 inches water lift through a 1-1/2 inch orifice.

3.6.3 Tank. The dump valve or drain used on the tank shall be UL listed or rated static conductive.

3.6.4 Filter. The filter and filter assembly shall be UL listed or shall conform to NFPA No. 77.

3.6.5 Switch. The power switch and enclosure shall be UL listed or shall conform to UL 894. Controllers, if used, shall be UL listed or shall conform to UL 698.

3.6.6 Wiring and conduit. All wiring and conduit in the type III cleaner shall conform to the requirements of the National Electrical Code.

3.6.7 Tools and attachments. Tools and attachments specified for the type II cleaners (see 3.5.2) shall be provided except that all type III tools and attachments shall be UL listed or shall conform to NFPA No. 77.

3.7 Manuals. Each cleaner shall be furnished with a manual of operating and maintenance instructions with an Illustrated Parts Breakdown (IPB). The IPB shall identify all components by part number to the lowest repair level. If minor assembly is required, the manual shall provide assembly instructions.

3.8 Workmanship. The cleaner and all tools and attachments shall be constructed, assembled, and finished in a manner to assure good quality equipment of a neat general appearance and free from imperfections which may affect durability or serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling for inspection and tests. Sampling for inspection and tests shall be performed in accordance with the provisions set forth in MIL-STD-105.

4.2.1 Sampling for inspection. Sample size shall be determined by inspection level S-2 of MIL-STD-105 with an Acceptable Quality Level (AQL) of 4.0 defects per 100 units.

4.2.2 Sampling for tests. Sampling for tests shall be in accordance with 4.2 except level S-3 with an AQL of 1.5.

4.2.3 Component and material inspection. In accordance with 4.1, the contractor is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements of referenced subsidiary specifications and standards to the extent specified, or, if none, in accordance with this specification.

4.2.4 End item inspection.

4.2.4.1 Visual examination. The sample cleaner shall be visually examined for the following specific defects but the cleaner and all tools and accessories shall be examined subjectively for workmanship (see 3.8). The failure of the cleaner to pass this examination shall be cause for rejection. The tools and attachments shall be checked for dimensions specified in 3.3.13. Failure to conform shall be cause for rejection.

1. No UL label or other evidence of conformity to UL requirements (see 3.2).
2. Not finished as specified (see 3.3.2).
3. Power cord not as specified (see 3.3.6 and 3.3.7).
4. Tanks not as specified (see 3.3.8).
5. Mobility requirements not as specified (see 3.3.10).
6. Stability not as specified (see 3.3.11).
7. Tools and attachments not as specified (see 3.3.12, 3.4.2, 3.5.2, and 3.6.7 as applicable).
8. Manual not as specified (see 3.7).
9. Workmanship not as specified (see 3.8).

4.2.4.2 Pre-operational tests.

4.2.4.2.1 Type III cleaner motors shall be tested in accordance with or shall be certified to be in accordance with UL 674 A and UL 674 B.

4.2.4.2.2 Hose tests. A compressive load of not less than 200 pounds shall be applied to any portion of the hose (at least 12 inches from any fitting) by means of parallel surfaces having a length of not more than 3 inches parallel to the axis of the hose for not less than 2 minutes and released. There shall be no ruptures and the resultant hose diameter shall not differ more than 1/16 inch from the diameter prior to the test.

4.2.4.2.3 Coupling tests. A tensile force of not less than 25 pounds shall be applied to the engaged tool, hose, and swivel couplings for not less than 2 minutes and released. Couplings shall not part and shall release and engage satisfactorily after relaxation.

4.2.4.3 Operational tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

4.2.4.3.1 General. The operational tests shall be performed with the cleaner set up in the dry pickup configuration and connected to a power source conforming to the motor nameplate data. Each sample cleaner shall be operated in the condition received for 8 hours with the orifice wide open. All lubrication points shall be visually checked after this run. Any evidence of excessive leaking, galling, metallic particles, or lack of lubricant shall be cause for rejection. The commutators, except type III motors, shall be visually examined. There shall be no evidence of excessive burning, pitting, or grooving.

4.2.4.3.2 Noise tests. The cleaner shall be set up in operational configuration with the hose, wand, and floor tool attached. Portable sound measuring equipment shall be used. With the cleaner in operation, two readings shall be taken using the A weighted, damped, or slow response scale. A third reading shall be taken to measure background noise after the cleaner is shut down. All readings shall be taken from the operator's station at the wand and no closer than 6 feet from the cleaner body. If the difference between the average of the first two readings and the background is greater than 14 db, disregard the background noise. If less than 14 db difference, combine the readings logarithmically. The log sum or the average, whichever is applicable, shall not be greater than 90 dbA.

4.2.4.3.3 Airflow tests. Each sample cleaner shall be tested for performance in accordance with FSMMA Industry Standard No. 1 with the following exceptions:

The connection between the orifice box and the cleaner inlet shall be via the hose and wand assembly to be furnished with the cleaner. Taping or similar sealing of the hose, wand, or cleaner coupling connections is not permitted. Clean, new filters shall be used. All filters required for dry pickup shall be installed. The test box shall be fitted with the specified orifice. The cleaner under test shall demonstrate the capability of developing the minimum water lift and CFM ratings specified for the type in 3.4, 3.5, or 3.6.

4.3 Examination of preparation for delivery. An examination shall be made to determine that preservation, packing, and marking are as required by section 5. Defects shall be as indicated but not limited to those in table I. The sample unit shall be one shipping container fully prepared for delivery. The lot number shall be the number of containers offered for inspection. The inspection level shall be S-2. The AQL shall be 4.0, expressed in terms of defects per hundred units.

TABLE I. Examination of preservation, packing, and marking

Examine	Defect
Preservation	Not as specified.
Packing	Container not as specified. Weight limitation of box exceeded. No skids on boxes with gross weight in excess of 200 pounds. Crate not as specified for cleaners weighing 1,000 or more pounds. Boxes for level A not fitted with case liners.
Marking	Omitted, incomplete, incorrect, illegible, of improper size, location, sequence, or method of application.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packing shall be level A or C, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

5.1.1 Level A. Vacuum cleaners, attachments, accessories, and repair parts shall be preserved in accordance with MIL-P-116, method III. Technical publications shall be preserved in accordance with MIL-P-116, method IC-1. When specified (see 6.2), complete vacuum cleaners shall be preserved in accordance with MIL-E-16298.

5.1.2 Level C. Each vacuum cleaner, attachments, accessories, and repair parts shall be preserved and packaged in accordance with the industry's standard practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Vacuum cleaners weighing less than 1,000 pounds. One or more complete vacuum cleaners of identical type and class shall be packed in a wood cleated-plywood box conforming to PPP-B-601, overseas type or a nailed wood box conforming to PPP-B-621, class 2 or a fiberboard box conforming to PPP-B-636, grade V3c or V3s, style RSC. The gross weight of boxes shall not exceed approximately 200 pounds, unless the weight of a vacuum cleaner exceeds this amount. When the gross weight of a box exceeds 200 pounds, the box shall be modified by the addition of skids in accordance with the applicable box specification. Contents of each box shall be cushioned, blocked, braced, and anchored to prevent movement of the item. Each box shall be provided with a waterproof case liner conforming to MIL-L-10547 and sealed in accordance with the appendix thereto. The boxes shall be sealed and strapped in accordance with the appendix to the applicable box specification. Flat steel strapping shall conform to QQ-S-781, type I, class B.

5.2.1.2 Vacuum cleaners weighing 1,000 pounds or more. When the weight of a complete vacuum cleaner is 1,000 pounds or more, it shall be packed in a sheathed wood crate conforming to MIL-C-104, type I, style A. Contents of the crate shall be cushioned, blocked, braced, and anchored to prevent movement of the item. Each crate shall be fitted with a case liner conforming to MIL-L-10547 and sealed in accordance with the appendix thereto.

5.2.2 Level B.

5.2.2.1 Vacuum cleaners weighing less than 1,000 pounds. Each vacuum cleaner shall be packed in a wood-cleated fiberboard, wirebound wood, wood cleated-plywood, nailed wood, or fiberboard box conforming to PPP-B-591, domestic type; PPP-B-585, class 1; PPP-B-601, domestic type; or PPP-B-636, class domestic, style optional. When the gross weight of a box exceeds 300 pounds, the box shall be modified by the addition of skids in accordance with the applicable box specification. The vacuum cleaner shall be cushioned, blocked, braced, and anchored to prevent movement of the item.

5.2.2.2 Vacuum cleaners weighing 1,000 pounds or more. Each vacuum cleaner shall be packed in crates conforming to PPP-C-650, style A or B, type V. The vacuum cleaner shall be anchored within the crate in accordance with the requirements in the appendix to PPP-C-650.

5.2.3 Level C. Vacuum cleaners preserved and packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall comply with the requirements of the National Motor Freight Classification or Uniform Freight Classification, as applicable.

5.3 Marking.

5.3.1 Civil agencies. In addition to any special marking required by the contract or order (see 6.2), marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special marking required by the contract or order (see 6.2), marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. These cleaners are intended for commercial or industrial use. Type I is for dry pickup only. Type II is for wet or dry pickup. Type III is for wet or dry pickup in hazardous locations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, class, style, and size desired (see 1.2.1).
(c) Tools and attachments desired if different (see 3.4.2, 3.5.2, and 3.6.7).
(d) Level of preservation and packaging required (see 5.1).
(e) Level of packing required (see 5.2).
(f) Marking required (see 5.3).

6.3 Guarantee. It is suggested that the contracting officer require the contractor guarantee each cleaner procured under this specification for a period of one year from date of delivery against all defects in material or workmanship. Replacement or repair of all parts defective in material or workmanship shall be made at no cost to the Government.

6.4 Bid samples. It is suggested that the contracting officer require bid samples be submitted for evaluation when this specification is used for other than definite quantity contracts. The sample machine shall be evaluated for conformance to all subjective and objective characteristic requirements of this specification. Provided no production changes are effected by the contractor, satisfactory performance of the sample shall obviate a continuing inspection requirement for the term of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:35Z
Check the source to verify that this is the current version before use.