W-F-001316(GSA-FSS)
March 25, 1968

INTERIM FEDERAL SPECIFICATION

FLASHLIGHT, RIGHT ANGLE

This Interim Federal Specification was developed by General Services Administration, Federal Supply Service, Standardization Division, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers prefocused flashlights for industrial use.

1.2 Classification.

1.2.1 Types, styles, and classes. The flashlights furnished under this specification shall be of the following types, styles, and classes, as specified (see 6.2).

Types:
- Type I - Metal Case
- Type II - Plastic Case

Styles:
- Style A - Standard
- Style B - Waterproof
- Style C - Waterproof and explosion proof

Classes:
- Class 1 - With spot lens
- Class 2 - With diffusion lens
- Class 3 - With spot and diffusion lens and a spare bulb

2. APPLICABLE DOCUMENTS

2.1 Specifications and standards. The following specifications and standards, of the issues in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:
- W-B-101 - Battery, dry
- PPP-B-566 - Boxes, folding, paperboard
- PPP-B-601 - Boxes, wood, cleated-plywood
- PPP-B-621 - Boxes, wood, nailed and lock-corner
- PPP-B-636 - Box, fiberboard
- PPP-B-665 - Boxes, paperboard, metal stayed (including stay material
- PPP-B-676 - Boxes, setup

Federal Standards:
- Fed. Std. No. 123 - Marking for domestic shipment (civilian agencies)
- Fed. Test Method Std. No. 151 - Metals, test methods
- Fed. Std. No. 595 - Colors

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Washington, D. C., Atlanta, Chicago, Kansas City, Mo., Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, Wash.

FSC 6230

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Specifications:
MIL-P-116 - Preservation, Methods of
MIL-P-22985 - Plastic, Ethyl Cellulose

Military Standards:
MIL-STD-105 - Sampling procedures and tables for inspection by attributes
MIL-STD-129 - Marking for shipment and storage

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

United States Department of Interior:
Bureau of Mines, Schedule 10C - Electric Mine Lamps

(Application for copies should be addressed to the Publication Distribution Section, Bureau of Mines, 4800 Forbes Avenue, Pittsburgh, Pa. 15212.)

Underwriters' Laboratories Inc. (UL) Standard:
UL 783 - Electric Flashlights and Lanterns for use in Hazardous Locations, Class I, Groups C and D.

(Application for copies should be addressed to Underwriters' Laboratories, Inc., 207 East Ohio Street, Chicago, Illinois 60611; Walt Whitman Road, Melville, New York 11749; or 1655 Scott S Boulevard, Santa Clara, California 95050.)

3. REQUIREMENTS

3.1 General. The flashlights furnished under this specification shall be of tubular design with the head located at a 90 degree angle to the base of the flashlight. The flashlight shall be complete with lens, reflector, lamp, lampholder, retaining ring, case, switch, end cap, clip, and suspension ring as specified herein. The flashlight shall be designed to operate on "D" type dry cell batteries that are in accordance with W-B-101. The batteries shall not be furnished.

3.1.1 Styles.

3.1.1.1 Style A. The style A flashlights shall be commercial types that are in accordance with the requirements specified herein except for the water tightness and explosion proof requirements.

3.1.1.2 Style B. The style B flashlights shall be watertight and shall meet all requirements specified herein except the explosion proof requirements.

3.1.1.3 Style C. The style C flashlights shall be in accordance with the requirements of this specification and shall be waterproof and explosion proof in accordance with the requirements of the Bureau of Mines, Schedule 10C, and UL 783. In the event of any conflict between this specification the requirements of the Bureau of Mines, Schedule 10C, and UL 783, the requirements of the Bureau of Mines shall govern.

3.2 Material. The materials throughout shall be suitable in every respect for the intended purpose. The flashlights and the component parts shall evidence no indication of damage, penetration of protective coating or corrosion when subject to the tests specified in section 4. All spring and switch contacts shall be of commercial grade, or better, spring brass, phosphor bronze or beryllium copper. Style A interior contacts, including end or base cap springs, may be of a suitable material such as copper coated steel provided the materials used have suitable electrical conductivity characteristics and meets all requirements of this specification. Dissimilar metals used in contact with each other shall be carefully selected to prevent electrolytic corrosion.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

3.2.1 Reflector. The contour of the reflector shall be essentially parabolic. The reflecting surface shall be vacuum or electroplated and polished to assure a coefficient of reflection that will meet the requirements of this specification. The reflector shall be lacquered on the inside only. The lacquer shall not react chemically with either the gaskets or the reflector material and shall have sufficient rigidity to prevent distortion when the lamp and batteries are in place. The reflecting surface shall be smooth and free from bubbles or pits.

3.2.2 Lens. The lens shall be formed from clear plastic that will not discolor with normal lifetime usage and will not be affected by salt water, or oils and shall meet all requirements of this specification.

3.2.3 Case.

3.2.3.1 Type I. The type I metal case flashlights shall be either copper coated steel or aluminum with a chrome plated or enamel finish that will meet all the requirements of this specification. The angle head shall be die cast zinc or of other similar material that will be in accordance with this specification. The case and the head shall be of sufficient thickness and finish to meet the requirements of this specification and in accordance with the best commercial practice for the intended use.

3.2.3.2 Type II. The body and the head of the type II flashlight shall be of molded plastic that meets or exceeds the mechanical and physical requirements as given in table II, type II of MIL-P-22985. The case of this flashlight shall meet all requirements and tests required by this specification for plastic case flashlights. Any conflict between MIL-P-22985 and this specification, the requirements of this specification shall govern.

3.2.3.3 Color. Unless otherwise specified by the purchaser, the case color for the style A flashlight shall be of the manufacturers option, style B shall be olive drab No. 14087, style C shall be magenta No. 17142. The colors shall be in accordance with Fed. Std. No. 595.

3.2.4 Gaskets. Gaskets used in style B and c flashlights shall be provided at any joint through which moisture could possibly pass into the interior of the flashlight. The gaskets may be of the manufacture's option but shall be resistant to oil and water,and shall meet the test requirements of this specification.

3.2.5 Water tightness. Styles B and C flashlights shall be watertight, no water shall enter the flashlight when tested as specified in 4.4.7.

3.3 Construction.

3.3.1 Case. The outside surface of the case shall be fluted, ribbed or knurled to minimum depth of .025 inches for secure gripping.

3.3.2 Cap and retaining ring. Means shall be provided through the use of threaded caps and retaining rings for securing the lens and batteries in place. The caps and rings shall have a minimum of 3 engaged threads for the plastic flashlight and a minimum of 2 engaged threads for metal flashlights.

3.3.2.1 Storage compartment. The class 3 flashlight shall have a storage compartment provided in the end cap and shall be capable of housing a lens and spare lamp in such a manner that it will be readily accessible but will not become displaced or broken when the flashlight is subjected to the tests specified in section 4.

3.3.2.2 Battery contact spring. The length and design of the rear contact spring shall be such that it will accommodate the required number of cells of any length between 2-5/16 inches and 2-13/32 inches. The spring shall compress a minimum of 3/8 inch and exert a force of not less than 2 pounds.

3.3.3 Threads. All threads shall be of design and fit that may be screwed tight using a torque not exceeding 25 inch pounds. The threads shall not strip or ride over those of mating parts when a torque of 75 inch pounds $\pm$ 2 inch pounds is applied.

3.3.4 Dimensions. The dimensions of the flashlight shall be of the values specified in Table I. The given dimensions are in inches.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

TABLE I

Class and Style	No. of Cells	Industry Lamp No.	O/A Dim. Length ≤ 1/4"	O/A Dim. Diameter ≤ 1/8"	Lens Thickness ≤ 0.01"	Lens Diameter ± 3/16	Battery Compartment I.D. ≤ 1/16"
A -1	2	PR-2	7-3/8	2-1/8	0.025	1-7/8	1-7/16
B -1	2	PR-2	7-3/8	2-1/8	0.025	1-7/8	1-7/16
C -1	2	PR-2	7-3/8	2-1/8	0.025	1-7/8	1-7/16
A -2	2	PR-2	7-3/8	2-1/8	0.025	1-7/8	1-7/16
B -2	2	PR-2	7-3/8	2-1/8	0.025	1-7/8	1-7/16
C -2	2	PR-2	7-3/8	2-1/8	0.025	1-7/8	1-7/16
B -3	2	PR-2	8-3/8	2-1/8	0.025	1-7/8	1-7/16
C -3	2	PR-2	8-3/8	2-1/8	0.025	1-7/8	1-7/16

3.3.5 Lens.

3.3.5.2 Spot lens. The spot lens shall project a concentrated beam of light such that the projected spot of light showing on a screen, the plane of which is perpendicular to the optical axis of the flashlight at a distance of 5 feet from the lens, shall not exceed 9 inches in diameter.

3.3.5.2 Diffusion lens. The diffusion lens when assembled to the flashlight shall project a beam of light such that the pattern shows on the screen, the plane of which is perpendicular to the optical axis of the flashlight, at a distance of 4 feet from the lens, shall be between 60 and 80 inches in diameter. The light pattern shall have uniform distribution of light except at the center where some concentration of light is desired.

3.3.5.3 Lens transmission. The light transmission of either lens shall be at least 83 percent.

3.3.6 Lamp and lampholders. The lamps furnished with the flashlights shall be prefocused miniature flange base, tungsten filament, single contact of the commercial type PR2 or PR6. The PR2 lamp shall be used for all tests. The PR6 lamp will be furnished in lieu of the PR2 lamp if requested by the contracting officer. The lamp shall be solidly retained in place in the lampholder. Means shall be provided to prevent the dry cells from damaging the base of the lamps when tested as specified in section 4. The type D dry cells shall be held against the lampholder by a helical spring or other acceptable means.

3.3.7 Switch. The switch shall be mounted on the side of the case and shall be a slide type which will be solidly retained in position when placed in either the "on" or "off" positions. When specified (see 6.2), a flashing position shall be provided. Switches shall resist accidental movement to the "on" position. The switch slide or button shall be designed to permit easy manipulation with one hand. The design and construction of the switch mechanism shall be such, that it will operate in a satisfactory manner for 35,000 continuous cycles at a minimum rate of 15 cycles per minute (see 4.4.11). The construction shall be such, that with the flashlight completely assembled, fresh dry cells in place, and the switch in the "off" position, it shall be impossible to energize the lamp by bridging any two points on the exposed surface of the electrical conductor.

3.3.8 Belt clip. The flashlights shall be furnished with a spring clip on the back and parallel to the longitudinal axis of the case, on the upper half of the flashlight. The open end of the clip shall face the butt end of the flashlight and have a minimum spring tension of 2 pounds against the case of the flashlight. The tip of the bottom of the clip shall be curved away from the case so that a 1/8 inch rod may readily pass into the spring tension area. The loop of the clip shall be sufficient to receive a rod of rectangular cross section 1/8 inch by 1-1/8 inches with rounded edges. The clip shall be capable of supporting a weight of 25 pounds.

3.3.9 Suspension ring. A suspension ring shall be secured to the bottom cap and fastened in such a manner that it can not be readily detached by hand. The suspension ring arrangement shall be so designed that the ring will seal firmly to and recess in the end cap. The suspension ring shall be capable of supporting, without distortion, a weight of 15 pounds for the style A and 25 pounds for the style B and style C.

3.3.10 Interchangeability. All corresponding parts of flashlights of the same type, style, class and manufacturer shall be mechanically and electrically interchangeable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

3.3.11 Cleaning. All parts shall be thoroughly cleaned. Traces of corrosive compound used for cleaning, plating, finishing, or machining shall be removed or chemically neutralized to prevent subsequent corrosion.

3.3.12 Workmanship. The flashlights shall be fabricated and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges; markings and dimensions; thoroughness of soldering, painting, and riveting; alignment of parts and toughness of assembly screws.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.1.1 Inspection conditions. Unless otherwise specified herein, all inspections shall be made at room temperature, pressure and humidity.

4.2 Sampling

4.2.1 Visual and mechanical. Sampling for visual and mechanical inspection shall be conducted in accordance with MIL-STD-105, inspection level S-4, acceptable quality level (AQL) 2.5.

4.2.2 Tests. Sampling for tests shall be conducted in accordance with MIL-STD-105, inspection level S-3, AQL 2.5.

4.3 Inspection. A visual and mechanical inspection shall be conducted in accordance with but not limited to the following classification of defects:

VISUAL AND MECHANICAL INSPECTION

Material	Parts or accessories missing or not as specified.
Dimensions	Not as specified.
Threaded Parts	Not as specified.

4.4 Tests.

4.4.1 Illumination readings. Illumination readings shall be taken with assembled flashlight. The flashlight shall be arranged so that its beam is projected on a screen, the plane of which is perpendicular to the optical axis of the flashlight with ten (10) feet between the lens and the screen as described below. For test purposes, the geometric center of the projected beam of light may be considered the point at which the optical axis of the flashlight pierces the test plane. Concentric circles one of eight (8) inch diameter and one of four (4) inch diameter shall be drawn on the screen.
The intersection of these circles with their vertical and horizontal diameters shall be indicated. The intensity of the light falling on the screen at the eight (8) points of intersection and at the center of the circles shall be read using a light sensitive element having a diameter of 1.50 $\pm$ 0.05 inches, centered on the points. The flashlight shall be turned on for 15 second intervals, and the reading for a point shall be taken at the end of the time interval. The flashlight will be turned off for 30 seconds between readings. The center point shall be read first, followed by the points on the inner circle and the points on the outer circle.
Conversion formula: Candle power = 100 X meter reading in foot candles. The light measuring equipment shall have a known accuracy of $\pm$ 5 percent or better. The illumination (candle power) shall be equal to or better than, 300 minimum to an average of 450 for the center point, and the four points on the four inch circle 125 minimum to an average of 200 for the four points on the eight (8) inch circle.

4.4.2 Dimensional and material stability test. The following test shall be made on completely assembled flashlights, including batteries, or dummies of equal weight and size. The flashlight shall be placed on a horizontal surface and subjected to a temperature of 150° F $\pm$ 5° F dry heat for 16 hours, followed by a temperature of 110° F $\pm$ 2° F at 90 percent relative humidity for 6 hours. The flashlights shall then be compared with untested flashlights for dimensional stability, crazing of surface, and other defects. The parts of the tested samples shall be interchangeable with

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

corresponding parts of untested samples, and, after new batteries have been installed shall be operable (see 3.3.4) and (3.2).

4.4.3 Impact. The style B and C flashlights shall be subjected to a temperature of minus 30° ± 5° F. The style A flashlights shall be subjected to a temperature of minus 20° ± 5° F. The flashlights shall be subjected to the temperatures indicated above for 2 hours and shall then be subjected to a 12 inch-pound impact using a 1 pound steel ball. The impact shall be applied (a) to the outside of the case tube at a point on the side opposite the switch; (b) to the head; (c) to the bottom cap; and (d) to lens ring. Failure to operate normally, or any chipping or cracking shall constitute failure of this test.

4.4.4 Drop test. The assembled flashlight complete with dry cells, lamps and lenses shall be dropped in a free fall through a distance of twelve (12) feet on the center of a bed of loose sand. The sand shall be at least 2 feet by 2 feet by 6 inches deep and the exposed surface shall be smoothed to a horizontal plane prior to each drop. Style A flashlight shall be dropped 6 times, style B and C flashlights shall be dropped 10 times in a vertical position upon the head of the flashlight, and 10 times in the vertical position upon the base of the flashlight. At the completion of the test the flashlights shall remain intact without cracks or damage to any part.

4.4.5 Oil test. Two samples out of each lot shall be submerged in a mineral oil bath, maintained at 125° F, for 15 minutes. The flashlights shall be carefully examined before and after the immersion bath. Any change in face, finish, color, dimensions or any other physical defects shall be considered as failure of this test. Style B and C flashlight shall be fully charged prior to test and shall function properly with equal light intensity before and immediately after removal from the oil bath. The exterior parts of the flashlight may be wiped clean before checking light intensity. A lot shall be considered as those items of the same type, style and class in a single order.

4.4.6 Gasket test, (excluding style A). Two flashlights shall be completely assembled including batteries. All component parts that are threaded and seat against a gasket shall be backed off a minimum of two (2) complete threads and then retightened to a waterproof condition. This shall be considered as one test cycle. There shall be a minimum of forty (40) test cycles all of which shall use the same torque pressure as used in the first test cycle. The maximum torque in inch pounds shall be established by the manufacturer, and shall not exceed 25 inch pounds. The established torque shall be maintained within ± 1/2 inch pound throughout the entire test. The component parts in each cycle shall remain for two minutes under manufacturer's designated torque pressure. Upon completion of the last cycle of operation the flashlights shall remain in the test tightened condition without changes of any kind and shall be used as samples in the watertightness test as specified in 4.4.7.

4.4.7 Watertightness (excluding style A). The specified test in 4.4.6 shall directly precede this test. The flashlights tested in 4.4.6 shall be submerged for a period of one hour to a depth of 3 feet below the surface of a 10 percent solution of sodium chloride at a room temperature of 25° ± 5° C. The flashlights shall then be wiped dry and checked for compliance with paragraph 3.2.5. The additional quantity of flashlights required under the sampling plan shall be charged with batteries and a torque of inch pounds as specified in 4.4.6 shall be applied to all threaded parts, and then submerged for a period of one hour to the depth of 3 feet below the surface of clear water, at room temperature 25° ± 5° C. The flashlights shall then be wiped dry and checked for compliance with paragraph 3.2.5.

4.4.8 Thread test. Starting with the case of the flashlight disassembled, it shall be assembled applying a maximum measured toque of 25 inch pounds to all threaded parts. The threaded parts shall then be examined to determine compliance with the first stated requirement of 3.3.3. A measured torque of 75 inch pounds ± 2 inch pounds shall then be applied to each of the threaded parts. The threads shall be examined for compliance with the second stated requirements of 3.3.3.

4.4.9 Battery spring test. With the lens ring, lens, reflector, and lampholder removed, the flashlight resting on its base, and the required number of dry cells of minimum size in place, a force shall be applied to the top of the upper dry cell as necessary to depress the spring and move the dry cells relative to the case to the position which they will occupy when the flashlight is completely assembled. For flashlights that cannot be so tested because of their design, comparable tests shall be made that will indicate that these flashlights meet spring extension and strength requirements of 3.3.2.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

4.4.10 Lens. The spotlight and diffusion lenses shall be tested to determine compliance with 3.2.2 and 3.3.5.

4.4.11 Switch. Flashlights shall be tested as follows: The sustained contact switch mechanism of the flashlight shall be tested by operating the button for 35,000 continuous cycles at a minimum rate of 15 cycles per minute, not to exceed 30 cycles per minute. A cycle shall consist of movements from "off" position to full "on" position and back to "off" position. The switch shall be operated under normal electrical load conditions and the lamp and batteries shall be renewed as often as required to assure that the switch mechanism is operating under normal load throughout the 35,000 cycles (see 3.3.7).

4.4.12 Belt clip. Belt clips shall be tested to determine compliance with 3.3.8 and subjected to the following tests: The flashlight shall be held in a horizontal plane, with the belt clip downward, a 2 pound weight shall then be suspended for one minute from the belt clip at its point of contact with the case. During this test, the clip shall not lose contact with the case. With the flashlight held in a horizontal plane with the belt clip up, a metal rod of rectangular cross section 1/8 inch by 1-1/8 inches with rounded edges shall be passed through the spring tension arc and withdrawn constituting 1 cycle. This test shall be operated for 100 cycles for style A flashlights, 250 cycles for style B flashlights, and 500 cycles for style C flashlights, at a rate not to exceed 10 cycles per minute. At the end of this test the belt clip shall still remain in contact with the case. With the flashlight held in vertical position with the butt end up, a weight of 25 pounds shall be suspended from the belt clip at its point of anchor with the case. The belt clip shall not loosen from the case (see 3.3.8).

4.4.13 Suspension ring. The suspension ring shall be tested by suspending a weight of 25 pounds for styles B and C, 15 pounds for the style A, from the ring for a period of 1 minute with the flashlight in a vertical position, base down, to determine compliance with 3.3.9. After this test the ring shall show no sign of distortion.

4.4.14 Salt spray (style B and C only). The flashlights, without batteries, shall be subjected to a salt spray test in accordance with Fed. Test Method Std. No. 151, method 811, for a period of 100 hours. Upon completion of the test, the flashlights shall be washed with fresh water, dried, and examined (see 3.2.5).

4.5 Inspection of preparation for delivery. An inspection shall be made to determine that the packaging, packing and marking comply with the requirements in section 5 of this specification. Defects shall be scored in accordance with table II. The sample unit shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects.

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; improper size; location, sequence, or method of application
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C as specified (see 6.2).

5.1.1 Level A. Each flashlight shall be individually packaged in accordance with submethods 1C-2 of MIL-P-116.

5.1.2 Level B. Each flashlight shall be packaged in a snug-fitting paperboard box conforming to PPP-B-665, PPP-B-566, or PPP-B-676. The container shall be secured to prevent accidental opening.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

5.1.3 Level C. Each flashlight shall be packaged to afford adequate protection against deterioration and damage during shipment from the supplier to the initial destination.

5.1.4 Intermediate packaging. Twelve flashlights of one stock number packaged as specified in 5.1 shall be intermediate packaged in a paperboard box conforming to PPP-B-566, PPP-B-665 or PPP-B-676. Each box shall be secured to prevent accidental opening.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Flashlights of like description in quantities as specified (see 6.2) shall be packed in a close-fitting box conforming to PPP-B-601, overseas type; or PPP-B-621, class 2. The boxes shall be closed and strapped in accordance with the appendix to the applicable box specification. When the gross weight exceeds 250 pounds, skids shall be provided in accordance with the applicable box specification.

5.2.2 Level B. Twelve intermediate packages concisting of 144 flashlights shall be packed in a fiberboard box conforming to PPP-B-636; class domestic, grade 275. Closure shall be in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The flashlights shall be packed to insure carrier acceptance and safe delivery at destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking. Marking shall be as specified in 5.3.1 or 5.3.2 (see 6.2).

5.3.1 Civil agency marking. In addition to markings required by the contract or order the interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agency markings. In addition to markings required by the contract or order the interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Flashlights covered by this specification are suitable for use by personnel in the repair and maintenance of equipment. The 3 styles specified herein are intended for the following uses:

Style A - General use.
Style B - General all around use including working in and around water.
Style C - Areas where danger from explosions of surrounding combustible gases, dust, or explosives are present.

6.2 Ordering data. Purchasers should select the preferred options offered herein and include the following data in procurement documents:

(a) Title, number, and date of this specification.
(b) Type, style, and class required (see 1.2.1).
(c) Switch with flashing position, if required (see 3.3.7).
(d) Color of case (see 3.2.3.3).
(e) Responsibility for inspection, if other than specified (see 4.1).
(f) Quantity of unit packages of flashlights required in shipping container (see 5.2.1).
(g) Selection of the applicable level of packaging and packing required (see 5.1 and 5.2).
(h) Marking, if other than specified (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.