A-A-436
October 12, 1979

COMMERCIAL ITEM DESCRIPTION

DRIVER, PROJECTILE UNIT, .38 CALIBER, UNDERWATER

The General Services Administration has authorized the use of this commercial item description.

Salient characteristics:

Designed exclusively for installing fasteners underwater in depths down to 600 feet.
Capable of installing any PATMI standard 3/8 inch diameter, 1-1/4 inch to 4 inches long, threaded stud or drive pin into steel up to 1 inch thick and into concrete of any compressive strength.
Utilizes an expendable barrel preloaded with a .38 caliber charge.
Treated to resist corrosion and wear.
Maximum weight 7-1/2 pounds.
Maximum length 15-1/2 inches.
Furnished with: Carrying case
Instruction and Operation manual
Loading rod
Test barrel
Spare parts kit
Rust preventative lubrication
Lubrication grease

Workmanship. Shall be free of defects that may impair serviceability and durability.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices, and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Preservation, packaging, packing, and marking. The drivers shall be preserved, packaged, and packed in accordance with normal commercial practice to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipment, handling, and storage. The shipping container shall be in compliance with National Motor Freight Classification and Uniform Freight Classification. Marking shall be in accordance with the contract or order.

Note: Assigned National Stock Number (NSN) 5130-00-387-9961.

PATMI Standards are available from the Powder Actuated Tool Manufacturers' Institute, Inc., 331 Madison Avenue, New York, NY 10017.

FSC 5130

GSA DC-01002442

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:08Z
Check the source to verify that this is the current version before use.