MIL-T-3338H
26 June 1987
SUPERSEDING
MIL-T-3338G
16 September 1974

MILITARY SPECIFICATION

* TABLE, FOLDING LEGS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type and size 2 foot by 3 foot table with folding legs (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-1558	- Paint, Stencil
V-T-285	- Thread, Polyester
QQ-S-698	- Steel, Sheet and Strip, Low-Carbon

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7105

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

TT-E-529	- Enamel, Alkyd, Semigloss
TT-F-336	- Filler, Wood, Paste
TT-F-340	- Filler, Wood, Plastic
TT-I-1795	- Ink, Marking, Stencil, Opaque (Porous and Non-Porous Surfaces)
MMM-A-181	- Adhesives, Phenol, Resorcinol, or Melamine Base
MMM-A-188	- Adhesive, Urea-Resin-Type (Liquid and Powder)
PPP-B-636	- Boxes, Shipping, Fiberboard

MILITARY

MIL-C-496	- Clips, End, Strap
MIL-W-530	- Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-B-543	- Buckles, Tongueless and Web Strap
MIL-W-13518	- Wood Preservative: Tetrachlorophenol and Pentachlorophenol, Surface Sealing Compound
MIL-L-35078	- Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-595	- Colors
FED-STD-751	- Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	- Marking for Shipment and Storage
MIL-STD-130	- Identification Marking of U.S. Military Property
MIL-STD-147	- Palletized Unit Loads

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-13-10	- Table, Folding Legs, Field; Assembly and Details
5-13-1871	- Table, Folding Legs; Packaging for Level A and Level B Shipment

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

B 633 - Electrodeposited Coatings of Zinc on Iron and Steel

D 2016 - Standard Test Methods for Moisture Content of Wood

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

UNITED STATES DEPARTMENT OF COMMERCE COMMERCIAL STANDARDS

Voluntary Product Standard PS 1 - Construction and Industrial Plywood

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.3).

3.2 Materials and components. Materials and components shall be as specified herein and on Drawings 5-13-10 and 5-13-1871. Materials not definitely specified shall be of the quality normally used by a manufacturer in standard commercial tables, provided the completed item complies with all provisions of this document. Recycled material may be used (see 6.4).

3.2.1 Steel, sheet and strip, low carbon. The steel sheet and strip shall be low carbon, cold rolled, any temper, quality, finish or edge, as applicable, conforming to 1008-1020 of QQ-S-698.

3.2.2 Wood.

3.2.2.1 Solid wood. Wood shall be uniformly dried without brashness, casehardening, or honeycombing to a moisture content of from 8 to 12 percent at time of assembly when tested as specified in 4.4.1.1. The slope of grain of any piece shall not exceed 1 inch in 10 inches of any face, except that grain dip steeper than 1 inch in 10 inch slope will be permitted, providing such dips do not exceed more than one-third of the face surface on which the dip occurs when tested as specified in 4.5.1. Exposed surfaces of wood members shall be free from bark streaks or pockets; decay; shake; splits; decayed, encased or checked knots; larvae channels; warp and other defects, except that the following will be permissible:

a. Mineral steaks
b. Medium stain that does not obscure the grain
c. Surface checks, not over 4 inches in length, and not grouped
d. Sound, tight, intergrown knots over 3/4 inch in diameter and not at an edge or corner of a piece
e. Holes not exceeding 1/16 inch in diameter and not occurring within 2 inches of each other on exposed surfaces, provided such holes are filled

3.2.2.1.1 Species of wood. Wood shall be any one of the following species:

Beech	Hickory
Birch, sweet or yellow	Pecan
Maple, big leaf, sugar or black (hard)	Oak, red or white
Ash, white	Alder, red
Elm, rock	Ramin or Meranti

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

* 3.2.3 Plywood, softwood. The plywood shall conform to group 1, HDO-EXT-DFPA of Voluntary Product Standard PS 1. The overlay shall be black in color.

3.2.4 Adhesive. The adhesive shall conform to MMM-A-188 or to type I or II, class 1 of MMM-A-181.

3.2.5 Buckles, tongueless and web strap. The buckles shall conform to type II, style 1, class 1, size 1, of MIL-B-543.

3.2.6 Clips, end strap. The clips shall conform to type I, class 1, size 1-inch of MIL-C-496.

3.2.7 Webbing, textile, cotton, general purpose, natural or in colors. The webbing shall conform to type II, class 4, 1-inch wide of MIL-W-530 and the color shall be Olive Drab 7.

3.2.8 Thread, polyester. The thread shall conform to type I or II, class I, size FF of V-T-285. The color shall be Olive Green S-1, Cable No. 66022.

3.2.9 Wood preservative. The preservative shall conform to type II of MIL-W-13518.

3.2.10 Ink, marking, stencil. The marking stencil ink shall conform to type I of TT-I-1795 and the color shall be black.

* 3.2.11 Paint, stencil, flat. The stencil paint shall conform to A-A-1558 and the color shall be black.

3.2.12 Hardware. The hinges, screws, bolts, rivets, burrs, and nuts shall be commercial items as specified on Drawing 5-13-10. At the option of the contractor, a truss head bolt or a round head step bolt may be used in lieu of the button head bolt.

3.2.13 Filler, wood, paste. The wood paste filler shall conform to TT-F-336.

3.2.14 Filler, wood, plastic. The plastic wood filler shall conform to TT-F-340.

3.2.15 Enamel. The enamel shall conform to TT-E-529. The color shall be Olive Drab 24037 to FED-STD-595.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

3.3 Construction. The table shall be fabricated in accordance with the design, details, dimensions, and materials, as shown on Drawing 5-13-10 and as specified herein. When placed on a flat level surface, the assembled table shall not rock more than 1/16 inch when tested as specified in 4.5.2. The hinged components shall not bind when the table is opened or closed.

3.3.1 Wood components. All surfaces of wood components shall be sanded to a smooth surface. All exposed surfaces of corners and edges shall be rounded.

3.3.1.1 Table top. The table top shall be fabricated from the plywood specified in 3.2.3. The top surface shall be smooth with no visible sign of protrusions.

3.3.1.2 Leg, leg stays, and leg stretcher. The legs, leg stays, and leg stretcher shall be fabricated from either one or two pieces of the wood specified in 3.2.2.1.1. In the two-piece wood construction, the pieces of wood shall be of the same species, the same approximate thickness, and shall be not less than 2 inches wide. The joint surfaces of the two pieces of wood shall be edge glued with the adhesive specified in 3.2.4, applied in accordance with 3.3.6.

3.3.1.3 Cleats. The cleats shall be fabricated from one piece of the wood specified in 3.2.2.1.1.

3.3.2 Screws. All screws shall be driven straight into place. The heads of the screws shall be flush with the surface or countersunk when applicable, as specified on Drawing 5-13-10.

* 3.3.3 Tee nuts. The tee nuts shall be attached to two hinge plates as shown on Drawing 5-13-10. The hinge plates shall be attached at the base of the table using adhesive conforming to MMM-A-188 or type I or II, class 1 of MMM-A-181 and eight each 7/8 inch L, No. 10 Flathead sheet metal screws. The leg hinges will than be attached to these boards.

3.3.4 Fastening clamp assembly. The fastening clamp assembly shall consist of clamp, bolt, rivet and wing nut. The clamps shall be fabricated from the material specified in 3.2.1. The clamps shall be riveted to each end of the leg spreaders. The rivets shall be set to permit the rotation of the clamps without binding. The ends of the bolts shall be peened after assembly of the wing nut with no evidence of cracks.

3.3.5 Clamp retainers. The retainers shall be fabricated from the material specified in 3.2.1. The retainers shall be fastened to the underside of the table in the location shown on Drawing 5-13-10.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

3.3.6 Application of adhesives. The adhesive shall be applied to joint surfaces in the manner recommended by the adhesive manufacturer. Pressure, pressing time, assembly periods, and curing temperature shall conform to the recommendations of the adhesive manufacturer.

3.3.7 Strap assembly. The strap shall be fabricated of the material specified in 3.2.7 and the thread shall be as specified in 3.2.8. The end clips shall be as specified in 3.2.6. The buckle shall be as specified in 3.2.5.

3.3.7.1 Machine stitching. The stitching shall have from six to eight stitches to the inch and shall be type 301, conforming to FED-STD-751. The tension on the thread shall permit no loose stitches. When a single needle sewing machine is used, the last end stitches shall be overstitched a minimum of 1/2 inch. When an automatic box stitching machine is used, the ends of the stitches shall be overlapped at least two stitches.

3.3.7.2 Setting of end clips. One end of the webbing shall be inserted the full depth of the end clip. The end clip shall be securely attached without cutting or fraying the webbing, and shall be flat, of the same thickness and width as the webbing.

3.4 Finish.

* 3.4.1 Steel components. Prior to assembly, all steel components, except the fastening clamps, shall be given a zinc coat conforming to type IV of ASTM B 633. The components shall then be given a coat of black Japan or Olive Drab enamel.

3.4.1.1 Fastening clamp assembly. The welded clamp and bolt shall be finished as specified in 3.4.1. Prior to assembly, the wing nut shall be finished as specified in 3.4.1.

3.4.2 Wood components.

3.4.2.1 Surface preparation.

3.4.2.1.1 Table top. All exposed side and end surfaces of the table top shall be filled with the wood filler specified in 3.2.13. All filled areas shall be sanded smooth, cleaned in accordance with the manufacturer's commercial practice, and given a coat of the preservative specified in 3.2.9.

3.4.2.1.2 Legs, stays, spreaders and cleats. All surfaces of the legs, stays, spreaders and cleats shall be sanded smooth, cleaned in accordance with the manufacturer's commercial practice, and given a coat of preservative specified in 3.2.9.

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the current version before use.

3.4.3 Enamel. All exposed surfaces of the wood components (including plastic wood filled counterbores of the table top), except the top and bottom surfaces of the table top, shall be given a coat of the enamel specified in 3.2.15.

3.5 Marking for identification. The table shall be marked for identification in accordance with MIL-STD-130 and as shown on Drawing 5-13-10. The marking medium shall conform to 3.2.10 or 3.2.11.

3.6 Workmanship. All surfaces of the finished table shall be free of burrs, slivers, and rough or sharp edges. Components shall not be broken, cracked, split, or malformed. Wood components shall be free from skips, chipped or torn grain, planer or other machine marks. The welding shall be free from pits, burn throughs, flashes, scale, or foreign matter. The enamel coating shall level out to a continuous, smooth, dry adherent film thickness without runs, drops, streaks, or area of no film. The coating shall be free from imbedded foreign matter and shall show no evidence of peeling, flaking, or blistering.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirement in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the currentversion before use.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.3), it shall be examined as specified in 4.4.4 and 4.4.5 and tested as specified in 4.5.2. The presence of any defect or failure of any test shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.4.1.1 Testing for moisture content of wood. Moisture content of wood requirement in 3.2.2.1 shall be determined in according with ASTM D 2016 at time of assembly, except that, when testing is performed by the electric moisture meter method, three determinations shall be made on each sample unit. The average of the three determinations shall be the moisture content of the sample unit. The lot size shall be all machined components prepared under the same conditions, stored as a group, and offered for inspection at one time. The sample unit shall be one piece of wood. The inspection level shall be S-1 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.0.

* 4.4.1.2 Testing for slope of wood grain. The slope of wood grain requirement specified in 3.2.2.1 shall be determined in accordance with 4.5.1. The lot size shall be all the solid wood offered for inspection at one time, prior to assembly. The sample unit shall be one piece of solid wood. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 1.0

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the current version before use.

4.4.2 In-process examination. Examination shall be made during the manufacturing process for requirements specified in table I. Whenever nonconformance is noted, correction shall be made to affected items and process.

TABLE I. In-process inspection

Requirement	Requirement paragraph
Zinc coating of steel components	3.4.1
Preservative coating of table sides, ends, and tee nut counterbores	3.4.2.1.1
Preservative coating of legs, stays, spreaders and cleats	3.4.2.1.2

* 4.4.3 Intermediate inspection. Inspection shall be made of the table for the defects specified in table II. The lot size shall be expressed in units of tables, prior to application of the enamel and after complete assembly, except for the straps. The sample unit shall be one table. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 1.0 for major defects and 6.5 for total defects.

TABLE II. Intermediate visual defects

Examine	Defect	Classification	
		Major	Minor
Wood components	Not specified species of wood		201
	Bark streaks or pocket		202
	Decay; shakes or splits	101	
	Decayed, encased, or checked knots	102	
	Larvae channels; warp	103	

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the current version before use.

TABLE II. Intermediate visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Wood components - continued	Medium stain that obscures the grain		203
	Surface checks over 4 inches in length	104	
	Sound, tight intergrown knots over 3/4 inch	105	
	Any knot at edge or corner	106	
	Holes over 1/16 inch diameter and within 2 inches of each other and not filled		204
	Not free from skips, chipped or torn grain, planer or other machine marks		205
Construction, assembly and workmanship			
Legs, leg stays, and leg spreader	Receiving hole for screw not countersunk where required		206
	Vertical edge of leg not smooth		207
	More than two pieces		208
	Excess glue not removed		209
Two-piece construction	Pieces not same species of wood, each piece less than 2 inches wide, or not edge-glued		210
Cleats	Not from one piece of wood		211
Table top	Exposed side end surfaces not filled completely with wood filler	107	
	Side, end surfaces not sanded smooth and cleaned		212
	Any exposed edge or corner not rounded		213

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the currentversion before use.

4.4.4 End item visual examination. The end item shall be examined for the defects listed in table III. The lot size shall be expressed in units of tables. The sample unit shall be one table. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 1.0 for major defects and 6.5 for total (major and minor combined) defects.

TABLE III. End item visual defects

Examine	Defect	Classification	
		Major	Minor
Finish	Not type specified	X	
	Color not as specified		X
	Area of no film		X
	Contains streaks, runs, drops, grit or wrinkles		X
	Dirt, grit or foreign material imbedded in finish		X
Construction	Component not type, size or shape specified	X	
	Component loose or missing	X	
	Component broken, cracked, split or malformed	X	
	Component in wrong location	X	
	Hinged components bind	X	
	More than one screw loose	X	
Leg stays	Edge not flush with top of legs		X
	End not flush with edge of leg		X
Table top	Top surface not smooth with visible signs of protrusions		X
Fastening clamp	Bolt not welded to fastening clamp bolt		X
	Less than three welds on bolt head		X
	End of bolt not peened		X

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the current version before use.

TABLE III. End item visual defects - Continued

Examine	Defect	Classification	
		Major	Minor
Strap assembly	Webbing frayed or cut		X
	Less than minimum stitches per inch	X	
	Wrong stitch type, loose stitches	X	
	End stitches not overstitched or overlapped as specified		X
Identification marking	Missing, illegible, incomplete, wrong location, or not as specified		X

* 4.4.5 End item dimensional examination. The end item shall be examined for the dimensions annotated with an asterisk on the drawings. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of tables. The sample unit shall be one table. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

* 4.4.6 End item testing. The end item shall be tested as specified in 4.5.2. The lot size shall be expressed in units of tables. The sample unit shall be one table. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.0.

4.4.7 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified

Source: https://assist.dla.mil -- Downloaded: 202640-16T17:31Z
Check the source to verify that this is the currentversion before use.

Examine	Defect
Workmanship	Inadequate application of components, such as incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

* 4.4.8 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1, and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement
Palletization	Pallet pattern not as specified Interlocking of loads not as specified Load not bonded with required straps as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

4.5 Methods of inspection.

4.5.1 Slope of wood grain. The slope of grain requirement in 3.2.2.1 shall be determined by combining the grain direction of two adjacent faces of a square or rectangular piece. When one of these faces is straight grained, the true slope of grain is shown on the other face. When there is a slope on both faces, the true or combined slope is greater than the slope on either face. Slope of grain is shown on edge-grained faces by summer-wood bands; by the direction in which a free-flowing ink or dye spreads; by the course taken by a narrow strip lifted by a knife point and torn out; or by the Teco or equal slope-grain detector.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

4.5.2 Level test. The table shall be set on a flat, level surface and alternately rocked at diagonally opposite corners. Rocking more than 1/16 inch on either of the diagonally opposite corners constitutes failure of this test.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial, as specified (see 6.2).

5.1.1 Level A. Tables shall be preserved as shown on Drawing 5-13-1871.

* 5.1.2 Commercial. Tables shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

* 5.2.1 Level A packing. Two tables, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style FOL (end-opening), grade V2s of PPP-B-636. Closure shall be in accordance with the appendix of PPP-B-636, except that inspection shall be as specified in 4.4.7. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Two tables, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to style FOL (end-opening), type CF, variety SW, or type SF, class domestic, grade 275 of PPP-B-636. Closure shall be in accordance with method II of the appendix of PPP-B-636, except that inspection shall be as specified in 4.4.7.

5.2.2.1 Weather-resistant containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636, except that inspection shall be as specified in 4.4.7. Closure shall be in accordance with the appendix of PPP-B-636.

* 5.2.3 Commercial packing. Tables, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), tables, packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV or type V in accordance with MIL-STD-147. Each prepared load shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be in accordance with appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing the pattern of each course.

* 5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Intended use. The table is intended to be used as a utility table in the field.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.3).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. Type and class of unit load required (see 5.2.1).
e. When weather-resistant grade fiberboard shipping containers are required for Level B packing (see 5.2.2.1).
f. When palletization is required (see 5.3).

* 6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.5 Subject term (key word) listing.

Field table
Folding legs, table
Table

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T17:31Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, as written, irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - ME
Air Force - 84

Preparing activity:

Army - GL

Project No. 7105-0256

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the currentversion before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US Army Natick Research, Development, and
Engineering Center
Natick, MA 01760-5014

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
STRNC-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research, Development,
and Engineering Center
ATTN: STRNC-ES
Box 14A
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-3338H	Table, Folding Legs

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP, 1 Apr 84

Source: https://assist.dla.mil -- Downloaded: 202610-16T17:31Z
Check the source to verify that this is the current version before use.