MILITARY SPECIFICATION

TRAILER, MUNITIONS HANDLING MHU-110/M

1. SCOPE

1.1 This specification establishes the requirements for manufacture and acceptance of the MHU-110/M munitions handling trailer.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Federal

QQ-R-566	Rods, Welding, Aluminum and Aluminum Alloys
QQ-S-781	Strapping, Steel, Flat and Seals
VV-B-680	Brake Fluid, Automotive
PPP-B-601	Boxes, Wood, Cleated-Plywood

Military

MIL-A-2550	Ammunition and Special Weapons, General Specification For
MIL-F-3541	Fittings, Lubrication
MIL-R-5031	Rod and Wire, Welding, Corrosion and Heat Resistant Alloys
MIL-R-5632	Rods and Wire, Steel, Welding
MIL-S-7742	Screw Threads, Standard, Optimum Selected Series, General Specification For
MIL-M-8090	Mobility Requirements, Ground Support Equipment, General Specification For
M1L-A-8421	Air Transportability Requirements, General Specification For
MIL-W-8604	Welding of Aluminum Alloys, Process For

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

MIL-W-8611	Welding, Metal Arc and Gas, Steels, and Corrosion and Heat Resistant Alloys, Process For
MIL-G-10924	Grease, Automotive and Artillery
MIL-P-1S024	Plates, Tags and Bands for Identification of Equipment
MIL-I-45208	Inspection System Requirements

STANDARDS

Military

MIL-STD- 109	Quality Assurance Terms and Definitions
MIL-STD- 129	Marking for Shipment and Storage
MIL-STD- 130	Identification Marking of U. S. Military Property
MIL-STD- 143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-281	Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies, Preservation and Packaging of
MIL-STD-480	Configuration Control, Engineering Changes, Deviations and Waivers
MIL-STD-808	Finish, Protective and Codes for Finishing Schemes for Ground and Ground Support Equipment
MIL-STD-810	Environmental Test Methods
MIL-STD-889	Dissimilar Metals
MIL-STD-1186	Cushioning, Anchoring, Bracing, Blocking and Waterproofing, with Appropriate Test Methods

DRAWINGS

U. S. Air Force

68E6881	Main Rail Assembly
68E6899	Main Structure, Drilling Detail
68E6900	Trailer, Munitions Handling MHU-110/M
68E6901	Main Structure Weldment
68E6910	Front Axle and Wheel Assembly
68E6959	Rear Axle and Wheel Assembly
68E6960	Deck Plate
69C6940	Stiffener

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity, or as directed by the Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Item definition. The MHU-110/M munitions handling trailer is a six-wheel flatbed trailer configured with accessory equipment to allow transport of Air Force munitions [single or pre-loaded) to the flight line from munitions storage areas. The trailer has a capacity of 15,000 pounds, and is capable of negotiating a Type III mobility course as outlined in MIL-M-8090. The trailer has also the capability of traversing (fifty passes) a soil having a vehicle rating cone index (RCI_{50}) equal to 45.

3.1.1 Major component list. The major components components of the trailer are as follows:

a. Body
b. Chassis
c. Accessory equipment

3.2 Characteristics.

3.2.1 Performance.

3.2.1.1 Brake system. Parking and service brakes shall be provialed as specified in MIL-M-8090. Service brakes shall be the inertia-actuated hydraulic type with a one-second delay dumping cycle to permit trailer backup. The pressure release (dumping cycle) shall be accomplished automatically.

3.2.1.2 Environmental conditions. The trailer shall withstand the following conditions without detrimental effect on subsequent operations.

a. High temperature +125°F
b. Low temperature -65°F
c. Sand and dust
d. Rain

3.2.1.3 Structural strength. The trailer shall be capable of withstanding the following loads without incurring damage or permanent set.

a. 15,000 pounds supported by diagonally opposite wheels with 20% on the front wheel and 80% on the rear wheels.

b. 45,000 pounds with 20% on the front wheels and 80% on the rear wheels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

3.2.1.4 Turning capability. The trailer shall be capable of executing a turn radius of 175 inches or less at 10 miles per hour (mph) without evidence of tipping, i.e. wheels not making contact with the ground, when loaded-in the following conditions.

a. 5000 pounds on any one side of trailer
b. 3000 pounds on any one corner of trailer

3.2.1.5 Electrical system. The electrical system shall be compatible with both a twelve and twenty-four volt power source.

3.2.1.6 Readability. The trailer, loaded and unloaded, shall be capable of being towed at speeds up to and including 20 to 35 mph, respectively, without any visible. deviations from the tow vehicle wheel path.

3.2.1.7 Accessories.

3.2.1.7.1 Rail system. The rail system (main rail and munition chocks) shall be capable of moving a cylindrical shape (similar to the size of a M-118 bomb) of 3000 pounds from one side of the trailer to the other without any binding of the munitions chocks in the main rail.

3.2.1.7.2 Rail extender. Two rail extenders, when installed on trailer, shall be capable of supporting 9000 pounds evenly distributed.

3.2.1.8 Air transportability. The trailer shall conform to the requirements of MIL-A-8421.

3.2.1.9 Height The overall height of the trailer bed shall be 30 inches ± 1/8 inch unloaded at a tire pressure of 32 pounds per square inch (psi).

3.2.1.10 Weight. The total weight of the trailer, excluding accessories shall be 3600 pounds ± 10 percent. The accessories are the munitions trolley assemblies, rail assemblies, rail extenders, explosive signs, tie down straps and stake panels.

3.2.1.11 Configuration control. Configuration control shall be performed in accordance with MIL-STD-480.

3.3 Design and construction.

3.3.1 Production drawings. The configuration of the trailer shall conform to Air Force Drawing 68E6900. If this specification and the drawing conflict, the specification shall govern. Any discrepancy, deficiency, or ambiguity shall be forwarded immediately to the contracting officer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

3.3.2 Standards of manufacture.

3.3.2.1 Metals. Metals shall be of the corrosion-resistant type, or suitably treated to resist corrosion due to fuels, salt spray, or atmospheric conditions likely to be met in storage or normal operation. When materials are used in the construction of the trailer that are subject to corrosion, they shall be protected against such corrosion in a manner that in no way prevents compliance with the requirements of this specification. The use of any protective coating that will crack, chip or scale with age or extremes of atmospheric conditions shall not be acceptable.

3.3.2.2 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.3.2.3 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein or on the applicable drawings shall be selected according to MIL-STD-143, except as provided in 3.3.2.4.

3.3.2.4 Commercial parts. Commercial parts having identical or better design properties and parameters than the MS and AN part numbers listed on the applicable drawings may be used where, on the date of request for proposal or invitation for bids, there are no equivalent standard parts readily available. In any case, commercial utility parts, like screws, bolts, nuts and cotter pins, having identical or better design properties may be used provided they are completely interchangeable with standard parts (MS or AN) without alteration. Configuration of the first article trailer and components thereof shall remain the same throughout the production effort except for approved changes.

3.3.2.5 Screw threads. Screw threads shall be in accordance with MIL-S-7742.

3.3.2.6 Welding. Welding shall conform to MIL-W-8604 for aluminum and aluminum base alloys and MIL-N-8611 for ferrous materials. Rods for welding aluminum shall conform to QQ-R-566. Rods for welding common steels and corrosion resisting steels shall conform to MIL-R-5632 and MIL-R-5031, respectively.

3.3.2.7 Lubrication. Grease for chassis lubrication shall conform to MIL-G-10924. Grease fittings shall be in accordance with MIL-F-3541. All grease fittings shall be accessible for pressure type lubrication without need for disassembly of any part of the trailer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

3.3.2.8 Painting. Each item to be painted as determined by related drawing requirements shall be cleaned and painted in accordance with the procedures outlined in the applicable drawings. In the absence of a specific drawing requirement, painting shall be in accordance with MIL-STD-808, yellow color nr, 13538, film designation DG. Finish processes shall be in accordance with MIL-STD-808, Type I exposure, finish code F-304 for aluminum and aluminum base alloys and finish code F-103 for all ferrous alloys.

3.3.2.9 Brake fluid. Brake fluid shall conform to W-B-680.

3.3.2.10 Identification of product, Except as noted in the procuring document, equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130 and applicable drawings. The identification plate shall be in accordance with MIL-P-15024.

3.3.3 Workmanship. The trailer, including all parts and accessories, shall be fabricated in a manner that will insure that the criteria of appearance, fit and adherence to specified tolerances shall be observed. Particular attention shall be given to neatness and thoroughness of marking of parts and assemblies, plating, printing, riveting, machine screw assemblage and welding. All parts shall be free from burrs and sharp edges which might mar associated equipment or cause injury. to using personnel. Workmanship shall be in accordance with MIL-A-2550.

3.4 Maintainability.

3.4.1 Wheels and tires.

3.4.1.1 The inside tires shall incorporate a valve stem that allows access for inflating the tires.

3.4.1.2 The tires and wheels shall be capable of being removed with standard or commercial tools.

3.4.1.3 Dual wheel assembly shall be such that outer wheel can be removed independent of inner wheel and such that the inner wheel and outer wheel can be removed simultaneously.

3.4.2 Brakes.

3.4.2.1 The brakes shall have the capability of being adjusted without removal of wheel assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:17Z
Check the source to verify that this is the current version before use.

3.4.2.2 The brake system shall possess the capability of preventing dust and foreign matter from getting into the brake system.

3.4.2.3 The brake system shall be such that the brake adjuster mechanism is accessible.

3.4.2.4 The brake line installation shall be such that any line can be replaced in not more than thirty minutes with standard or commercial tools by one man.

3.4.2.5 The brake line shall be installed such that visual inspection can be performed by maintenance personnel.

3.4.2.6 The parking brake mechanical linkage shall be installed to give access for adjustment.

3.4.2.7 The surge brake shall incorporate a grease fitting so that greasing of the surge brake main guide shaft can be accomplished with standard or commercial tools.

3.4.3 Chassis.

3.4.3,1 Springs. A grease fitting shall be incorporated to allow greasing of spring shackles with standard or commercial tools. The grease fitting shall be accessible to maintenance personnel.

3,4.3.2 Tie rods. A grease fitting shall be incorporated to allow greasing of the tie rods with standard or commercially available tools. The grease fitting shall be accessible to maintenance personnel.

3.4.4 Electrical.

3.4.4.1 The electrical harness shall be fabricated in three sections to allow replacement of any one section in not more than one hour by one man.

3.4.4.2 The electrical harness shall be installed to be visible for inspection by maintenance personnel.

3.4.4.3 Light bulbs shall be accessible with standard or commercial hand tools by maintenance personnel.

3.4.5 Rail and chock system.

3.4.5.1 The rollers on the rail shall be of the permanent lube type.

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:17Z
Check the source to verify that this is the current version before use.

3.4.5.2 The rollers shall possess capability of being removed and reinstalled with standard or commercial hand tools.

3.4.5.3 The munition chock face shall possess the capability of being replaced in not more than ten minutes by one man.

3.5 First article. The first two units, representative of the production trailer, shall be submitted for testing prior to regular production.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless othewise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein unless disapproved by the government. The government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Definitions. Reference may be made to MIL-STD-109 to define inspection terms used herein.

4.2 Preproduction sample.

4.2.1 Inspection to be performed. The assemblies and components shall be inspected for all inspections specified in 4.2.3 of this specification and all additional requirements of the applicable drawings. All tests shall be performed as specified in 4.6.

4.2.2 Submission of product. At the time the completed item of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the item complies with all quality assurance provisions of the approved current written description of the system.

b. Number of items of product inspected.

c. Results obtained for all inspection performed.

d. Drawing, specification number and date, together with an “identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:17Z
Check the source to verify that this is the current version before use.

e. Certificates of compliance on all material purchased by the contractor when such material is controlled by Government specification referenced in any of the contractual documents,

f. Number of items.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2.3 Inspection. Each trailer shall be inspected to insure conformance to the dimension and tolerance on the applicable drawings as noted below. Any trailer failing to meet the inspections shall be rejected until the defect is corrected. The methods of inspections as reflected below shall be by gages when identified by the letter "G" and by visual examination when-identified by the letter"V".

4.2.3.1 Drawing 68E6960.

Categories	Defects	Method of Inspection
Major		
101	.350 hole size incorrect	G
102	Location of .350 holes incorrect	G
Minor		
201	Trailer length and width incorrect	G

4.2.3.2 Drawing 68E6881.

Categories	Defects	Method of Inspection
Maj or		
101	Tube support location incorrect	G

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

4.2.3.3 Drawing 68E6901.

Categories	Defects	Method of Inspection
Major		
101	Location of stiffener incorrect	G

4.2.3.4 Drawing 68E6910

Categories	defects	Method of Inspection
Major		
101	Adjustment of stops incorrect	G
102	Front axle location incorrect	G

4.2.3.5 Drawing 68E6900.

Categories	Defects	Method of Inspection
Major		
101	Wheel toe-in incorrect	G
Minor		
201	Workmanship incorrect	v
202	Material incorrect	v
203	Markings incorrect	v
204	Painting incorrect	v

4.2.3.,6 Drawing 68E6959.

Categories	Defects	Method of Inspection
Major		
101	Lateral location of axle incorrect	G

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

4.2.3.7 Drawing 69 C6940.

Categories	Defects	Method of Inspection
Major		
101	Stiffener holes located incorrect	G

4.2.3.8 Drawing 68 E6899.

Categories	Defects	Method of Inspection
Major		
101	Stiffener hole size incorrect	G

4.3 Test conditions. The test conditions are described under the individual test to which they apply.

4.4 Preproduction testing.

4.4.1 Test sample. See 3.5 of this specification.

4.4.2 Preproduction tests, The first article test shall consist of all tests described in 4.6.

4.5 Acceptance test. Acceptance tests shall consist of the following:

a. Production test
b. Periodic sampling test

4.5.1 Production tests. Production tests are shown in Table I and shall be accomplished on all trailers.

4.5.1.1 Rejection and retest. When any item fails to meet a specification production test requirement it shall be rejected and the cause of failure identified.

4.5.2 Periodic sampling tests. One trailer shall be selected from each 10, or fraction thereof, on the contract or order and subjected to sampling tests. The test sample shall be selected by the procuring activity from production units which have successfully completed all production tests. The sampling tests shall consist of all tests listed in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

4.5.2.1 Rejection and retest. When any item selected from a production run fails to meet the specification, no item still on hand or later produced shall be accepted until the extent and cause of failure are determined and solved.

4.5.2.2 Continuance of production tests. Production tests may be continued at the discretion of the contracting officer pending the investigation of a sampling test failure. However, final acceptance of items on hand or produced later shall not be made until it is determined that the items meet all the requirements of this specification and applicable drawings.

4.5.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items previously accepted. The contractor shall be responsible for correcting the known defect in all units up through the previous sampling test.

4.6 Test methods and Procedures.

4.6.1 Brake system tests.

4.6.1.1 Parking brakes. The loaded [15,000 lb - 80% on rear axles and 20% on front axles) trailer shall be positioned on level, dry concrete surface. Install a dynamometer between the lunette of trailer tow bar and prime mover and/or winch system. A horizontal force of 8S00 lbs shall be applied to the dyamometer/tow bar without wheels of trailer rolling.

4.6.1.2 Inertia brakes.

4.6.1.2.1 The trailer loaded with a 15,000 lb test load shall be backed ten times to determine the capability of the inertia brakes to release in one second or less.

4.6.1.2.2 The trailer loaded with a 15,000 lb test load shall be towed at a speed of twenty miles per hour on a level, dry, concrete surface. The trailer shall be stopped within thirty feet. Trave 1 distance measurement shall be made from the point of first brake application to full stop. This test shall be performed five times, each test performed immediately in succession.

4.6.1.2.3 Fifty sudden stops of the loaded trailer shall be made from 20 mph immediately in succession. At the end of the fiftieth cycle, the brake discs and actuating mechanisms shall be inspected. No overheating causing distortion or obscure physical defects shall he apparent as a result of the fifty stops.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

4.6.1.2.4 It shall be demonstrated that the emergency breakaway system, when actuated, functions the same as the service brake hydraulic system.

4.6.2 Environmental tests. The trailer shall be subjected to the following environmental tests in accordance with MIL-STD-810. Operating temperatures for the trailer shall be -65°Fahrenheit to a +125° Fahrenheit. Storage temperature shall be -80° Fahrenheit for a period of not less than 48 hours. Operations to be performed during the environmental tests shall consist of moving each munitions chock, rolling of the trailer wheels, setting and releasing of the parking brakes, and moving of the trailer tongue to insure that there are no adverse effects when operating in these extremes.

a. High temperature test, Method 501, procedure two.
b. Low temperature test, Method 502, procedure one.
c. Sand and dust test, Method 510, procedure one.
d. Rain test, Method 506.

4.6.3 Structural tests.

4.6.3.1 Diagonal block test. The trailer shall be loaded with a 15,000 lb test load. The load distribution shall be 80% on the rear axles and 20% on the front axle. Two diagonally opposite wheels shall be jacked up to allow placement of eight inch blocks under the wheels. When the wheels are rested on the blocks and supporting the total weight, distortion of a permanent nature shall not occur to the frame or frame members.

4.6.3.2 Overload test. The trailer shall be loaded with 45.000 lb test load. The load distribution shall be 80% on the rear axles and 20% on the front axle. The trailer shall then be checked for damage or permanent set.

4.6.4 Turning characteristics test. The trailer shall be subjected to twenty sharp left and twenty sharp right turns at a turn radius of one hundred seventy five inches at a speed of 10 mph on level pavement. The turns shall be negotiated without any of the wheels losing contact with the pavement. This test shall be repeated twice, once with a 5,000 lb test load evenly distributed on one side of the centerline of the trailer, making ten left and ten right turns, and once with a 3,000 lb test load evenly distributed on a front quarter, for ten left and ten right turns.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

4.6.5 Electrical system compatibility tests. The trailer lighting system shall be tested to insure that all lights function properly. The lighting system shall be tested with both a twelve and twenty-four volt power source.

4.6.6 Road test. The trailer shall be subjected to a fifty mile road test as follows:

Condition	Mileage	Speed
Loaded (15,000)	25 mi	20 mph
Empty	25 mi	35 mph

The trailer shall withstand these tests without experiencing adverse tracking characteristics, yaw, sway, or dogwalk tendencies.

4.6.7 Rail system tests.

4.6.7.1 Main rail test. A 3,000 lb test load shall be evenly supported by one pair of munition chocks. The chocks shall be moved from one side of the trailer to the other side and out to the end of the rail extender. This procedure shall be repeated for 100 cycles. During cycling, any interference, binding or tendency of the chocks to tip out of the rails shall be cause for rejection of the rail system.

4.6.7.2 Rail extender test. One pair of rail extenders shall be installed on the rails of the trailer. A test load of 9,000 lbs shall be evenly supported on the rail extenders so that the center of gravity of the test weight lies nine inches from the outer end of the rail extenders. The test load shall then be removed and the rail extenders shall be inspected for any damage or pernanent structural set.

4.6.8 Physical measurements.

4.6.8.1 Height measurement. The height of the unloaded trailer shall be measured at a minimum of four points on the bed for conformance with the requirements of 3.2.1.9.

4.6.8.2 Weight measurement. The unloaded trailer, excluding accessories, shall be weighed to insure compliance with the requirement of 3.2.1.10. The scale accuracy shall be included in the weight tolerance of 3.2.1.10.

4.7 Maintainability. The maintainability requirements stated in 3.4 of this specification shall be satisfactorily demonstrated during the first article acceptance testing program.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A or C. Each trailer with accessories shall be preserved and packaged in accordance with MIL-STD-281.

5.2 Packing. Packing shall be Level A, B or C as specified (see 6.2) .

5.2.1 Level A. Each trailer, preserved and packaged as specified in 5.1, shall be shipped as a mobile unit. Accessory equipment shall be packed in shipping containers conforming to PPP-B-601, overseas type, style A or B. Interior cushioning, anchoring, blocking, bracing, and waterproofing shall be in accordance with MIL-STD-1186. The container will be strapped to the deck of the trailer with 1 1/4 inch strapping conforming to QQ-S-781.

5.2.2 Level B. Level B packing shall be the same as Level A except the accessory equipment shipping container shall conform to PPP-B-601, domestic type, style A or B.

5.2.3 Level C. The trailers, packaged as specified in 5.1, shall be packed to incur carrier acceptance and safe delivery at destination. Containers shall conform to the Uniform Freight Classification Rules or regulations of other carriers as applicable to the mode of transportation. This may conform to the supplier's commercial practice when such meets the requirements of this level.

5.3 Marking. In addition to any special marking required by the contract or order, the trailers and shipping containers shall be marked in accordance with the requirements of ML-STD-129.

6. NOTES

6.1 Intended use. The trailer described herein is intended for use by the Air Force to transport nonnuclear munitions over rough terrain and paved surfaces in support of tactical aircraft operations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should include:

a. Title, number and date of this specification

b. Site of first article test

c. Whether contractor is responsible for all tests

d. Disposition of first article

e. Level of preservation and packaging (see 5.1)

f. Level of packing (see 5.2)

Custodian:
Air Force 18

Preparing Activity:
Air Force 18

Reviewer:
Air Force 82

Project Number 1740-F127

Source: https://assist.dla.mil -- Downloaded: 202610-21T15:17Z
Check the source to verify that this is the current version before use.

TABLE

	Requirements Para.	Verification Para.	First Article Test	Production Test	Sampling
Conformance to Drawings	.3.1, 3.3.3	4.2.3	X	X	
Inertia Brakes:					
Backup	.2.1.1	4.6.1.2.1	X	X	
Stop Case 1	.2.1.1	4.6.1.2.2	X	X	
Stop Case 2	.2.1.1	4.6.1.2.3	X		X
Parking Brakes	.2.1.1	4.6.1.1.1		X	
Emergency Breakaway	.2.1.1.1	4.6.1.2.4	X	X	
High Temperature	.2.1.2a	4.6.2a	X		
Low Temperature	.2.1.2b	4.6.2b	X		
Sand and Dust	.2.1.2c	4.6.2c	X		
Rain	.2.1.2d	4.6.2d	X		
Structural Strength	.2.1.3	4.6.3	X		X
Turning Capability	.2.1.4	4.6.4	X		X
Electrical System	.2.1.5	4.6.5	X	X	
Roadability	.2.1.6	4.6.6	X	X	
Rail System:					
Main Rail	.2.1.7.1	4.6.7.1	X	X	
Rail Extender	2.1.7.2	4.6.7.2	X	X	
*Air Transportability	2.1.8				
Maintainability	4	4.7	X		
Height	2.1.9	4.6.8.1	X	X	
Weight	2.1.10	4.6.8.2	X		

*Waived

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE AIR FORCE

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATE

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 73236 WASHINGTON D C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE AIR FORCE

AD/ENPQ
Eglin AFB, FL 32542

Source: https://assist.dla.mil -- Downloaded: 202640-21T15:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T15:17Z
Check the source to verify that this is the current version before use.