MIL-G-21032A(SHIPS)
AMENDMENT - 1
28 April 1960

MILITARY SPECIFICATION

GASKETS, METALLIC-ASBESTOS, SPIRAL WOUND (FOR ASA COMMERCIAL FLANGED JOINTS IN PIPING SYSTEMS) (IDENTIFICATION SYMBOL 2410)

This amendment forms a part of Military Specification MIL-G-2103A(SHIPS), 3 March 1959.

Page 1, paragraph 2.1: Add: "PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material)".

Page 2, paragraph 2.1: Delete the following:

"MIL-P-116 - Preservation, Methods of.

"NAVY DEPARTMENT
General Specifications for Inspection of Material."

Page 7, paragraph 4.1: Delete and substitute:

"4.1 The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 7, paragraph 4.2.1: Delete and substitute:

"4.2.1 Qualification tests.—Inspection and tests to determine conformance to type II gaskets for Qualification purposes shall be conducted at a laboratory satisfactory to the Bureau of ships. A supplier may have his gaskets qualified in any pressure series by passing the specified tests for the series concerned. These tests consist of those indicated in table V."

Page 8, paragraph 4.2.1.1, lines 13 and 14: Delete note in its entirety.

Page 9, table V, second column: Delete "3.4.6" referenced in two places and substitute "3.4.5".

Page 9, paragraph 4.4.2.1: Delete and substitute:

"4.4.2.1 Line thermal shock test.—The apparatus used for this test shall consist of 6 inch pipe sections flanged together with welding-neck flanges to provide two joints. The center or spool-piece section shall consist of two flanges butt welded together. The end sections shall consist of 6 inch size pipe flanged at one end and blanked off at the other. One end section shall be provided with steam and boiler feedwater inlet connections and the other with an exhaust connection. Two nozzles for directing a spray of boiler feedwater on the inner periphery of the test joints shall be centrally located within the apparatus, one at the centerline of each joint. Each nozzle shall consist of a 1/2 inch size pipe with 6 holes of 1/8 inch diameter drilled radially at 60 degree intervals around the pine. Thermocouples shall be placed approximately for measurement of temperatures at outer surface of pipe, at the raised faces of the test joints, of inlet steam and boiler feedwater, and at the exhaust connection. The test shall consist of 20 cycles of thermal shock obtained by changing conditions from steam at 600 p.s.i.g. and 850°F. to boiler feedwater at 750 p.s.i.g. and 250°F. for series 300, 400 and 600. The test joints shall be inspected closely for leakage during the shocks.

Page 11, table VI, footnote 3: Delete "when tested at the Naval Engineering Experimental Station, Annapolis, Md.".

Page 11, paragraph 4.5: Delete.

Pages 11 and 12, Section 5: Delete and substi following:

"5. PREPARATION FOR DELIVERY

"5.1 Packaging.— (see 6.2)

"5.1.1 Level A.—Gaskets and refills shall be packaged in folding or set-up paperboard or fiber boxes conforming to Specification PPP-B-566, PPP-B-636, PPP-B-665, or PPP-B-676. Quantity per unit package shall be as specified (see 6.2). Box closures and gross weight limitations shall conform to the box specification and the appendix thereto. When specified (see 6.2), material may be bulk packed directly into shipping containers as specified in 5.2.1 and 5.2.2.

"5.1.2 Level C.—Gaskets and refills shall be packaged in accordance with the supplier's commercial practice.

"5.2 Packing.— (See 6.2)

FSC 5330

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:29Z
Check the source to verify that this is the current version before use.

"5.2.1 Level A.—Gaskets and refills of like types, series and size packaged as specified (see 6.2) shall be packed in overseas type or class wood cleated fiberboard, nailed wood, fiber, wirebound wood, wood cleated veneer paper overlaid, or wood cleated plywood boxes conforming to Specification PPP-B-591, PPP-B-621, PPP-B-636, class 3, PPP-B-585, class 3, MIL-B-10377, or PPP-B-601, respectively, at the option of the contractor. Shipping containers shall have case liners conforming to Specification MIL-L-10547. Case liners for boxes conforming to Specification PPP-B-636 may be omitted provided all joints and corners of the boxes are sealed with minimum 1-1/2 inch tape conforming to Specification PPP-T-76. Boxes shall be closed and strapped in accordance with the applicable box specification or appendix thereto, except fiber boxes may be banded with tape conforming to type IV of Specification PPP-T-97 and the appendix thereto. The gross weight of wood or wood cleated boxes shall not exceed 200 pounds; fiber boxes shall not exceed the weight limitations of the applicable box specification. Intermediate fiber boxes conforming to class 2 or 3 of Specification PPP-B-636, closed, sealed and banded as specified herein, and used as the shipping container need not be overpacked.

"5.2.2 Level B.—Gaskets and refills of like types, series and size packaged as specified (see 6.2) shall be packed in domestic type or class wood cleated fiberboard, nailed wood, wirebound wood, cleated plywood or wood cleated veneer paper overlaid boxes or class 2 fiber boxes conforming to Specification PPP-B-591, PPP-B-621, PPP-B-585 (class 1), PPP-B-601, MIL-B-10377 or PPP-B-636, respectively, at the option of the contractor. Box closure shall be as specified in the applicable box specification or appendix thereto. The gross weight of wood or wood cleated boxes shall not exceed 200 pounds; fiber boxes shall not exceed the weight limitations of the applicable box specification. Intermediate fiber boxes conforming to Specification PPP-B-636, closed as specified herein, and used as the shipping container need not be overpacked.

"5.2.3 Level C.—Gaskets of like types, series and size packaged as specified (see 6.2) shall be packed in containers which will insure acceptance by common carrier and safe delivery at destination. Shipping containers shall comply to the Uniform Freight Classification Rules or other carrier regulations as applicable to the mode of transportation.

"5.3 Marking.—In addition to any special marking specified in the contract or order or herein, interior packages and exterior shipping containers shall be marked in accordance with Standard MIL-STD-129."

Page 12, paragraph 6.2(d): Delete and substitute the following: "(d) Quantity per unit package (see 5.1.1)."

Page 12, paragraph 6.2: Add the following"
"(g) When bulk packaging is required (see 5.1)."

Preparing activity
Navy-Bureau of Ships
(Project 5330-0027Sh)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:29Z
Check the source to verify that this is the current version before use.