MILITARY SPECIFICATION SHEET


TRANSFORMERS, PULSE, LOW POWER,

TYPE TP7SX1110AN

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformers described herein shall consist of this specification and the latest issue of MIL-T-21038.

(B) This specification is inactive for new design after the date of this specification.



INCHES	MM
.025	.64
.0938	2.38
.422	10.72
.625	15.88
3.250	82.55

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ±.032(.81 mm).

FIGURE 1. Dimensions and configuration.

(B) denotes changes

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 202610-19T08:32Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics including waveform parameters.

Dash No.	DCR (ohms)			Blocking oscillator pulse					Coupling circuit characteristics							Frequency response 2/ ± 2 dB	Turns ratio
				Pulse width (μs)	Rise time (μs)	Over-shoot %	Droop %	Back swing %	Pulse width (μs)	Volts out .	Rise time (μs)	Over-shoot %	Droop %	Back swing %	Impedance 1/ out, in (ohms)		
	1-2	3-4	5-6														
001	50	58	67	10	.30	0	20	8	10	24	.25	10	10	50	1000	7.1 kHz to 1.35 MHz	1:1:1
002	78	96	112	16	.75	0	20	10	16	23	.40	5	15	20	1000	1.65 kHz to 3.05 MHz	1:1:1
003	104	135	165	25	2.0	0	30	10	25	24	1.5	5	10	10	1000	1.7 kHz to 315 kHz	1:1:1

1/ See figure 2.
2/ Per coupling circuit (Z), in/out, 1 V input.




FIGURE 2. Test circuit.

Source: https://assist.dla.mil -- Downloaded: 20264O-19T08:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case: Encapsulated.

Terminals: Solid wire leads, type D per MIL-STD-1276, tinned.

Weight: 6.0 grams.

Terminal strength: Method 211, MIL-STD-202, test condition A - pull 2.5 pounds.

Dielectric withstanding voltage:

At atmospheric pressure: Method 301, MIL-STD-202. 1,250 volts rms for 60 seconds between windings and ground.

Barometric pressure (reduced): Method 301, MIL-STD-202 and method 105, test condition B, MIL-STD-202. 565 volts rms between windings and ground.

Insulation resistance: Method 302, test condition B, MIL-STD-202. Not less than 10,000 megohms.

Electrical characteristics: See table I.

Test circuit: See figure 2.

Life (expectancy "X"): Applicable.

Temperature rise: Not applicable.

Vibration high frequency: Method 204, test condition B, MIL-STD-202.

Shock (specified pulse): Method 213, test condition H, MIL-STD-202.

Ⓑ Quality assurance provisions:

Qualification inspection: Not applicable for this specification.

Quality conformance inspection: Groups A and B tests of MIL-T-21038 shall be applicable.

Part number: M21038/10 - (dash number from table I).

Preparing activity:
Air Force - 85

(Project 5950-0587-05)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.