MILITARY SPECIFICATION SHEET


TRANSFORMERS, PULSE, LOW POWER,

TYPE TP6RX5310CZ

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the transformers described herein shall consist of this specification and the latest issue of MIL-T-21038.

(B) This specification is inactive for new design after date of this specification.



INCHES	MM
.016	.41
.219	5.56
.344	8.74
1.500	38.10

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ±.032 (.81 mm).

FIGURE 1. Dimensions and configuration.

(B) denotes change

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics including waveform parameters.

Dash No.	DCR (ohms)			Blocking oscillator pulse					Coupling circuit characteristics								Frequency response 2/ ±2 dB	Turns ratio
				Pulse width (μs)	Rise time (μs)	Over-shoot %	Droop %	Back swing %	Pulse width (μs)	Volts out	Rise time (μs)	Over-shoot %	Droop %	Back swing %	Impedance 1/ (ohms)			
	1-2	3-4	5-6												in	out		
001	9.4	7.1	2.6	5	0.05	0	12	12	5	8	0.09	2	12	25	560	200	15 kHz to 4 MHz	5:3:1
002	2.9	2.2	8.2	1	0.02	4	4	6	1	6.6	0.05	0	6	12	280	100	12.5 kHz to 3.25 MHz	5:3:1
003	0.55	0.41	0.15	0.1	0.01	0	0	20	0.1	8	0.01	0	0	5	140	50	170 kHz to 32 MHz	5:3:1

1/ See figure 2.
2/ Per coupling circuit (Z), in/out, 1 V input.




FIGURE 2. Test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case: Metal.

Terminals: Insulated, gold plated dumet leads, (see figure 2).

Weight: 0.07 ounce maximum.

Terminal strength: Method 211, MIL-STD-202, test condition A - pull 2.5 pounds.

Dielectric withstanding voltage:

At atmospheric pressure: Method 301, MIL-STD-202. 100 volts rms for 60 seconds between windings and case.

Barometric pressure (reduced): Method 301, MIL-STD-202 and method 105, test condition E, MIL-STD-202. 100 volts rms between windings and case.

Insulation resistance: Method 302, test condition A, MIL-STD-202. Not less than 10,000 megohms.

Electrical characteristics: See table I.

Test circuit: See figure 2.

Life (expectancy "X"): Applicable.

Temperature rise: Not applicable.

Vibration high frequency: Method 204, test condition B, MIL-STD-202.

Shock (specified pulse): Method 213, test condition H, MIL-STD-202.

Ⓑ Quality assurance provisions:

Qualification inspection: Not applicable for this specification.

Quality conformance inspection: Groups A and B tests of MIL-T-21038 shall be applicable.

Part number: M21038/7 - (dash number from table I).

Preparing activity:
Air Force - 85

(Project 5950-0587-04)

Source: https://assist.dla.mil -- Downloaded: 20260-19T08:32Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.