
MILITARY SPECIFICATION SHEET

TRANSFORMERS, PULSE, LOW POWER,

TYPE TP7SX1110AZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the transformers described herein shall consist of this specification and the latest issue of MIL-T-21038.



Inches	mm
.025	0.64
.0938	2.38
.359	9.12
.563	14.30
3.250	82.55

NOTES:
1. Dimensions are in inches
2. *Metric equivalents are given for general information only.*
3. Unless otherwise specified, tolerance is ±.032 (0.81 mm).

FIGURE 1. Dimensions and configuration.

(B) denotes change

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.

(B) TABLE I. Electrical characteristics including waveform parameters.

Dash no.	DCR (ohms ±25%)			Blocking oscillator pulse					Coupling circuit characteristics							Frequency response 2/ ±2 dB	Turns ratio
				Pulse width (µs)	Rise time (µs)	Over-shoot %	Droop %	Back swing %	Pulse width (µs)	Volts out	Rise time (µs)	Over-shoot %	Droop %	Back swing %	Impedance 1/ out, Tn (ohms)		
	1-2	3-4	5-6													kHz MHz	
001	3.7	4.0	4	.20	.026	0	25	8	.20	18	.01	30	15	65	500	260 to 93	1:1:1
002	5.5	5.8	6	.50	.03	0	20	5	.50	20	.01	30	20	65	500	85 to 73	1:1:1
003	8	8.5	9	1	.04	0	20	10	1	24	.02	15	15	65	500	50 to 62.5	1:1:1
004	20	21	22	2	.05	0	20	10	2	27	.05	10	15	35	500	24.5 to 49	1:1:1
005	28	31	33	3	.10	1	20	8	3	26	.07	10	10	35	500	12.6 to 5.65	1:1:1
.006	36	41	44	5	.13	1	25	8	5	23	.15	10	10	45	1000	13 to 3.465	1:1:1

1/ See figure 2.
2/ Per coupling circuit (Z), in or out, 1 V input.




FIGURE 2. Test circuit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Case: Encapsulated.

Terminals: Solid wire leads, type D per MIL-STD-1276, tinned.

Weight: 4.0 grams.

Terminal strength: Method 211, MIL-STD-202, test condition A, pull 2.5 pounds.

Dielectric withstanding voltage:

At atmospheric pressure: Method 301, MIL-STD-202. 1,250 volts rms for 60 seconds between windings and ground.

Barometric pressure (reduced): Method 301, MIL-STD-202 and method 105, test condition B, MIL-STD-202. 565 volts rms between windings and ground.

Insulation resistance: Method 302, test condition B, MIL-STD-202. Not less than 10,000 megohms.

Electrical characteristics: See table I.

Test circuit: See figure 2.

Life (expectancy "X"): Applicable.

Temperature rise: Not applicable.

Vibration high frequency: Method 204, test condition B, MIL-STD-202.

Shock (specified pulse): Method 213, test condition H, MIL-STD-202.

Part number: M21038/9- (dash number from table I).

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 11, 17
DLA - ES

User activities:
Army - ME
Navy - MC, SH
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5950-0673-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:32Z
Check the source to verify that this is the current version before use.