MILITARY SPECIFICATION

BELT, AIRCRAFT SAFETY, LAP, TROOP, TYPE MC-1A

This specification is approved for use by the Department of the Air Force, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a detachable aircraft lap safety belt designated type MC-1A

2. APPLICABLE DOCUMENTS

* 2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. Unless otherwise specified, the following specifications, standards, and handbooks of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	Boxes, Wood Cleated - Plywood.
PPP-B-636	Boxes, Shipping, Fiberboard.
PPP-B-676	Boxes, Set-Up.

MILITARY

MIL-P-116	Preservation, Packing, Methods of.
MIL-L-15040	Labels, Garmet, (Woven Rayon).

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.
MIL-STD-130	Identification Marking of U.S. Military Property.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: the Engineering Division, San Antonio ALC/MMEDO, Kelly AFB, TX 78241 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1680

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:25Z
Check the source to verify that this is the current version before use.

DRAWING

U.S. Air Force

56E590	Belt - Aircraft Safety, Lap, Troop, Type MC-1A, Assembly of.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

* 2.1.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

American Society for Testing and Materials (ASTM)

D 3951	Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using agencies.)

3. REQUIREMENTS

3.1 General. The requirements specified on drawing 56E590 shall form a part of this specification. When drawing requirements conflict with this specification, the requirements of this specification shall govern.

3.2 Strength. Each troop lap belt shall be capable of withstanding a static load of 2,500 pounds without weakening of the webbing, or stitching, slippage of the webbing through the adjusting hardware, or deformation of the metal fittings.

3.3 Marking. Each half of the belt shall be marked by means of a sewed label located as shown on 56E590. These labels shall be in accordance with MIL-L-15040, type I, on a black background, lettering to read in the direction of the warp of the label. The information appearing on the label shall be in accordance with MIL-STD-130, and shall read as follows:

Belt, Aircraft Safety, Lap Troop
Type MC-1A
Specification Nr. MIL-B-8437 (USAF)
Stock Nr.
Contract or Order Nr.
Date of Manufacture
Manufacturer's Name or Trademark

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:25Z
Check the source to verify that this is the current version before use.

3.4 Workmanship. The belt, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirement specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Acceptance tests. Acceptance tests shall consist of:

a. Individual tests.

b. Sampling plans and tests.

4.1.1.1 Individual tests. Each lap safety belt shall be subjected to the following tests:

4.1.1.2 Examination of product. Each belt shall be examined to determine conformance with this specification with respect to material, workmanship, and markings.

4.1.1.3 Proof load. Each belt shall be assembled in a testing machine by attaching the end snap metal fittings to one moveable and one stationary head, with the quick release latch assembly closed. A proof load of 1,000 pounds shall be applied. There shall be no evidence of weakening of the webbing or stitching, slipping of the webbing through the metal adjusters or deformation of any metal fittings in the belt assembly.

4.1.2 Periodic sampling tests.

4.1.2.1 Lot. A lot shall consist of safety belts manufactured under essentially the same conditions and submitted for inspection at substantially the same time.

4.1.2.2 Ultimate load test. Sampling for the ultimate load test shall be in accordance with level L4 of the appendix to MIL-STD-105, with an AQL of 0.40. Each sample belt shall be assembled in testing machine (as described in 4.1.1.3) and subjected to a static load of 2500 pounds. Any evidence of weakening of the webbing or stitching, slippage or webbing through the adjusting hardware, or deformation of the metal fittings shall be cause for rejection. Belts and components thereof subjected to the ultimate load test shall be destroyed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:25Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Belts shall be cleaned in accordance with MIL-P-116, process C-1.

5.1.1.2 Preservative applications. Preservatives shall not be used.

5.1.1.3 Unit packs. Unless otherwise specified (see 6.2), each belt shall be individually unit packed in accordance with MIL-P-116, method 1A, and packaging in containers meeting PPP-B-636, class domestic or PPP-B-676.

5.1.2 Commercial. The commercial preservation of belts shall be in accordance with the requirements of ASTM D 3951.

5.2 Packing. Packing shall be level A, B or commercial, as specified (see 6.2).

5.2.1 Level A. The packaged belts shall be packed in containers conforming to PPP-B-601, overseas type. Closure and strapping shall be in accordance with applicable container specification.

5.2.2 Level B. The packaged belts shall be packed in fiberboard containers conforming to PPP-B-636, class weather resistant, style optional or PPP-B-601, domestic type. Closure and strapping shall be in accordance with applicable container specification or appendix thereto.

5.2.3 Commercial. The packaged belts shall be packed in accordance with the requirements of ASTM D 3951.

5.3 Marking. In addition to any special or other identification marking required by the contract (see 6.2) each unit pack, intermediate and exterior container shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

6.1 Uses. The type MC-1A safety belt covered by this specification is intended for use to secure troop personnel in their aircraft seats and is easily and quickly detachable if cargo only is to be carried in the aircraft.

6.2 Ordering data. Purchase requests and invitations for bids should specify whether domestic or export shipment is required.

* 6.3 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:25Z
Check the source to verify that this is the current version before use.

NOTICE: When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise in manner licensing the holder or any person or corporation or conveying any right or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

Custodian:
Air Force - 99

Preparing activity:
Air Force - 82

(Project 1680-F513)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:25Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2020-10-17T10:25Z
Check the source to verify that this is the current version before use.