MIL-C-8498D(USAF)
14 April 1971
SUPERSEDING
MIL-C-8498C(USAF)
11 July 1958

MILITARY SPECIFICATION

COMPRESSOR, AIR, GASOLINE ENGINE DRIVEN, 15 CFM, 200 PSI, TYPE MC-2A

1. SCOPE

1.1 Scope. This specification covers one type of 15 CFM, 200 psig, gasoline engine driven, 2-wheel mounted air compressor, designated type MC-2A.

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-C-3600	Compressors, Air and Gas (except Oxygen) Packaging of
MIL-M-8090	Mobility Requirements, AGE General Specification for
MIL-E-11275	Engines, Gasoline, Industrial Type, General Specification for
MIL-C-26805	Compressor Units, Air, General Requirements for
MIL-T-83926	Tires, Pneumatic, Special Purpose

STANDARDS

Federal

FED-STD 595	Colors

Military

MS35000	Battery, Lead-Acid

DRAWING

Air Force

50C 24046	Coupling, Air Duct, 6-Inch

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

FSC/4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General specification. The requirements of MIL-C-26805 as applicable to the Type II, Class 1 compressor apply as requirements of this specification with the exceptions and additions specified herein. When specifications conflict, this specification shall govern first and MIL-C-26805 shall govern second.

3.2 Description. The air compressor shall be 2-wheel mounted, enclosed, and shall consist essentially of a two-stage, air-cooled, reciprocating compressor or an air-oil cooled multi-stage rotary compressor, either type to be equipped with a gasoline engine power unit, air receiver, air hose and accessories described herein.

3.3 Preproduction. This specification makes provisions for preproduction testing.

3.4 Design and construction.

3.4.1 Gasoline engine. The compressor shall be driven by an air-cooled, 4 cycle gasoline engine. The gasoline engine (including a fuel tank of sufficient capacity for not less than 8 hours operation and a manual and electric cranking system) shall conform to MIL-E-11275 except an alternator shall be supplied in lieu of a generator.

3.4.2 Mobility. Compressor units shall be designed to meet the mobility requirements of MIL-M-8090 as specified for type II, group A mobility except as follows:

a. Service brakes, bumpers, fenders and mud flaps shall not be required.

b. Unless otherwise specified (see 6.2) reflectors shall not be furnished.

c. Unless otherwise specified (see 6.2) safety chains shall not be furnished.

d. The compressor unit shall be stabilized in a level attitude when not connected to the towing equipment by a retractable leg.

3.4.3 Air receiver tank. The air receiver tank shall be of the horizontal type with a minimum capacity of 8 gallons.

3.4.4 Drive. The compressor shall be either direct drive or multiple V-belt drive with no clutch required.

3.4.5 Pressure regulation. A constant-speed-type unloader shall be provided that is adjustable from 100 to 250 psig, and shall be factory set to unload at 200 ± 5 psig. The range between loading and unloading shall not exceed 50 ± 10 psig. When the compressor is stopped a device shall be provided to automatically unload the compressor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

3.4.6 Space envelope. The dimensions of the complete unit shall be within 49 inches high, 59 inches wide and 89 inches long.

3.4.7 Weight. The maximum weight shall be 1,000 pounds wet.

3.4.8 Treatment and painting. The portions of the compressor normally painted shall be cleaned, treated and painted in accordance with the manufacturers standard commercial practice and the finish shall be color No. 13538 according to FED-STD No. 595.

3.4.9 Receiver drain. In addition to a siphon drain, the receiver shall be equipped with a ¼ NPT static drain, located at the lowest point in the receiver. The drain shall be plugged with a ¼ NPT pipe plug.

3.4.10 Battery. The battery shall satisfy the requirements of MIL-C-26805 and MS 35000-1 except the electrolyte shall be furnished with each unit.

3.4.11 Duct connections. A duct connection shall be provided on the enclosure according to MIL-C-26805 and Drawing 50C24046.

3.4.12 Tires and tubes. Tires and tubes shall meet the requirements of MIL-T-83926.

3.5 Performance.

3.5.1 Rated output. The compressor shall deliver a minimum of 15 cfm of free air at a pressure of 200 psig for continuous operation and at a pressure of 250 psig for intermittent operation.

4. QUALITY ASSURANCE PROVISIONS

4.1 General. Sampling, inspection, and testing of the compressor shall be in accordance with MIL-C-26805.

4.2 Preproduction tests. Preproduction tests shall be as specified in MIL-C-26805.

5. PREPARATION FOR DELIVERY

5.1 General. The compressors shall be preserved, packaged, packed, and marked in accordance with MIL-C-3600. The level of preservation, packaging, and packing shall be level A, B, or C as specified (see 6.2).

6. NOTES

6.1 Intended use. The type MC-2A air compressor is intended for use in hangars, garages, on flight lines or wherever a portable source of compressed air is required.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. When reflectors shall be other than as specified (see 3.4.2.b).

Source: https://assist.dla.mil --- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

c. When safety chain shall be other than as specified (see 3.4.2.c).

d. Selection of applicable levels of preservation, packaging and packing.

6.3 Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian
Air Force - 84

Preparing activity
Air Force - 84

Project No. 4310-F044

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES" IN WHAT WAY?

4. REMARKS (*Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity*)

SUBMITTED BY (*Printed or typed name and activity*) | DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4063, WHICH IS OBSOLETE. 47 APLC RAFB,GA JUN 67 - 500

Source: https://assist.dla.mil -- Downloaded: 202610-17T10:26Z
Check the source to verify that this is the current version before use.

FOLD

WRAMA/MMEME
ROBINS AFB GA 31093

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE

UNITED STATES AIR FORCE
OFFICIAL BUSINESS

WRAMA/MMEME
ROBINS AFB GA 31093

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.