MIL-C-8499D(USAF)
8 June 1971
SUPERSEDING
~~MIL-C-8499C(USAF)~~
13 October 1958

MILITARY SPECIFICATION

COMPRESSOR, AIR, ELECTRIC MOTOR DRIVEN, PORTABLE, TYPE MB-2A

1. SCOPE

1.1 Scope. This specification covers one type electric motor driven, reciprocating or rotary, 15 CFM, 200 PSIG, 2-wheel mounted air compressor, designated Type MB-2A.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-C-3600	Compressors, Air and Gas (Except Oxygen) Packaging of
MIL-M-8090	Mobility Requirements, Ground Support Equip., General Specification for
MIL-C-26805	Compressor Units, Air/Gas, General Requirements for
MIL-T-83926	Tires, Pneumatic, Special Purpose

STANDARDS

Federal

FED-STD-595	Colors

(Copies of documents required by suppliers in conjunction with specific procurement function should be obtained from the procuring activity or as directed by the contracting officer).

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

FSC 4310

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

3.2 General specification. The requirements of MIL-C-26805, as applicable to the Type II, Class 2 compressor apply as requirements of this specification with the exceptions and additions specified herein. When specifications conflict, this specification shall govern first and MIL-C-26805 shall govern second.

3.3 Description. The compressor shall be 2-wheel mounted and shall consist essentially of a two-stage, air-cooled, reciprocating compressor or an air-oil cooled, multi-stage rotary compressor, either type to be equipped with an explosion proof motor and controls, air receiver, air hose and accessories described herein.

3.4 Design and construction.

3.4.1 Mobility. Compressor units shall be designed to meet the mobility requirements of MIL-M-8090 as specified for Type II, Group A mobility except as follows:

a. Service brakes, bumpers, fenders and mud flaps shall not be required.

b. Unless otherwise specified (see 6.2) reflectors shall not be furnished.

c. Unless otherwise specified (see 6.2) safety chains shall not be furnished.

d. The compressor unit shall be stabilized in a level attitude when not connected to the towing equipment by a retractable leg.

3.4.2 Receiver. The air receiver shall have a minimum capacity of 80 gallons.

3.4.3 Phase reversal switch. A switch shall be provided to reverse the phase sequence.

3.4.4 Enclosure. A weather proof enclosure shall not be provided.

3.4.5 Tires and tubes. Tires and tubes shall meet the requirements of MIL-T-83926.

3.4.6 Treatment and painting. The portions of the compressor normally painted shall be cleaned, treated and painted in accordance with the manufacturers standard commercial practice and the finish color shall be yellow, No. 13538, according to FED-STD-595.

3.5 Performance.

3.5.1 Rated output. The compressor shall deliver a minimum of 15 CFM of free air at a pressure of 200 PSIG for continuous operation and at a pressure of 250 PSIG for intermittent operation.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

4.1 General. Sampling, inspecting and testing of the compressor shall be in accordance with MIL-C-26805.

4.2 Preproduction tests. Preproduction tests shall be as specified in MIL-C-26805.

5. PREPARATION FOR DELIVERY

5.1 General. The compressors shall be preserved, packaged, packed and marked in accordance with MIL-C-3600. The level of preservation, packaging and packing shall be level A, B or C as specified (see 6.2).

6. NOTES

6.1 Intended use. The Type MB-2A air compressor is intended as a portable source of compressed air for locations where explosive atmospheres may exist.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification.

b. When reflectors shall be other than as specified (see 3.4.1.b).

c. When safety chains shall be other than as specified (see 3.4.1.c).

d. Selection of applicable levels of preservation, packaging and packing.

6.3 Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Air Force - 84

Preparing activity:
Air Force - 84

Project No. 4310-F048

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T10:26Z
Check the source to verify that this is the current version before use.