MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM, POLAR, INSULATED, METAL CASE, WITH PLASTIC END-FILL, NONHERMETICALLY SEALED, STYLE CX03

This amendment forms a part of MIL-C-49137/3, dated 14 May 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Following title, insert: "

Inactive for Design after 15 SEP 1985

"

PAGE 2

TABLE I, delete and substitute:

"TABLE I. Style CX03 characteristics.

Type designation 1/	DC rated voltage (85°C)	Cap. (nom)	DC leakage (max) +25°C	Dissipation factor	Case size
	Volts	µF	µA	%	
CX03D475-	6	4.7	1.0	6	A
CX03H685-	15	6.8	1.0	6	R
CX03H226-	15	22	3.0	8	D
CX03K106-	25	10	1.5	8	C
CX03N104-	50	0.10	1.0	4	A

"

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Navy - SH
Air Force - 17, 85, 99
DLA - ES

User activities:
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1555)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.