MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE),
TANTALUM, NON-POLAR, NONHERMETICALLY SEALED
STYLES CX07 and CX17

This amendment forms a part of Military Specification MIL-C-49137/7(ER), dated 25 November 1981, and is approved for use by the Electronics Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1 (dimension table): Delete and substitute:

Case size	Dimensions T Min	T Max	W Min	W Max	H Min	H Max	M ±.002	S
				CX07				
A	.090	.125	.090	.125	.145	.180	.010	.100 ±.020
B	.145	.180	.105	.140	.205	.240	.010	.100 ±.020
C	.190	.220	.150	.180	.285	.315	.016	.150 ±.025
D	.200	.230	.200	.230	.305	.335	.016	.200 ±.025
				CX17				
E	.090	.125	.090	.125	.185	.220	.010	.100 ±.020
F	.145	.180	.105	.140	.245	.280	.010	.100 ±.020
G	.190	.220	.150	.180	.340	.370	.016	.150 ±.025
H	.200	.230	.200	.130	.250	.390	.016	.200 ±.025

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.002	.05	.125	3.18	.220	5.59	.335	8.47
.010	.25	.140	3.56	.230	5.84	.340	8.64
.016	.38	.145	3.68	.240	6.10	.350	8.89
.020	.41	.150	3.81	.245	6.22	.370	9.40
.025	.51	.180	4.57	.280	7.11	.390	9.91
.090	2.29	.190	4.83	.285	7.24	1.500	38.10
.100	2.54	.200	5.08	.305	7.75		
.105	2.67	.205	5.21	.315	7.91		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.

PAGE 4

Case material: Delete and substitute:
"Polyester sleeve and epoxy end filled or plastic encapsulated."

PAGE 5

Following Life requirement, add:
"Resistance to solvents Not applicable."

Custodian:
Army - ER

Review activity:
DLA - ES

Agent:
DLA - ES

Preparing activity:
Army - ER

(Project 5910-A386-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.