PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM MOLDED, CONFORMAL COATED AND METAL CASED WITH PLASTIC END FILL, NONHERMETICALLY SEALED, GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-49137B, dated 30 September 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 12

TABLE V, delete table and substitute the following:

TABLE V. Group A inspection.

Inspection	Requirement paragraph	Test method paragraph	Sampling procedure
Subgroup 1 DC leakage Capacitance Dissipation factor	 3.7 3.8 3.9	 4.8.4 4.8.5 4.8.6	 20 samples 0 failures
Subgroup 2 Visual and mechanical inspection Construction analysis (metal cased units only)	 3.1, 3.3, 3.3.1, 3.4, 3.4.1, 3.4.2, 3.21 and 3.23 3.6	 4.8.1 4.8.3	 13 samples 0 failures
Subgroup 3 Solderability	 3.19	 4.8.16	13 samples 0 failures

PAGE 20

Add the following statement: "6.7 Retention of qualification. For the purposes of retention of qualification (see 4.5) and conformance inspection (see 4.6), the manufacturer may use retention of qualification data from MIL-PRF-39003 provided the internal parts are manufactured using the same process as MIL-PRF-39003."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - MI
Navy - AS, MC, OS, SH
Air Force – 19, 99
DLA – CC

Preparing activity:
Army - CR

Agent:
DLA – CC

(Project 5910-2195)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.