MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM, POLAR, MOLDED, NONHERMETICALLY SEALED, STYLE CX01

This amendment forms a part of MIL-C-49137/1A, dated 14 May 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1, dimension table, delete and substitute the following:

Case size	DIMENSIONS			
	Diameter D (Max)	Length L (Max)	Lead size	
			Dia.	AWG
A	.120 (3.05)	.310 (7.87)	.020 ±.0015 (.51 ±.040)	24
B	.200 (5.08)	.400 (10.16)	.025 ±.002 (.64 ±.05)	22,24
C	.220 (5.59)	.560 (14.22)	.025 ±.002 (.64 ±.05)	22,24

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, CG, MC, OS
Air Force - 19

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-1595-2)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.