INCH-POUND
MIL-PRF-49137/2B
9 October 1997
SUPERSEDING
MIL-C-49137/2A
14 May 1979

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM, POLAR, CONFORMAL COATED, NONHERMETICALLY SEALED, STYLES CX02 AND CX12

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the capacitors described herein shall consist of this document and the latest issue of Specification MIL-PRF-49137.



	Case Size				Lead Size	
	CX02					
Case size	Diameter (D)		Height (H)			
	Inches	mm	Inches	mm	Dia	AWG
A	0.175	4.45	0.425	10.80	0.020	24,22
B	0.250	6.35	0.500	12.70	0.020	24,22
C	0.350	8.89	0.650	16.51	0.025	22
D	0.400	10.16	0.750	19.05	0.025	22
	CX12					
E	0.175	4.45	0.350	8.89	0.020	24,22
F	0.250	6.35	0.500	12.70	0.020	24,22

NOTES:
1. Lead spacing shall be measured within 0.050” (1.27 mm) from the point of emergence from the body or the bottom of the crimp.
2. Case size dimensions are maximum.
3. Dimensions are in inches.
4. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
5. Metric equivalents are in parentheses.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A: Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

TABLE I. Style CX02 and CX12 characteristics.

Type designation 1/	DC rated voltage (85°C)	Cap. (nom)	DC leakage (max) +25°C	Dissipation factor	Case size
	Volts	µF	µA	%	
CX-2D685-	6	6.8	1.0	6	A,E
CX-2D476-	6	47.0	3.0	8	B,F
CX-2D686-	6	68.0	4.5	8	B,F
CX02D157-	6	150.0	10.0	10	C
CX02D337-	6	330.0	20.0	10	D
CX-2F475-	10	4.7	1.0	6	A,E
CX-2F336-	10	33.0	3.5	8	B,F
CX02F107-	10	100.0	10.0	10	C
CX02F227-	10	220.0	20.0	10	D
CX-2H335-	15	3.3	1.0	6	A,E
CX-2H226-	15	22.0	3.5	8	B,F
CX02H686-	15	68.0	10.0	8	C
CX02H157-	15	150.0	20.0	10	D
CX-2J225-	20	2.2	1.0	6	A,E
CX-2J156-	20	15.0	3.0	8	B,F
CX02J476-	20	47.0	10.0	8	C
CX02J107-	20	100.0	20.0	10	D
CX-2K155-	25	1.5	1.0	6	A,E
CX-2K106-	25	10.0	2.5	8	B,F
CX02K336-	25	33.0	9.0	8	C
CX02K686-	25	68.0	15.0	8	D
CX-2M685-	35	6.8	2.5	6	B,F
CX02M226-	35	22.0	8.0	8	C
CX02M336-	35	33.0	10.0	8	D
CX02M476-	35	47.0	10.0	8	D
CX-2N104-	50	.1	1.0	4	A,E
CX-2N154-	50	.15	1.0	4	A.E
CX-2N224-	50	.22	1.0	4	A.E
CX-2N334-	50	.33	1.0	4	A.E
CX-2N474-	50	.47	1.0	4	A.E
CX-2N684-	50	.68	1.0	4	A.E
CX-2N105-	50	1.0	1.0	4	A,E
CX-2N155-	50	1.5	1.0	6	B,F
CX-2N225-	50	2.2	1.5	6	B,F
CX-2N335-	50	3.3	2.0	6	B,F
CX-2N475-	50	4.7	2.5	6	B,F
CX02N685-	50	6.8	3.5	6	C
CX02N106-	50	10.0	5.0	8	C
CX02N156-	50	15.0	6.0	8	C
CX02N226-	50	22.0	10.0	8	D

1/ Complete type designation will include additional symbols indicating style and capacitance tolerance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1.
Case material: Dipped, epoxy or plastic.
Leads: Solder-coated metal.
DC rated voltage: See table I.
Operating temperature: -55° to +85°C.

DC leakage (DCL): See table I.

Capacitance (cap.): See table I.
Cap. tolerance: ±10% (K), or ±20% (M).

Dissipation factor (DF): See table I.

Stability at low and high temperature: In accordance with MIL-PRF-49137.

Step 1 (+25°):	DCL	- See table I.
	Cap.	- Within tolerance specified in table I.
	DF	- See table I.
Step 2 (-55°C):	ΔCap.	- Within -15 percent of step 1 measured value.
	DF	- 200 percent of table I.
Step 3 (+25°C):	DCL	- See table I.
	ΔCap.	- Within 10 percent of step 1 measured value.
	DF	- See table I.
Step 4 (+85°C):	DCL	- 10 times 25°C limit (see table I).
	ΔCap.	- Within +15 percent of step 1 measured value.
	DF	- 150 percent of table I.
Step 5 (+25°C):	DCL	- See table I.
	ΔCap.	- Within 10 percent of step 1 measured value.
	DF	- See table I.

Surge voltage: In accordance with MIL-PRF-49137.
DCL - See table I.
ΔCap. - Within 10 percent of initial value.
DF - See table I.

Life: Method 108 of MIL-STD-202.
1,000 hours:

At 25°C:	DCL	- 200 percent of table I.
	ΔCap.	- Within 10 percent of initial measured value.
	DF	- See table I.

NOTES:
1. Revision letters are not used to denote change due to the extensiveness of the changes.
2. These capacitors are intended to be used only where supplemental moisture protection is provided or for noncritical applications where hermetic moisture protection is not required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Navy - AS, CG, MC, OS, SH
Air Force - 19, 85, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-1944-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:49Z
Check the source to verify that this is the current version before use.