MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE),
TANTALUM, POLAR, NONHERMETICALLY SEALED
STYLES CX06 and CX16

This amendment forms a part of MIL-C-49137/6A(ER), dated 6 March 1981, and is approved for use within the US Army Laboratory Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

FIGURE 1 (dimension table), delete and substitute:

Case size	Dimensions							
	T		W		H		N	S
	Min	Max	Min	Max	Min	Max	±.002	
A	.025	.040	.035	.050	.080	.100	.007	.030 ±.015
B	.025	.040	.055	.070	.105	.125	.010	.050 ±.015
C	.050	.070	.100	.120	.140	.165	.010	.100 ±.020
D	.060	.075	.160	.185	.195	.225	.010	.150 ±.020
E	.075	.110	.195	.220	.260	.290	.016	.180 ±.025
F	.100	.130	.200	.230	.280	.310	.016	.200 ±.025
G	.120	.150	.340	.375	.435	.475	.016	.300 ±.025

INCHES	MM	INCHES	MM	INCHES	MM	INCHES	MM
.002	0.05	.060	1.52	.150	3.81	.280	7.11
.007	0.18	.063	1.60	.160	4.06	.290	7.37
.010	0.25	.070	1.78	.165	4.19	.300	7.62
.015	0.38	.075	1.90	.180	4.57	.310	7.87
.016	0.41	.080	2.03	.185	4.70	.340	8.64
.020	0.51	.100	2.54	.195	4.95	.375	9.52
.025	0.64	.105	2.67	.200	5.08	.435	11.05
.030	0.76	.110	2.79	.220	5.59	.475	12.07
.035	0.89	.120	3.05	.225	5.72	.750	19.05
.040	1.02	.125	3.18	.230	5.84	1.000	25.40 *
.050	1.27	.130	3.30	.250	6.35		
.055	1.40	.140	3.56	.260	6.60		

* FIGURE 1, note 3, delete and substitute:

"3. The positive lead on CX06 shall be at least .125 inch (3.18 mm) longer than the negative lead."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Current https://assist.dla.mil - Downloaded: 2025-10-22T19:53Z
Check the source to verify that this is the current version before use.

PAGE 4

Case material, delete and substitute:

"Polyester sleeve and epoxy end filled or plastic encapsulated."

PAGE 5

Following Life requirement, add:

"Resistance to solvents: Not applicable."

At the end of marking, add:

"At the option of the manufacturer, color coding may be used to mark the capacitance, dc rated voltage, and manufacturer's trademark on case sizes A and B and the use of three lines to mark the date, lot code, and manufacturer's trademark on case sizes E, F, and G, as long as it is the same order as shown in the example."

Concluding material: Delete and substitute as printed below.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army - ER

Review activity:
DLA - ES

Preparing activity:
Army - ER

Agent:
DLA - ES

(Project 5910-A410)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:50Z
Check the source to verify that this is the current version before use.