MILITARY SPECIFICATION

PERISCOPES, TANK: 11747126 AND 11747127

This Amendment forms a part of Military Specification MIL-P-48566(MU), dated 9 April 1976, and is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Add Paragraph 3.6.1 as follows:

"3.6.1 Sealing. The Periscope equipped with purging valve, without the head assembly, shall show no evidence of leakage in excess of 0.1 psi/hour at 5 + 0.25 psig internal pressure using dry nitrogen gas having a dew point of -25° or lower. The unit shall also be purged and filled with dry nitrogen gas."

Add Paragraph 4.6.6.1 as follows:

"4.6.6.1 Sealing. For Periscope equipped with purging valve. The nitrogen gas used for this test shall conform to Federal Specification BB-N-411, Type 1, Grade B, Class 1. Prior to performing the sealing test, the internal atmosphere of the Unit shall be tested utilizing the internal pressure testing apparatus of Drawing F8565556 together with a dew point tester. Attach the internal pressure testing apparatus to one purging port and the dew point tester to the other purging port. Apply an internal pressure of 1.0 to 2.0 psig (.07 to .14 kg/cm^2) of nitrogen gas to the periscope assembly while simultaneously capturing the initial exhaust of gas. The dew point of the initial amount of the exhausted gas from the unit shall conform to the requirements of 3.6.1, as measured with the dewpoint tester. Subsequent to this test, the sealing test of the unit shall be performed. The internal pressurizing to test the sealing of the unit shall be performed using the special testing equipment conforming to Drawing F8565556. The unit shall be pressurized to the requirements of 3.6.1 in

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.

accordance with the internal pressure test procedure delineated on Sheets 1 of 2 of Drawing F8565556. The pressure shall be retained for the time period specified. Any evidence of leakage at the end of the minimum time period shall not exceed the tolerance specified in 3.6.1, as measured on the monitoring pressure gages of the testing equipment. Should leakage of the unit exceed the tolerance specified in 3.6.1, the unit shall be considered defective and shall be rejected. A record of beginning and ending local atmospheric pressure and temperature shall be kept. Corrections to the gage reading shall be made based upon any changes in these variables. Temperature changes shall be measured to an accuracy of $\pm$ 0.5°F, pressure changes to $\pm$ 0.2" Hg.

NOTE: An increase of 1°F in the internal temperature of the unit will produce an increase of 0.04 psi in the gage reading. An increase of 0.1" Hg of atmospheric pressure will produce a decrease of 0.05 psi in the gage reading."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-A114)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:32Z
Check the source to verify that this is the current version before use.