MILITARY SPECIFICATION

WARHEAD SECTIONS, GUIDED MISSILE, H.E. M258E6 LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-W-48856B (AR) dated 7 August 1985, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Department and Agencies of the Department of Defense.

PAGE 4

In para 3.4 change:

From: The warhead cable and connector shall meet the following continuity requirements after machining of explosives:

To: The warhead cable and connector shall meet the following continuity requirements prior to loading of explosives and after machining of explosives:

PAGE 7

In para 3.6.2 change:

	RESISTANCE BETWEEN ALL PINS AND WARHEAD CASE	RESISTANCE (OHMS)
From:	All pins + DC	= 10 MEG OHMS
	All pins - DC	= 10 MEG OHMS
To:	All pins + DC	$\geq$ 10 MEG OHMS
	All pins - DC	$\geq$ 10 MEG OHMS

AMSC N/A FSC: 1336
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assistdla.mil - Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.

In para 4.4.2.2 change Major Characteristics 101, 109, 110 to read under the appropriate columns as follows:

Category Major	Exam or Test	AQL or 100%	Req Para	Para ref/ Insp. Meth
101	Continuity does not conform to requirements prior to loading.	100%	3.4	4.5.3/ 4.5.5/ Gage
109	J1 connector damaged, not secure 1/, or misaligned prior to loading.	100%	3.2	Visual/ Manual/ Gage
110	P3 connector damaged prior to loading.	100%	3.2	Visual/ Manual

In para 4.4.2.2 add new major categories in the appropriate columns as follows:

Category Major	Exam or Test	AQL or 100%	Req Para	Para ref/ Insp. Meth
111	Continuity does not conform to requirements after loading	100%	3.4	4.5.3/ 4.5.5/ Gage
112	P3 connector damaged after loading	100%	3.2	Visual/ Manual

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1336-A518)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:42Z
Check the source to verify that this is the current version before use.