NOT MEASUREMENT SENSITIVE


MIL-DTL-3628/166D
20 February 2024
SUPERSEDING
MIL-DTL-3628/166C
5 October 2020

DETAIL SPECIFICATION SHEET

BADGE, ASTRONAUT DEVICE FOR SPECIFIED QUALIFICATION AND OCCUPATIONAL BADGES, USAF/USSF/ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3628.



DASH NO.
-1: Regular Size
-2: Miniature Size
-3: Dress Miniature Size
-4: Regular Size, Subdued

MATERIAL:
Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
-1, -2, -3: 24K Gold Plated, Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.

-4: Dull, Flat Brown Enamel Finish and shall match TIOH Metal Finish Chip Number 22.

DEMINSION (Device):
HEIGHT (Overall):
-1, -4: 15/32 inch (REF)
-2: 3/8 inch (REF)
-3: 15/64 inch (REF)

WIDTH (Overall):

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:56Z
Check the source to verify that this is the current version before use.

-1, -4: 11/32 inch (REF)
-2: 9/32 inch (REF)
-3: 11/64 inch (REF)
THICKNESS (At thickest point): 0.050 inch ± 0.010 inch

ASTRONAUT DEVICE:

1. That portion of the design element of the badges to which the astronaut device will be affixed shall be recessed sufficiently to provide a flat platform to which the device shall be soldered. At the option of the manufacturer, the platform may be cut into the working die.
2. An astronaut device shall be affixed to the shield portion of the Army Aviator, Army Flight Surgeon, and Army Aircraft Crewman badges as shown on TIOH Drawing B-5-84.
3. An astronaut device shall be affixed to the delta, globe portion of the Space badges as shown on TIOH Drawing B-5-170B.
4. Images are for illustration of astronaut device placement.



AVIATION BADGE WITH ASTRONAUT DEVICE



SPACE BADGE WITH ASTRONAUT DEVICE

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Badges with the astronaut device attached shall be manufactured in accordance with the latest revision to the following specification sheets:

MIL-DTL-3628/157	Badge, Qualification, Aviation, Aviator, Army
MIL-DTL-3628/158	Badge, Qualification, Aviation, Aviator, Senior, Army
MIL-DTL-3628/159	Badge, Qualification, Aviation, Aviator, Master, Army
MIL-DTL-3628/160	Badge, Qualification, Aviation, Flight Surgeon, Army
MIL-DTL-3628/161	Badge, Qualification, Aviation, Flight Surgeon, Senior, Army
MIL-DTL-3628/162	Badge, Qualification, Aviation, Flight Surgeon, Master, Army
MIL-DTL-3628/163	Badge, Qualification, Aviation, Aircraft Crewman, Army
MIL-DTL-3628/164	Badge, Qualification, Aviation, Aircraft Crewman, Senior, Army
MIL-DTL-3628/165	Badge, Qualification, Aviation, Aircraft Crewman, Master, Army
MIL-DTL-3628/238	Badge, Occupational, Space, Air Force/Space Force/Army

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
Air Force - 11

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-071)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T19:56Z
Check the source to verify that this is the current version before use.