M1L-C-62191
AMENDMENT 2
14 November 1985
SUPERSEDING
Amendment 1
30 June 1978

MILITARY SPECIFICATION

CONTROL ASSEMBLY, PUSH-PULL, GENERAL SPECIFICATION FOR

This amendment forms a part of Military Specification MIL-C-62191, dated 25 March 1974 and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1, under SPECIFICATIONS, Federal: Delete the following,

"PP-B-621	- Boxes, Wood, Nailed and Lock Corner."
"PP-B-636	- Box, Fiberboard."
"MIL-P-116	- Preservation, Method of."

2.1, under SPECIFICATIONS, Federal: After "TT-E-489", Insert,

"TT-E-529	- Enamel, Alkyd, Semi-gloss."

2.1, under STANDARDS, Military: Delete,

"MIL-STD-129	- Marking for Shipment and Storage."

PAGE 2

3.2, line 6: Add at the end of paragraph "'There is no requirement that an Item be manufactured from virgin materials (see 6.5).'"

PAGE 3

3.3.3.1, line 3: Add to end of sentence l "per TT-E-489 or TT-E-529."

FSC 2990

DISTRIRUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:24Z
Check the source to verify that this is the current version before use.

PAGE 4

*Table I, Dash No. 28, under “C”: Delete “’34.000” and substitute “134.000”, and under "D": Delete “37.500” and substitute “137.500”.

PAGE 5

Table I, Dash No. 32, under ““D’”: Delete "88.000”” and substitute “76.000”’.

PAGE 6

3.3.7.3, line 4: Delete “’conforming to Federal Specification TT-E-489." Add to end of paragraph "On plastic knobs, hot stamp marking with contrasting color is acceptable.”

3.3.10: Delete first sentence and substitute “Guide tube shall be of brass, steel, zinc or aluminum or a combination of the above. When steel is used, it shall have a corrosion resistant electrochemical finish. The guide tube shall usually incorporate the treaded mounting adapter and mounting shoulder.”

3.3.10.2,1ine 6: Delete "1/4 inch diameter” and substitute “3/32 inch diameter.”

PAGE 7

3.4.1.1: Delete second sentence and substitute "Where locking action is actuated by the turning of the T-handle, locking and unlocking shall be accomplished with a minimum of 1/4 turn and a maximum of 3/4 turn of the handle to right or left.*’

PAGES 12, 13 and 14

5.1 thru 5.3: Delete and substitute,

"5.1 Preservation, packing, packing, and marking. Preservation, packaging, packing, and marking shall be in accordance with the applicable packaging standard or packaging data sheet, as furnished at the time of invitation for bid for the level of Preservation and packaging, and level of packing specified (see 6.2). “

PAGE 15

6.2, line K: Delete entire sentence and substitute “’Selection of applicable level of preservation and packaging and level of packaging (see 5.1).”’

Add the following new paragraph,

"6.5 Recycled materials. The use of recycled materials which meet the requirements of the applicable material specifications without jeopardizing the intended use of the item shall be encouraged (see 3.2).’”

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:24Z
Check the source to verify that this is the current version before use.

The margin of this amendment is marked with an asterisk to indicate where an addition from the previous amendment was made. This was done as a convenience only and the Government assumes no liabillty whatsoever for any inaccuracies in the notation. Bidders and contractors are cautioned to evaluate the requirement of this document based on the entire content irrespective of the marginal notation and relationship to the previous amendment.

Custodian:
Army - AT
Navy - YD
AF-99

Preparing activity:
Amy - AT

(Project No. 2990-0102)

Review activities:
DLA - CS
AF-82

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T01:24Z
Check the source to verify that this is the current version before use.