INCH-POUND

MIL-PRF-55365/4E
AMENDMENT 1
9 November 2000

PERFORMANCE SPECIFICATION

CAPACITORS, CHIP, FIXED, TANTALUM, ESTABLISHED RELIABILITY,
STYLES CWR06 AND CWR09

This amendment forms a part of MIL-PRF-55365/4E, dated 3 July 1997, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Under NOTES: delete note 9 in its entirety and replace with the following. “9. When solder coated terminations are required, add an additional .015 inch (0.38 mm) to the above listed tolerances for “L”, “W”, “H” and “P” for each case size.”

PAGE 4

Under NOTES: delete note 8 in its entirety and replace with the following. “8. When solder coated terminations are required, add an additional .015 inch (0.38 mm) to the above listed tolerances for “L”, “W”, “H”, “P” and “W_2” for each case size.”

Change TABLE I to TABLE II at each place that it occurs on this page.

PAGE 5

Change TABLE I to TABLE II at each place that it occurs on this page.

Delete in its entirety: “Surge current (optional): This test, when applicable, shall be performed on a 100 percent basis following voltage conditioning of the qualification and group A tests. Capacitors shall be subjected to ten consecutive cycles under the following conditions:”

Replace with: “Surge current (optional): This test when applicable, shall be performed on a 100 percent basis following voltage aging for qualification and group A tests. If option A, B, or C is requested, the test sequence and temperature shall be as described in Table I. In all cases, the capacitors shall be subjected to 10 consecutive cycles under the following conditions:”

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.

The following Table I shows the three performed surge current tests and when they are performed with respect to Voltage aging (exponential) or Weibull grading (Life accelerated).

TABLE I. Optional surge current testing

	Following Voltage Aging Exponential	Before Weibull Grading (Life accelerated FR)	After Weibull Grading (Life accelerated FR)
Option A (+25°C ± 5°C)	X	N/A	X
Option B (-55°C +5°C, -0°C and +85°C ±5°C)	X	N/A	X
Option C (-55°C +5°C, -0°C and +85°C ±5°C)	N/A	X	N/A

MIL-PRF-55365/4, Page 5, following Temperature: delete in its entirety and replace with Option A: (+25°C ±5°C) or Option B: (-55°C +5°C, -0°C and +85°C ±5°C) or Option C: (-55°C +5°C, -0°C and +85°C ±5°C).

PAGE 6

Change from .09 to .9 the ESR of the following parts: CWR0-C-107---, CWR0-D-686---, CWR0-F-476---, CWR0-H-336---

Change Cap. Value of CWR0-F-336--- and CWR0-H-336--- from 33.3 to 33.0

Change TABLE I to TABLE II

PAGE 7

Change TABLE I to TABLE II

Change CWR0-N-475--- from an ESR of 2.0 to 1.5, change ESR of CWR0-J-226--- from .09 to .9

Table II, footnote 1, delete in its entirety and replace with: "1/ Complete PIN shall include additional symbols to indicate system termination finish, capacitance, tolerance, product level and if applicable, surge current option letter A: (+25°C ± 5°C) or Option B: (-55°C +5°C –0°C and +85°C ± 5°C) which can be done after Weibull grading or exponential voltage aging. Option C: (-55°C +5°C –0°C and +85°C ± 5°C) is for Weibull grading only with surge current testing done prior to Weibull grading. If optional surge current is not required, the last "-" shall be deleted."

Custodians:
Army - CR
Navy - EC
Air Force - 11

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS, SH
Air Force - 19, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-2006)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:16Z
Check the source to verify that this is the current version before use.