METRIC
MIL-PRF-55681/10B
3 July 1997
SUPERSEDING
MIL-C-55681/10A
14 July 1989

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, CHIP, MULTIPLE LAYER, FIXED, CERAMIC DIELECTRIC, ESTABLISHED RELIABILITY AND NON-ESTABLISHED RELIABILITY, STYLE CDR34, METRIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-55681.



mm	Inches
0.25	.010
0.30	.012
0.50	.020
0.60	.023
1.50	.059
3.20	.125
4.50	.176

NOTES:
1. Dimensions are in millimeters.
2. Unless otherwise specified, tolerance is ± .25.
3. Dimensions and tolerances are for bare chips. For solder coated terminations add .60 to the positive length tolerance and .30 to the positive width and thickness tolerance.
4. Inch equivalents are given for general information only.

FIGURE 1. Style CDR34 capacitors.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:55Z
Check the source to verify that this is the current version before use.

TABLE I. Style CDR34 capacitor characteristics.

Part or Identifying Number (PIN) 1/	Capacitance pF	Capacitance tolerance	Rated temperature and voltage-temperature limits	Rated voltage V dc
CDR34BP222B - - -	2,200	F, J, K	BP	100
CDR34BP242B - - -	2,400	F, J, K	BP	100
CDR34BP272B - - -	2,700	F, J, K	BP	100
CDR34BP302B - - -	3,000	F, J, K	BP	100
CDR34BP332B - - -	3,300	F, J, K	BP	100
CDR34BP362B - - -	3,600	F, J, K	BP	100
CDR34BP392B - - -	3,900	F, J, K	BP	100
CDR34BP432B - - -	4,300	F, J, K	BP	100
CDR34BP472B - - -	4,700	F, J, K	BP	100
CDR34BP512A - - -	5,100	F, J, K	BP	50
CDR34BP562A - - -	5,600	F, J, K	BP	50
CDR34BP622A - - -	6,200	F, J, K	BP	50
CDR34BP682A - - -	6,800	F, J, K	BP	50
CDR34BP752A - - -	7,500	F, J, K	BP	50
CDR34BP822A - - -	8,200	F, J, K	BP	50
CDR34BP912A - - -	9,100	F, J, K	BP	50
CDR34BP103A - - -	10,000	F, J, K	BP	50
CDR34BX273B - - -	27,000	K, M	BX	100
CDR34BX333B - - -	33,000	K, M	BX	100
CDR34BX393B - - -	39,000	K, M	BX	100
CDR34BX473B - - -	47,000	K, M	BX	100
CDR34BX563B - - -	56,000	K, M	BX	100
CDR34BX104A - - -	100,000	K, M	BX	50
CDR34BX124A - - -	120,000	K, M	BX	50
CDR34BX154A - - -	150,000	K, M	BX	50
CDR34BX184A - - -	180,000	K, M	BX	50

1/ The complete PIN will include additional symbols to indicate capacitance tolerance, termination and product level.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Capacitance value: See table I.

Capacitance tolerance: F = ±1 percent; J = ±5 percent; K = ±10 percent; M = ±20 percent. See table I.

Rated voltage: See table I.

Operating temperature range: -55°C to +125°C.

Product level: Non-established Reliability - C; Established Reliability - M, P, R, and S.

Marking: In accordance with MIL-PRF-55681.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:55Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Navy - AS, MC, OS, SH
Air Force - 19, 99
DLA - CC

Preparing activity:
Army - CR

Agent:
DLA - CC

(Project 5910-1923-10)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T23:55Z
Check the source to verify that this is the current version before use.