MILITARY SPECIFICATION

CARTRIDGE, THRUSTER, M42A1

This amendment forms a part of Military Specification MIL-C-46200A(MU), dated 2 July 1963, and is approved for use within the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* 2.1 Delete: "MIL-E-5272. . ." and "MIL-STD-639. . ." in their entirety.
Add: "MIL-STD-810 Environmental Test Methods and Engineering Guidelines".

* Add: "2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the document which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer, Naval Ordnance Station, Standardization Branch (5241), Indian Head, MD 20640-5000.

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:12Z
Check the source to verify that this is the current version before use.

PAGE 2

ANSI B46.1 Surface Texture (Surface Roughness, Waviness and Lay)

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, NY 10018.)

(Nongovernment standards and other publications are normally available from the organization which prepares or which distributes the documents. These documents also may be available in or through libraries or other informational services.)"

PAGE 2

* 3.5.1 Delete ". . . prescribed in specification MIL-E-5272, Procedure XII . . ." and substitute ". . . prescribed in MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5 . . .".

4.2 Delete "30 cartridges" and substitute "35 cartridges".

* 4.3.2 Delete "The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 . . ." and substitute "The roughness comparison standards prescribed in ANSI-B46.1 . . .".

PAGE 6

4.3.3.3 Delete "30 assembled x-rayed cartridges" and substitute "35 assembled x-rayed cartridges".

Add: "4.3.3.5 Sealant application. Five cartridges from each production lot shall be selected for this test. Failure of any cartridge to comply with the drawing requirements shall be cause for rejection of the lot of cartridges".

* 4.4.3 Delete ". . . Specification MIL-E-5272, Procedure XII" and substitute ". . . MIL-STD-810, Method 514.3, Test Procedure I, Test Condition I-3.2.5".

Add: "4.4.4.5 Sealant application. The cartridge shall be disassembled in such a manner that determination can be made that the sealant has been applied for the full length of the joining surface at the junction of the cartridge head and case sidewall and that the propellant cavity is free of sealant."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:12Z
Check the source to verify that this is the current version before use.

6.1 Delete and substitute:

"6.1 Advisory propellant loading data.

Black powder, Class A-4	20.0 grains minus 2.0 grains
Propellant, Class M-10	31.0 grains minus 3.0 grains

Grains dimensions

Length	.135
Diameter	.049
Perforation diameter	.013
Web thickness	.018
No. of perforations	one"

Changes from previous issue. The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Preparing Activity:
Navy - OS
Project No. 1377-N831

☆U.S. GOVERNMENT PRINTING OFFICE: 1986 — 704-036/45798

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T05:12Z
Check the source to verify that this is the current version before use.