MIL-T-21868/3B(SA)
5 May 1984
SUPERSEDING
MIL-T-21868/3A
15 March 1976

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, SOLID TIRES

6,000 POUND (2722 KG) CAPACITY, 130 INCH (3300 MM) LIFT, SHIPBOARD

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification For, dated 5 May 1984.

REQUIREMENTS

1.	Capacity	6000 Lbs. (2722kg) at 24 inch (610mm) load center
2.	Collapsed mast height	87 1/2 inches (2225 mm) (maximum)
3.	Fork lift height	130 inches (3300 mm) (minimum)
4.	Free lift height	42 inches (1065 mm) (minimum)
5.	Fork mounting	MS 16956 or MS 16959
6.	Fork size, folding type	2 inches (50 mm) thick (maximum) 6 inches (150 mm) wide (maximum) 40 inches (1015 mm) long + 0 inches (0 mm) -1/2 inches (15 mm)
7.	Fork spacing (measured between outer edges of forks)	40 inches (1015mm) spread (minimum) 14 inches (355 mm) together (maximum)
8.	Solid tires	2 drive 2 steer
9.	Overall truck length	152 inches (3860 mm) (maximum with forks)
10.	Overall truck width	50 inches (1270 mm) (maximum)
11.	Overhead guard height	87 inches (2210 mm) (maximum)
12.	Gross truck weight	12,500 pounds (5669 kg) (maximum)
13.	Static overhead guard test load	11,000 lbs. (4989 kg)
14.	Right angle turn dimension "A"	164 inches (4165 mm)
15.	Underclearance beneath mast assembly loaded	3 inches (75 mm) (minimum)
16.	Longitudinal stability - stacking	4 percent slope (2.3 degrees)
	- traveling	27 percent slope (15.1 degrees)
17.	Lateral stability - stacking	6 percent slope (3.4 degrees)
	- traveling	40 percent slope (21.8 degrees)
18.	Acceleration	0 to 22 Ft (7 m) in 4 sec 22 Ft (7 m) to 44 Ft (14 m) in 2 sec

Custodian:

Navy - SA

Review Activities:

Navy - SA, MC

User Activities:

Navy - SA,SH,MC

Preparing Activity:

Navy - SA

Project No. 3930-0561

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.