INCH-POUND
MIL-T-21868/3C(SA)
5 DECEMBER 1989
SUPERCEDING
MIL-T-21868/3B(SA)
5 MAY 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, SOLID TIRES, 6,000 POUND (2722 KG) CAPACITY, 130 INCH (3300 MM) LIFT, SHIPBOARD

The complete requirements for procuring this truck described herein shall consist of this document and Military Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification for, dated 5 December 1989.

REQUIREMENTS

1.	Capacity	6000 Lbs. (2722kg) at 24 inch (610mm) load center
2.	Collapsed mast height	87 1/2 inches (2225 mm) (maximum)
3.	Fork lift height	130 inches (3300 mm) (minimum)
4.	Free lift height	42 inches (1065 mm) (minimum)
5.	Fork size, folding type	2 inches (50 mm) thick (maximum) 6 inches (150 mm) wide (maximum) 40 inches (1015 mm) long + 0 inches (0 mm) -1/2 inches (15 mm)
6.	Fork spacing	40 inches (1015mm) spread (minimum) 14 inches (355 mm) together (maximum)
7.	Solid tires	2 drive 2 steer
8.	Overall truck length	152 inches (3860 mm) (maximum with forks)
9.	Overall truck width	50 inches (1270 mm) (maximum)
10.	Overhead guard height	87 inches (2210 mm) (maximum)
11.	Truck weight (without rated load)	12,500 pounds (5669 kg) (maximum)
12.	Right angle turn dimension "A"	164 inches (4165 mm) (maximum)
13.	Underclearance	3 inches (75 mm)(minimum)
14.	Longitudinal stability (minimum)	
	- stacking	4 percent slope (2.3 degrees)
	- traveling	27 percent slope (15.1 degrees)
15.	Lateral stability (minimum)	
	- stacking	6 percent slope (3.4 degrees)
	- traveling	40 percent slope (21.8 degrees)
16.	Deck loading	7,400 pounds (3356 kg) (maximum)

Custodian:
Army - None
Navy - SA
Air Force - None

Preparing Activity
Navy - SA

Project No 3930-0645-1

Interested Activities
User and Review - Navy - SH

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.