MIL-T-21868/4B(SA)
5 May 1984
SUPERSEDING
MIL-T-21868/4A
15 March 1976

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, PNEUMATIC TIRES,

6,000 POUND (2722 KG) CAPACITY, 130 INCH (3300 MM) LIFT, SHIPBOARD

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification For, dated 5 May 1984.

REQUIREMENTS

1.	Capacity	6,000 Lbs. (2772kg) at 24 inches (610mm) load center
2.	Collapsed mast height	89 1/4 inches (2265mm) (maximum)
3.	Fork lift height	130 inches (3300mm) (minimum)
4.	Free lift height	51 inches (1295mm) (minimum)
5.	Fork mounting	MS 16956 or MS 16959
6.	Fork size, folding type	2" (5mm) thick (maximum) 6" (150mm) wide (maximum) 40" (1015mm) long plus 0" - 1/2"
7.	Fork spacing (measured between outer edges of forks	48" (1220mm) spread (minimum) 14" (355mm) together (maximum)
8.	Pneumatic Tires	4- drive (2 dual) 2- steer
9.	Overall Truck Length	160 inches (4065mm) (maximum with forks)
10.	Overall Truck Width	69 inches (755mm) (maximum)
11.	Overhead guard height	91 inches (2310mm) (maximum)
12.	Gross Truck Weight	13,000 lbs. (5869kg) (maximum)
13.	Static overhead guard test load	11,000 lbs. (4989kg)
14.	Right angle turn dimension "A"	200 inches (5080mm)
15.	Underclearance beneath mast assembly loaded	5 inches (125mm) (minimum)
16.	Longitudinal stability	
	- stacking	4 percent slope (2.3 degrees)
	- traveling	18 percent slope (10.2 degrees)
17.	Lateral stability - stacking	6 percent slope (3.4 degrees)
	- traveling	40 percent slope (21.8 degrees)
18.	Acceleration	0 to 22 ft. (7m) in 4 sec. 22 Ft (7 mm) to 44 ft. (14m) in 2 sec.

Custodian:

Navy - SA

User Activities:

Navy - SA,SH,MC

Review Activities:

Navy - SA, MC

Preparing Activity:

Navy - SA

Project No. 3930-0562

© U.S. GOVERNMENT PRINTING OFFICE: 1984—705—040/A3068

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.