INCH-POUND
MIL-T-21868/4C(SA)
5 DECEMBER 1989
SUPERCEDING
MIL-T-21868/4B(SA)
5 MAY 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, PNEUMATIC TIRES, 6,000 POUND (2722 KG) CAPACITY, 130 INCH (3300 MM) LIFT, SHIPBOARD

The complete requirements for procuring this truck described herein shall consist of this document and Military Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification for, dated 5 December 1989.

REQUIREMENTS

1.	Capacity	6,000 Lbs. (2772kg) at 24 inches (610mm) load center
2.	Collapsed mast height	89 1/4 inches (2265mm) (maximum)
3.	Fork lift height	130 inches (3300mm) (minimum)
4.	Free lift height	51 inches (1295mm) (minimum)
5.	Fork size, folding type	2" (5mm) thick (maximum) 6" (150mm) wide (maximum) 40" (1015mm) long plus 0" - 1/2"
6.	Fork spacing	48" (1220mm) spread (minimum) 14" (355mm) together (maximum)
7.	Pneumatic Tires	4- drive (2 dual) 2- steer
8.	Overall Truck Length forks)	160 inches (4065mm) (maximum with
9.	Overall Truck Width	69 inches (755mm) (maximum)
10.	Overhead guard height	91 inches (2310mm) (maximum)
11.	Truck weight (without rated load)	13,000 lbs. (5869kg) (maximum)
12.	Right angle turn dimension "A"	200 inches (5080mm) (maximum)
13.	Underclearance	5 inches (125mm) (minimum)
14.	Longitudinal stability (minimum)	
	- stacking	4 percent slope (2.3 degrees)
	- traveling	18 percent slope (10.2 degrees)
15.	Lateral stability (minimum)	
	- stacking	6 percent slope (3.4 degrees)
	- traveling	40 percent slope (21.8 degrees)
16.	Deck loading	4,000 pounds (1814 kg) (maximum)

Custodian:
Army None
Navy SA
Air Force None

Interested Activities
User and Review - Navy - SH

Preparing Activity
Navy SA

Project No 3930-0645-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.