MIL-T-21868/8B(SA)
5 May 1984
SUPERSEDING
MIL-T-21868/8A
15 March 1976

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, PNEUMATIC TIRES,

20,000 POUND (9070 KG) CAPACITY, 220 INCH (5590 MM) LIFT, SHIPBOARD

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification For, dated 5 May 1984.

REQUIREMENTS

1.	Capacity	20,000 Lbs. (9070kg) at 24 inches (610mm) load center
2.	Collapsed mast height	128 inches (3250mm) (maximum)
3.	Fork lift height	220 inches (5590mm) (minimum)
4.	Free lift height	6 inches (150mm) (minimum)
5.	Fork mounting	N.A.
6.	Fork size	3" (75mm) thick (maximum) 10" (25mm) wide (maximum) 48" (1220mm) long + 0" - 1/2"
7.	Fork spacing (measured between outer edges of forks)	58" (1475mm) spread (minimum) 22" (560mm) together (maximum)
8.	Pneumatic tires	4- drive (2 dual) 2- steer
9.	Overall truck length	240 inches (6095mm) (maximum with forks)
10.	Overall truck width	96 inches (2440mm) (maximum)
11.	Overhead guard height	103 inches (2615mm) (maximum)
12.	Gross truck weight	30,800 Lbs. (1368kg) (maximum)
13.	Static overhead guard test load	20,000 Lbs. (9070kg)
14.	Right angle turn dimension "A"	264 inches (6705 mm)
15.	Underclearance beneath mast assembly	6 inches (150mm) (minimum) loaded
16.	Longitudinal stability	
	- stacking	4 percent slope (2.3 degrees)
	- traveling	18 percent slope (10.2 degrees)
17.	Lateral stability - stacking	10 percent slope (5.7 degrees)
	- traveling	50 percent slope (26.6 degrees)
18.	Acceleration	0 to 100 ft (31m) in 12 sec.

Custodian:
Navy - SA

Review Activities:
Navy - SA, MC

User Activities:
Navy - SA, SH, MC,

Preparing Activity:
Navy - SA

Project No. 3930-0565

* U.S. GOVERNMENT PRINTING OFFICE: 1984—703—040/A3070

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.