INCH-POUND
MIL-T-21868/8C(SA)
5 DECEMBER 1989
SUPERCEDING
MIL-T-21868/8B(SA)
5 MAY 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, PNEUMATIC TIRES, 20,000 POUND (9070 KG) CAPACITY, 220 INCH (5590 MM) LIFT, SHIPBOARD

The complete requirements for procuring this truck described herein shall consist of this document and Military Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification for, dated 5 December 1989.

REQUIREMENTS

1.	Capacity	20,000 Lbs. (9070kg) at 24 inches (610mm) load center
2.	Collapsed mast height	134 inches (3405mm) (maximum)
3.	Fork lift height	220 inches (5590mm) (minimum)
4.	Free lift height	6 inches (150mm) (minimum)
5.	Fork size	3" (75mm) thick (maximum) 10" (25mm) wide (maximum) 48" (1220mm) long + 0" - 1/2"
6.	Fork spacing	58" (1475mm) spread (minimum) 22" (560mm) together (maximum)
7.	Pneumatic tires	4- drive (2 dual) 2- steer
8.	Overall truck length forks)	240 inches (6095mm) (maximum with
9.	Overall truck width	98 inches (2490mm) (maximum)
10.	Overhead guard height	115 inches (2920mm) (maximum)
11.	Truck weight (without rated load)	30,800 Lbs. (1368kg) (maximum)
12.	Right angle turn dimension "A"	264 inches (6705 mm) (maximum)
13.	Underclearance	6 inches (150mm) (minimum) loaded
14.	Longitudinal stability (minimum)	
	-stacking	4 percent slope (2.3 degrees)
	-traveling	18 percent slope (10.2 degrees)
15.	Lateral stability (minimum)	
	-stacking	10 percent slope (5.7 degrees)
	-traveling	40 percent slope (21.8 degrees)
16.	Deck loading	10,500 pounds (4762 kg) (maximum)

Custodian:
Army None
Navy SA
Air Force None

Interested Activities
User and Review - Navy - SH

Preparing Activity
Navy - SA
Project No 3930-0645-4

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.