MIL-T-21868/9A(SA)
5 May 1984
SUPERSEDING
MIL-T-21868/9
17 March 1976

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, SOLID TIRES,

6,000 POUND (2722 KG) CAPACITY, 92 INCH (2335 MM) LIFT, SHIPBOARD, LOW SILHOUETTE

The complete requirements for procuring this truck described herein shall conist of this document and Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification For, dated 5 May 1984.

REQUIREMENTS

1.	Capacity	6,000 lbs, (2722kg) at 24 inches (610mm) load center
2.	Collapsed mast height	68 inches (1225mm) (maximum)
3.	Fork lift	92 inches (2335mm) (minimum)
4.	Free lift height	33 1/2 inches (850mm) (minimum)
5.	Fork mounting	MS 16956 or MS 16959
6.	Fork size, folding type	2 1/16" (52mm) thick (maximum) 6 1/16" (155mm) wide (maximum) 40" (1015mm) long + 0" - 1/2"
7.	Fork spacing (measured between outer edges of forks)	44" (1120mm) spread (minimum) 14" (355mm) together (maximum)
8.	Solid tires	2- drive and 2-steer
9.	Overall truck length	154 inches (3910mm) (maximum with forks)
10.	Overall truck width	61 inches (1550mm) (maximum)
11.	Overhead guard height	70 inches (1780mm) (maximum)
12.	Gross truck weight	12,800 lbs. (5805kg) (maximum)
13.	Seat Height	28 inches (710mm) (maximum) above floor level
14.	Static overhead guard test load	11,000 lbs. (4989kg)
15.	Right angle turn dimension "A"	180 inches (4572mm)
16.	Underclearance beneath mast assembly -loaded	3 inches (75mm) (minimum)
17.	Longitudinal stability	
	- stacking	8 percent slope (4° 35')
	- traveling	27 percent slope (15° 7')
18.	Lateral stability - stacking	8 percent slope (4o 35')
	- traveling	40 percent slope 21° 48')
19.	Upright tilt	5 degrees forward (minimum) 10 degrees rearward (minimum)
20.	Acceleration	0 to 22 Ft (7 m) in 4 sec. 22 Ft to 44 Ft (14 m) in 2 sec.

Custodian:
Navy-SA

Review Activities:
Navy - SA, MC

User Activities:
Navy, SA, SH, MC

Preparing Activity:
Navy - SA,

Project No. 3930-0566

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.