INCH-POUND
MIL-T-21868/9B(SA)
5 DECEMBER 1989
SUPERCEDING
MIL-T-21868/9A(SA)
5 MAY 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, DIESEL, SOLID TIRES,

6,000 POUND (2722 KG) CAPACITY, 92 INCH (2335 MM) LIFT, SHIPBOARD, LOW SILHOUETTE

The complete requirements for procuring this truck described herein shall consist of this document and Military Specification MIL-T-21868, Trucks, Lift, Fork, Diesel, Shipboard, General Specification for, dated 5 December 1989.

REQUIREMENTS

1.	Capacity	6,000 lbs. (2722kg) at 24 inches (610mm) load center
2.	Collapsed mast height	68 inches (1225mm) (maximum)
3.	Fork lift	92 inches (2335mm) (minimum)
4.	Free lift height	33 1/2 inches (850mm) (minimum)
5.	Fork size, folding type	2 1/16" (52mm) thick (maximum) 6 1/16" (155mm) wide (maximum) 40" (1015mm) long + 0" - 1/2"
6.	Fork spacing	44" (1120mm) spread (minimum) 14" (355mm) together (maximum)
7.	Solid tires	2- drive 2-steer
8.	Overall truck length forks)	154 inches (3910mm) (maximum with
9.	Overall truck width	66 inches (1675mm) (maximum)
10.	Overhead guard height	70 inches (1780mm) (maximum)
11.	Truck weight (without rated load)	12,800 lbs. (5805kg) (maximum)
12.	Seat Height floor level	30 inches (760mm) (maximum) above
13.	Right angle turn dimension "A"	180 inches (4572mm) (maximum)
14.	Underclearance	3 inches (75mm) (minimum)
15.	Longitudinal stability (minimum)	
	- stacking	8 percent slope (4° 35')
	- traveling	27 percent slope (15° 7')
16.	Lateral stability (minimum)	
	- stacking	8 percent slope (4o 35')
	- traveling	40 percent slope 21° 48')
17.	Deck loading	8400 pounds (3809 kg) (maximum)

Custodian:
Army None
Navy SA
Air Force None

Interested Activities
User and Review - Navy - SH

Preparing Activity
Navy - SA

Project No 3930-0645-5

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:35Z
Check the source to verify that this is the current version before use.