INCH-POUND

MIL-T-21869/12F
1 December 1989
SUPERSEDING
MIL-T-2l869/l2E
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

2,000 POUND (910 KILOGRAM) CAPACITY, 127 INCH (3220 MILLIMETER) LIFT,

GENERAL PURPOSE, TYPE "EE"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For.

REQUIREMENTS

1.	Capacity	2,000 Lbs. (910 Kg) at 24 inches (610mm) load center
2.	Collapsed mast height	84 inches (2130mm) (maximum)
3.	Fork height	127 inches (3220mm) (minimun)
4.	Free lift height	57 inches (1450mm) (minimum)
5.	Fork size	1.81 in. thick (50mm) (maximun) 4.06 in. wide (100mm) (maximum) 36 in. (910mm) long + 0.25" (6mm) 0.5" (mm)
6.	Fork spacing	28 in. (710mm) spread (minimum)
7.	Static overhead guard test load	4,000 Lbs. (1820mm)
8.	0verhead guard height	84 inches (2130mm) (maximum)
9.	Tangential steering force at rim of had wheel	150 Lbs. (670N) for nonpower and 25Lbs. (110N) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100mm) when side shifter attachment is used)	128 inchs (3250mm)
11.	Lifting speed	30 feet (9m) per minute (minimun)
12.	Lowering speed	27 feet (8m) per minute (minimum)
13.	High drive speed	5 to 8 miles (8 to 13Km) per hour
14.	Slope ascension	15 percent slope (8.5 dgrees)
15.	Stability to be in accordance with ANSI B56.1	
16.	Upright Tilt: Forward Rearward	(2 degrees +/- 0.5 degree) (6.5 dgrees +/- 0.5 dgree)

17. Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 15367.

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:36Z
Check the source to verify that this is the current version before use.