INCH-POUND

MIL-T-21869/21G
1 December 1989
SUPERSEDING
MIL-T-21869/21F
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFRT, FORK, ELECTRIC, SOLID TIRES,

4,000 POUND (1820 KILOGRAMS) CAPACITY, 100 INCH (2540 MILLIMETERS) LIFT,

SHIPBOARD, TYPE "EE"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For.

REQUIREMENTS

1.	Capacity	4,000 lbs. (1820 kg) at 24 inches (610mm) load center
2.	Collapsed mast height	68 inches (1720mm) (maximum)
3.	For k Fork height	100 inches (2540mm) (minimum)
4.	Free Free lift height	42 inches (1070mm) (minimum)
5.	Fork Fork size	1.81 in. (50mm) thick (maximum) 5.06 in. (130mm) wide (maximum) 36 in. (910mm) long + 0.25in. (6mm) 0.5 inches (l2mm)
6.	For k Fork spacing (Measured between outer edges of forks):	38 inch (970mm) spread (minimum) 12 inch (300mm) together (maximum)
7.	Static overhead guard test load	8,000 LbS. (3630kg)
8.	Overhead guard height	91 inches (2310mm) (maximum)
9.	Tangential steering force at rim of hand wheel	150 Lbs. (670N) for nonpower and 25 Lbs. (110N) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100m) when side shifter attachment is used)	142 inches (3600mm)
11.	Lifting speed	25 feet (8m) per minute (minimum)
12.	Lowering speed	27 feet (8m) per minute (minimum)
13.	High drive speed.	3.5 to 4.5 miles (6-7Km) per hour
14.	Slope ascension	26.8 percent slope (15 degrees) 6 percent slope (3.4 degrees)
15.	Longitudinal stability - stacking traveling	26.8 percent slope (15 degrees) 9 percent slope (5.2 degrees)
16.	Lateral stability - stacking traveling	40 percent slope (21.8 degrees)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.

17.	Semite brakes	4 wheels
18.	Parking Brakes	Hand brake required
19.	Overall truck width	42 inches (1077mm) (maximum}
22.	Upright Tilt: forward	(2 degrees +/- 0.5 degree)
	rearward	(6.5 degrees +/- 0.5 degree)

21. Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 15367.

22 l Siped tires, folding forks, weighing device, and sideshift attachment are required.

23.	Overall maximum length measured from the forward portion of the heel of the fork to the rear extreme of the truck.	96 inches (2440mm)
24.	Overall maximum weight of truck with battery	9900 Lbs . (4500Kg)

FSC 3930

Custodian:

Navy - SA

Review Activities:

Navy - SH, OS

User Activity:

Navy - MC

Preparing Activity:

Navy - SA

Project No.

3930-0644-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.