MIL-T-21869/22G
1 December 1989
SUPERSEDING
MIL-T-21869/22F
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

6000 POUND (2730 KILOGRAMS) CAPACITY, 100 INCH (2540 MILLIMETERS) LIFT,

SHIPBOARD, TYPE "EE"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification Rx.

REQUIREMENTS

1.	Capacity	6000 Lbs. (2730 Kg) at 24 inches (610 mm) load center
2.	Collapsed mast height	68 inches (1730mm) (maximum)
3.	Fork height	100 inches (2540mm) (minimum)
4.	Free lift height	42 inches (1070mm) (minimum)
5.	Fork size	2.06 in. thick (50mm) (maximum) 6.06 in wide (150mm) (maximum) 36 in. (910mm) long + 0.25 in. (6mm) -0.5 in. (12mm)
6.	Fork spacing (measured between outer edges of forks) :	40 inch (1020mm) spread (minimum) 14 inches (360mm) together (maximum)
7.	Static overhead guard test load	11,000 Lbs. (5000Kg)
8.	Overhead guard height	91 inches (2310mm) (maximum)
9.	Tangential steering force at rim of hand wheel	150 Lbs. (670N) for nonpower and 25Lb (11 ON) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100mm) when side shifter attachment is used)	156 inches (3960mm)
11.	Lifting speed	25 feet (8m) per minute (minimum)
12.	Lower speed	27 feet (8m) per minute (minimum)
13.	High drive speed	3.5 - 4.5 miles (6-7Km) per hour
14.	Slope ascension	26.8 percent slope (15 degrees)
15.	Longitudinal stability - stacking	6 percent slope (3.4 degrees)
	traveling	26.8 percent slope (15 degrees)
16.	Lateral. stability -- stacking	9 percent slope (5.2 degrees)
	traveling	40 percent slope (21.8 degrees)
17.	Service brakes	4 wheels
18.	Parking brakes	Hand brake required

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.

19.	Overall truck width	44 inches (l120mm) (maximum)
20.	Upright Tilt: forward	(2 degrees +/-0.5 degree)
	rearward	(6.5 degrees +/- 0.5 degree)
21.	Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 15367.	
22.	Siped tires, folding forks, weighing device, and sideshift attachment are required.	
23.	Overall maximum length measured from the forward portion of the heel of the fork to the rear extreme of this truck.	110 inches (2800mm)
24.	Overall maximum weight of truck with battery	11,500 Lbs. (5220 Kg)

FSC 3930

Custodian:

Navy - SA

Preparing Activity:

Navy SA

Review Activities:

Navy - SH, OS,

Project No.

3930-0644-3

User Activities:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.