MIL-T-21869/27D
13 Janaury 1984
SUPERSEDING
MIL-T-21869/27C
17 March 1974

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES, 6,000 POUND CAPACITY, 127 INCH LIFT, ASHORE, TYPE "EX"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For, dated 13 January 1984.

REQUIREMENTS

1.	Capacity	6,000 Lbs. at 24 inches load center
2.	Type	EX
3.	Collapsed mast height	83 inches (maximum)
4.	Fork height	127 inches (minimum)
5.	Free lift height	57 inches (minimum)
6.	Fork mounting	MS-16956
7.	Fork size	2 1/16" thick (maximum) 6 1/16" wide (maximum) 40" long + 1/4" - 1/2"
8.	Fork spacing	40" spread (minimum)
9.	Static overhead guard test load	11,000 Lbs.
10.	Overhead guard height	91 inches (maximum)
11.	Type of steering	Power
12.	Tangential steering force at rim of hand wheel	150 Lbs.
13.	Right angle turn, dimension "A" (add 4 inches when side shifter attachment is used)	156 inches
14.	Lifting speed	20 feet per minute (minimum)
15.	Lowering speed	27 feet per minute (minimum)
16.	High drive speed	3 1/2 to 4 1/2 miles per hour
17.	Slope ascension	15 percent slope (8.5 degrees)
18.	Stability shall be in accordance with ANSI B56.1	
19.	Service brakes	4 wheels
20.	Overall truck width	44 inches (maximum)
21.	Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 16974.	

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.

MIL-T-21869/27D

Custodian:

Navy - SA

Review Activities:

Navy - OS

Preparing Activity:

Navy - SA

Project No. 3920-0518

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.