MIL-T-21869/32F
1 December 1989
SUPERSEDING
MIL-T-21869/32E
13 January 1984

MILITARY SPECIFICATIONS

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

4,000 POUND (1820 KILOGRAMS) CAPACITY, 100 INCH (2540 MILLIMETERS) LIFT,

SHIPBOARD, TYPE "EX"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specdification For.

1.	Capacity	4,000 Lbs. (1820 Kg) at 24 inchs (610mm) load center
2.	Collapsed mast height	68 inches (1730mm) (maximum)
3.	Fork height	100 inches (2540mm) (minimum)
4.	Free lift height	42 inches (1070mm) (minmum)
5.	Fork size	2.25 in. (60mm) thick (maximum) 5.5 in. (140 Omm) wide (maximum) 40 in. (1020 Omm long + 0.25 in. (6mm) -0.5 in. (12mm)
6.	Fork spacing (measured between outer edges of forks):	40 inch (1020mm) spread (minimum) 14 in. (360mm) together (maximum)
7.	Static overhead guard test load	8,000 Lbs. (3640 Kg.)
8.	Overhead guard height	91 inches (2310mm) (maximum)
9.	Tangential steering force at rim of hand Wheel	150 Lbs. (570N} for nonpower and 25 Lbs. (110N) for Power steering
10.	Right angle turn, dimension "A" (add 4 inches (100mm) when side shifter attachment is used)	148 inches (3760mm)
11.	Lifting speed	25 feet (8m) per minute (minimum)
12.	Lowering speed	27 feet (8m) per minute (minimum)
13.	High drive speed	3.5 to 4.5 miles (6 to 7 kilometers per hour
14.	Slope ascension	26.8 percent slope (15 degrees) 6 percent slope (3.4 degrees)
15.	Longitudinal stability - stacking traveling	26.8 percent slope (15 degrees) 9 percent slow (5.2 degrees)
16.	Lateral stability - stacking traveling	40 percent slope (21.8 degrees)
17.	Service brakes	4 wheels
18.	Parking brakes	Hand brake requirement
19.	Overall truck width	44.5 inches (1130mm) (maximum)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.

20.	Upright tilt: Forward	(2 degrees ± 0.5 degree)
	Rearward	(6.5 degrees + 0.5 degree)
21.	Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 16974.	
22.	Siped tires, folding forks, weighing device, and side shift attachment are required	
23.	Overall maximum length measured from the forward portion of the heel of the fork to the rear extreme of the truck.	96 inches (2440mm)
24.	Overall maximum weight of truck with battery.	11,500 Lbs. (5220Kg.)

FSC 3930

Custodian:

Navy - SA

Preparing Activity:

Navy - SA

Review Activities:

Project No.

3930-0644-4

Navy - OS, SH,

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:37Z
Check the source to verify that this is the current version before use.