INCH-POUND

MIL-T-21869/38F
1 December 1989
SUPERSEDING
MIL-T-21869/38E
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

4,000 POUND (1820 KILOMETERS) CAPACITY, 144 INCH (3660 MILLIMETERS) LIFT

GENERAL PURPOSE, TYPE "EE"

TRIPLE STAGE MAST

The complete requirements for procuring this truck described herein shall consist of this document and Specifcaiton MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For.

REQUIREMENTS

1.	Capacity	4,000 Lbs. (1820 Kg.) at 24 inches (610mm) load center
2.	Collapsed mast height	84 inches (2130m) (maximum)
3.	Fork height	144 inches (3660mm) (minimum)
4.	Free lift height	42 inches (1100mm) (minimum)
5.	Fork size	1.8 in. (50mm) thick (maximum) 5.06 in. (130mm) wide (maximum) 40 in. (1020mm long + 0" (0mm) -1/2 in. (12mm)
6.	Fork spacing (measured between outer edges of forks):	38 inch (970mm) spread (minimum) 12 inches (300mm) together (maximum)
7.	Static overhead guard test load	8,000 Lbs. (3640Kg.)
8.	Overhead guard height	84 inchs (2130mmn) (maximum)
9.	Tangential steering force at rim of hand wheel	150 Lbs. (670N) for nonpwer and 25 Lbs. (110N) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100mm) when side shifter attachment is used)	142 inches (3610mm)
11.	Lifting speed	25 feet (8m) per minute (minimum)
12.	Lowering speed	27 feet (8m) per minute (minimum)
13.	High drive speed	5 to 8 miles (8 to 13 kilometers) per hour
14.	Slope ascension	15 percent slope (8.5 degrees)
15.	Stability to be in accordance with ANSI B56.1	
16.	Upright tilt: Forward Rearward	(2 degrees +/-0.5 degree) (6.5 degrees +/-0.5 degree)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:38Z
Check the source to verify that this is the current version before use.