INCH-POUND

MIL-T-21869/39F
01 DECEMBER 1989
SUPERSEDING
MIL-T-21869/39E
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

6,000 POUND (2720 KILOGRAM) CAPACITY, 180 INCH (4570 MILLIMETER) LIFT.,

GENERAL PURPOSE, TYPE "E"

TRIPLE STAGE MAST

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For.

REQUIREMENTS

1.	Capacity	6,000 Lbs. (2720 Kg.) at 24 inch (610mm) load center
2.	Collapsed mast height	84 inches (2130mm) (maximum)
3.	For k height	180 inches (4570mm) (minimum)
4.	Free lift height	53 inches (1350mm) (minimum)
5.	Fork size	2.06 in. (50mm) thick (maximun) 6.06 in. (150mm) wide (maximum) 40 in. 1020mm) long + 0" (0mm) -0.5 in. (12mm)
6.	Fork spacing (measured between outer edges of forks):	40 inch (1020mm) spread (minimum) 14 inches (360mm) together (maximum)
7.	static overhead guard test load	11,000 Lbs. (5000Kg)
8.	Overhead guard height	91 inches (2240mm) (maximum)
9.	Tangential steering force at rim of hand wheel	150 Lbs. (670N) for nonpwer and 25 Lbs. (110N) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100mm) when side shifter attachment is used)	156 inches (4000mm)
11.	Lifting speed	18 feet (6m) per minute (minimum)
12.	Lowering speed	27 feet (8m) per minute (minimun)
13.	High drive speed	5 to 8 miles (8 to 13 kilometers) per hour
14.	Slope ascension	15 percent slope (8.5 degrees)
15.	Stability to be in accordance with ANSI B56.1	
16.	Upright tilt: Forward	(2 degrees +/-0.5 degree)
	Rearward	(6.5 degrees +/-0.5 degree)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:38Z
Check the source to verify that this is the current version before use.