INCH-POUND

MIL-T-21869/51E
01 DECEMBER 1989
SUPERSEDING
MIL-T-21869/51D
13 January 1984

MILITARY SPECIFICATION SHEET

TRUCK, LIFT, FORK, ELECTRIC, SOLID TIRES,

10,000 POUND (4540 KILOGRAM) CAPACITY, 110 INCH (2800 MILLIMETER) LIFT,

TYPE "EE"

The complete requirements for procuring this truck described herein shall consist of this document and Specification MIL-T-21869, Trucks, Lift, Fork, Electric, Sit-Down, Front Wheel Drive, Rear Wheel Steer, General Specification For, dated 13 January 1984.

REQUIREMENTS

1.	Capacity	10,000 Lbs. (4540mm) at 24 inches (610mm) load center
2.	Collapsed mast height	91 inches (2310mm) (maximum)
3.	Fork height	110 inches (2800mm) (minimum)
4.	Free lift height	48 inches (1220mm) (minimum)
5.	Fork size	2.56 in. (70mm) thick (maximum) 7.56 in. (190mm) wide (maximum) 40 in. (1020mm) long + 0" (0mm) -1/2 in. (12mm)
6.	Fork spacing	42 in. (110mm) spread (minimum)
7.	Static overhead guard test load	15,000 Lbs. (6810 Kg)
8.	Overhead guard height	91 inches (2310mm) (maximum)
9.	Tangential steering force at rim of hand wheel	150 Lbs. (670N) for nonpower and 25 Lbs (110N) for power steering
10.	Right angle turn, dimension "A" (add 4 inches (100mm) when side shifter attachment is used)	163 inches (410mm)
11.	Lifting speed	12 feet (4m) per minute (minimum)
12.	Lowering speed	27 feet (8m) per minute (minimum)
13.	High drive speed	4 miles 6.4 (kilometers) per hour (minimum)
14.	Slope ascension	15 percent slope (8.5 degrees
15.	Stability in accordace with ANSI B 56.1	
16.	Upright tilt: Forward	(3 degrees +/- 0.5 degree)
	Rearward	(8 degrees +/- 0.5 degree)

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:38Z
Check the source to verify that this is the current version before use.

17. Battery well is required. Dimensions shall be determined from MIL-T-21869 and MS 15367 for one or two each batteries.

Custodian:

Navy -SA

Army - ME

Preparing Activity:

Navy - SA

Project No.

3930-0644-9

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T10:38Z
Check the source to verify that this is the current version before use.